

MATERIAL SAFETY DATA SHEET

### S2240 SCARLET NM

Version Number 1.0 Revision Date 06/19/2002 Page 1 of 6 Print Date 11/5/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	S2240 SCARLET NM
Product code	:	FO00006887
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Diatomaceous earth	61790-53-2	1 - 5
Titanium dioxide	13463-67-7	1 - 5

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET

# S2240 SCARLET NM

sion Date 06/19/2002	Print Date 11/5/2
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases of doubt, seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available.
Flammable Limits Upper explosion limit Lower explosion limit	<ul><li>No data available.</li><li>No data available.</li></ul>
Autoignition temperature Suitable extinguishing media	<ul> <li>Not applicable.</li> <li>Carbon dioxide blanket, dry powder, foam, Water spray.</li> </ul>
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	<ul> <li>May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binde universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing





# S2240 SCARLET NM

sion Number 1.0 vision Date 06/19/2002			Print	Page 3 o Date 11/5/20	
	Р	ume condensates may contain of reriodically clean hoods, ducts, ccumulation of these materials	and other surfaces to mi		
Storage		Leep containers dry and tightly nd contamination. Store in a c		e absorption	
8. H	EXPOSURE	CONTROLS / PERSONAL	PROTECTION		
Respiratory protection	: U	Under normal handling condition	ons a respirator may not l	be required.	
Eye/Face Protection	: S	afety glasses with side-shields.			
Hand protection	: Protective gloves.				
Skin and body protection	: L	Long sleeved clothing.			
Additional Protective Measures	: S	afety shoes.			
General Hygiene Considerations		Iandle in accordance with good Vash hands before breaks and a		afety practice.	
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)					
Components	Value	Exposure time	Exposure type	List:	
Diatomaceous earth	10 mg/m3	Time Weighted Average (TWA):	Inhalable dust.	ACGIH	
		/ ·		t	

Diatomaccous cartin	(TWA):		militable dust.	Medin
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	ACGIH
Diatomaceous earth	20 mppcf	PEL:	Total dust.	Z3
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1

### 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- : Liquid
  : Viscous, Liquid
  : RED
  : Very faint
  : Not applicable
  : Not applicable
  : Immiscible
- Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH
- Not established
  Not determined
  Not applicable.
  Not determined
  Not determined
  Not applicable.
- 10. STABILITY AND REACTIVITY



#### MATERIAL SAFETY DATA SHEET

# S2240 SCARLET NM

Version Number 1.0 Revision Date 06/19/2002 Page 4 of 6 Print Date 11/5/2011

Stability	: S	table.
Hazardous Polymerization	: W	/ill not occur.
Conditions to avoid		eep away from oxidizing agents and open flame. To avoid thermal ecomposition, do not overheat.
Incompatible Materials		acompatible with strong acids and oxidizing agents. Avoid contact ith acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	(f sı da af	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen NOx), hydrogen chloride (HCl), other hazardous materials, and noke are all possible. Prolonged heating may result in product egradation. As a general rule of thumb, degradation begins to occur fter one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	C	hemical Name	Effect	Target Organ		
61790-53-2	Diaton	naceous earth	Irritant	Eyes, Respiratory system.		
13463-67-7	Titaniu	ım dioxide	Systemic effects	Respiratory system.		
		12. ECOLOGIO	CAL INFORMATION	N		
Persistence and degradability		: Not readily b	: Not readily biodegradable.			
Environmental Toxicity		: Environmental toxicity has not been established for this mixture as a whole.				
Bioaccumulation Potential		: No data avail	No data available.			
Additional advice		: No data avail	No data available.			
		13. DISPOSAL	CONSIDERATIONS	5		
Product		generator of v classification	Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
Contaminated packaging				e. The generator of waste material ste classification, transportation		



MATERIAL SAFETY DATA SHEET

# S2240 SCARLET NM

Version Number 1.0 Page 5 of 6 Revision Date 06/19/2002 Print Date 11/5/2011 and disposal in accordance with applicable federal, state/provincial and local regulations. **14. TRANSPORT INFORMATION** U.S. D.O.T. / CA T.D.G. : Not regulated for transportation. Classification (Non-bulk ground) ICAO/IATA Not regulated for transportation. : IMO / IMDG Not regulated for transportation. : **15. REGULATORY INFORMATION US Regulations: OSHA Status** Classified as hazardous based on components. · All components of this product are listed on the TSCA inventory or are **TSCA Status** : exempt. US. EPA CERCLA Hazardous Substances (40 CFR 302) Not applicable **California Proposition** : WARNING! This product contains a chemical known in the State of 65 California to cause cancer. Not applicable Canadian Regulations: WHMIS Classification : D2B WHMIS Ingredient Disclosure List CAS-No. 1344-28-1 7631-86-9 101-02-0 108-05-4 1314-23-4 75-01-4 DSL : Listed.



### MATERIAL SAFETY DATA SHEET

## S2240 SCARLET NM

Version Number 1.0 Revision Date 06/19/2002		Page 6 of 6 Print Date 11/5/2011	
National Inventories:			
Australia AICS	:	Listed.	
China IECS	:	Not determined.	
Europe EINECS	:	Not determined.	
Japan ENCS	:	Not determined.	
Korea KECI	:	Listed.	
Philippines PICCS	:	Not determined.	
16. OTHER INFORMATION			

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.