

MATERIAL SAFETY DATA SHEET

# S230NV PW NAVY

Version Number 1.0 Revision Date 06/11/2002 Page 1 of 7 Print Date 11/4/2011

# 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	S230NV PW NAVY
Product code	:	FO00006892
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
1,2-Benzenedicarboxylic acid, butyl	85-68-7	30 - 60
phenylmethylester		
Carbon black	1333-86-4	0.1 - 1
Diatomaceous earth	61790-53-2	1 - 5

# **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

S230NV PW NAVY





#### Version Number 1.0 Page 2 of 7 Revision Date 06/11/2002 Print Date 11/4/2011 **Medical Conditions** : None known. Aggravated by Exposure: 4. FIRST AID MEASURES Inhalation Move to fresh air in case of accidental inhalation of fumes from : overheating or combustion. When symptoms persist, or in all cases of doubt, seek medical advice. Ingestion : Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice. Rinse immediately with plenty of water for at least 15 minutes. If eye Eyes : irritation persists, seek medical attention. Skin Wash off with soap and plenty of water. If skin irritation persists seek : medical attention. **5. FIRE-FIGHTING MEASURES** Flash point No data available. : Flammable Limits Upper explosion limit : No data available. Lower explosion limit No data available. : Autoignition temperature : Not applicable. Suitable extinguishing media Carbon dioxide blanket, dry powder, foam, Water spray. : Special Fire Fighting : Fullface self-contained breathing apparatus (SCBA) used in positive Procedures pressure mode should be worn to prevent inhalation of airborne contaminants. Unusual Fire/Explosion : May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under Hazards fire conditions. 6. ACCIDENTAL RELEASE MEASURES Personal precautions Wear appropriate personal protection during cleanup, such as : impervious gloves, boots and coveralls. Should not be released into the environment. The product should not Environmental precautions : be allowed to enter drains, water courses or the soil. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, Methods for cleaning up : universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

#### 7. HANDLING AND STORAGE





# S230NV PW NAVY

Version Number 1.0 Revision Date 06/11/2002		Page 3 of 7 Print Date 11/4/2011
Handling	:	Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.
8. EXPOSI	UF	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	Under normal handling conditions a respirator is not required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Carbon black	3.5 mg/m3	Time Weighted Average	Total dust. as carbon	ACGIH
		(TWA):	black	
Carbon black	3.5 mg/m3	PEL:	Total dust. as carbon	OSHA Z1
			black	
Diatomaceous earth	10 mg/m3	Time Weighted Average	Inhalable dust.	ACGIH
		(TWA):		
	3 mg/m3	Time Weighted Average	Respirable dust.	ACGIH
		(TWA):		
Diatomaceous earth	20 mppcf	PEL:	Total dust.	Z3

## 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- : Liquid
  : Viscous, Liquid
  : BLUE
  : Very faint
  : Not applicable
  : Not applicable
  : Immiscible
- Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH
- Not established
  Not determined
  Not applicable.
  Not determined
  Not determined
  Not determined
  Not applicable.



#### MATERIAL SAFETY DATA SHEET

# S230NV PW NAVY

Version Number 1.0 Revision Date 06/11/2002 Page 4 of 7 Print Date 11/4/2011

	10. STABILITY AND REACTIVITY
Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
85-68-7	1,2-Benzenedicarboxylic	Irritant	Eyes, Skin.
	acid, butyl		
	phenylmethylester		
		Systemic effects	Liver, reproductive system.
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
61790-53-2	Diatomaceous earth	Irritant	Eyes, Respiratory system.

#### LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
85-68-7	1,2-Benzenedicarboxylic	Oral LD50	2,330 mg/kg	rat
	acid, butyl	Dermal LD50	>10 gm/kg	rabbit
	phenylmethylester			
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:



MATERIAL SAFETY DATA SHEET

# S230NV PW NAVY

Revision Date 06/11/2002

Version Number 1.0

Page 5 of 7 Print Date 11/4/2011

CAS-No.	Chemical Name	OSHA	IARC	NTP
1333-86-4	Carbon black	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

#### Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

#### **12. ECOLOGICAL INFORMATION**

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: No data available.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. D.O.T. / CA T.D.G.	: Not regulated for transportation.



#### MATERIAL SAFETY DATA SHEET

# S230NV PW NAVY

Version Number 1.0 Revision Date 06/11/2002				Page 6 of Print Date <i>11/4/201</i>
Classification (Non-bulk ground)				
ICAO/IATA	: Not reg	gulated for transpo	ortation.	
IMO / IMDG	: Not reg	gulated for transpo	ortation.	
	15. REGU	LATORY INFO	RMATION	
US Regulations:				
OSHA Status	: Classif	ïed as hazardous l	based on components.	
TSCA Status	: All cor exemp		roduct are listed on the	e TSCA inventory or are
US. EPA CERCLA Hazard	ous Substances (	(40 CFR 302)		
Chemical Name	CAS-No.	% in Product	RQ for component	RQ for Mixture/Product
1,2-Benzenedicarb oxylic acid, butyl	85-68-7	31.04	100lbs	322 LB

California Proposition : WARNING! This product contains a chemical known in the State of California to cause cancer.

Not applicable Canadian Regulations:

phenylmethylester

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
1344-28-1	
1333-86-4	
12239-87-1	
7631-86-9	
101-02-0	
108-05-4	
1314-23-4	
85-68-7	
75-01-4	

DSL

: Listed.

### MATERIAL SAFETY DATA SHEET

# S230NV PW NAVY

Version Number 1.0 Revision Date 06/11/2002 Page 7 of 7 Print Date 11/4/2011

vUne.

National Inventories:

Australia AICS	: Listed.
China IECS	: Listed.
Europe EINECS	: Not determined.
Japan ENCS	: Not determined.
Korea KECI	: Listed.
Philippines PICCS	: Not determined.

# **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.