PolvOne

MATERIAL SAFETY DATA SHEET **S3920 FLO RED HS**

Version Number 1.1 Revision Date 04/14/2009

Page 1 of 7 Print Date 1/7/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	S3920 FLO RED HS
Product code	:	FO00006979
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Azodicarbonamide	123-77-3	1 - 5
Titanium dioxide	13463-67-7	0.1 - 1
Calcium carbonate	1317-65-3	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye and skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET **S3920 FLO RED HS**

Version Number 1.1 Revision Date 04/14/2009 Page 2 of 7 Print Date 1/7/2012

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 No data available No data available Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE

POLYONE CORPORATION

PolyOne.

MATERIAL SAFETY DATA SHEET **S3920 FLO RED HS**

Version Number 1.1 Revision Date 04/14/2009		Page 3 of 7 Print Date 1/7/2012
	:	Heat only in areas with appropriate exhaust ventilation. Processing
		fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.
8. EXPOS	SUI	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average		MX OEL
		(TWA):		
	20 mg/m3	Short Term Exposure Limit		MX OEL
		(STEL):		
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average	Total dust.	OSHA Z1A
		(TWA):		
	10 mg/m3	Time Weighted Average	as Ti	MX OEL
		(TWA):		
	20 mg/m3	Short Term Exposure Limit	as Ti	MX OEL
	_	(STEL):		

9. PHYSICAL AND CHEMICAL PROPERTIES

PolyOne

MATERIAL SAFETY DATA SHEET S3920 FLO RED HS

Version Number 1.1 Revision Date 04/14/2009

Page 4 of 7 Print Date 1/7/2012

Form Appearance Color Odour Melting point/range Boiling Point: Water solubility	 liquid Viscous, liquid RED Very faint Not applicable Not applicable Immiscible 	Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH	 Not established Not determined Not applicable Not determined Not determined Not applicable
	10. STABILITY ANI	D REACTIVITY	
Stability	: Stable.		
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from ox decomposition, do	idizing agents and open fl not overheat.	ame. To avoid thermal
Incompatible Materials		strong acids and oxidizing plymers and acetal copolyr	
Hazardous decomposition products	(NOx), hydrogen cl smoke are all possi degradation. As a g after one hour at 17	D2), carbon monoxide (CC hloride (HCl), other hazard ble. Prolonged heating ma general rule of thumb, deg 7°C (350°F), after 10 mi inutes at 232°C (450°F).	lous materials, and ay result in product radation begins to occur nutes at 204 °C (400

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
123-77-3	Azodicarbonamide	sensitizer	Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory
			system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
123-77-3	Azodicarbonamide	LC50	200 mg/l	rat
		Oral LD50	> 6,400 mg/kg	rat
		Dermal LD50	> 2,000 mg/kg	rabbit

MATERIAL SAFETY DATA SHEET **S3920 FLO RED HS**

Version Number 1.1

Revision Date 04/14/2009

Page 5 of 7 Print Date 1/7/2012

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Azodicarbonamide 123-77-3 Sensitizer to the respiratory system with repeated minimal inhalation. While no chronic health problems have been identified, individuals with respiratory problems should avoid inhalation exposure to this material.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: No data available
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.

		Pc	olyOne.	
LYONE CORPORATION				
TERIAL SAFETY DATA SHEET				
920 FLO RED HS				
sion Number 1.1 ision Date 04/14/2009			Pag Print Date 1	ge 6 1/7/2
IMO / IMDG (maritime) : Refer to specific	c regulation.			
15. REGULATOR	Y INFORM	ATION		
US Regulations:				
OSHA Status : Classified as ha	zardous base	l on component	ts.	
TSCA Status : All components TSCA Inventory		uct are listed on	n or exempt from the	
US. EPA CERCLA Hazardous Substances (40 CFR 3	302)			
Not applicable				
California Proposition : Not applicable 65 SARA Title III Section 302 Extremely Hazardous Su	bstance			
Unless specific chemicals are identified under this se Chemical Name CAS	^	oduct is Not Ap % in Product	RQ for component	gula
SARA Title III Section 313 Toxic Chemicals: Unless specific chemicals are identified under this se Canadian Regulations: National Pollutant Release Inventory (NPRI)				gula
Chemical Name Zinc oxide	CAS-No. 1314-13-2	0.10 - 1		
2-[6-(ethylamino)-3-(ethylimino)-2,7-dimethyl- 3H-xanthine-9-yl] benzoic acid ethyl ester monohydrochloride (C.I. basic red 1)	989-38-8	0.10 - 1		
WHMIS Classification : D2A WHMIS Ingredient Disclosure List CAS-No.				

PolyOne.

MATERIAL SAFETY DATA SHEET S3920 FLO RED HS

Version Number 1.1 Revision Date 04/14/2009 Page 7 of 7 Print Date 1/7/2012

112945-52-5 DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:		
Australia AICS	:	Not determined
China IECS	:	Not determined
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined
16. OTHER INFORMATION		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.