MATERIAL SAFETY DATA SHEET **S4601 BLUE GS SP HO**

Version Number 1.1 Revision Date 02/14/2007

Page 1 of 6 Print Date 11/26/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone number	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	S4601 BLUE GS SP HO
Product code	:	FO00007033
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5
Calcium carbonate	1317-65-3	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne.

MATERIAL SAFETY DATA SHEET **S4601 BLUE GS SP HO**

Version Number 1.1 Revision Date 02/14/2007 Page 2 of 6 Print Date 11/26/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 No data available No data available Not applicable Carbon dioxide blanket, water spray, dry powder, foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing



MATERIAL SAFETY DATA SHEET **S4601 BLUE GS SP HO**

Version Number 1.1 Revision Date 02/14/2007 Page 3 of 6 Print Date 11/26/2011

fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.

Storage

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average		MX OEL
		(TWA):		
	20 mg/m3	Short Term Exposure Limit		MX OEL
		(STEL):		
Silica, amorphous,	20 mppcf	PEL:	Total dust.	Z3
fumed, crystal-free				
	0.8 mg/m3	Time Weighted Average		Z3
		(TWA):		
	10 mg/m3	Time Weighted Average	Inhalable particulate.	MX OEL
		(TWA):		
	3 mg/m3	Time Weighted Average	Respirable dust.	MX OEL
		(TWA):		

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color : liquid: Viscous, liquid: BLUE

Evaporation rate Specific Gravity: Bulk density Not establishedNot determinedNot applicable

PolyOne.

MATERIAL SAFETY DATA SHEET **S4601 BLUE GS SP HO**

Version Number 1.1 Revision Date 02/14/2007

_

Page 4 of 6 Print Date 11/26/2011

Odor Melting point/range Boiling Point: Water solubility	: N : N	ery faint ot applicable ot applicable nmiscible	Vapor pressure Vapour density pH	: : :	Not determined Not determined Not applicable
	1(). STABILITY AND RE	CACTIVITY		
Stability	:	Stable.			
Hazardous Polymerization	:	Will not occur.			
Conditions to avoid	:	Keep away from oxidizide decomposition, do not o		me.	To avoid thermal
Incompatible Materials	:	Incompatible with stron with acetal homopolyme			
Hazardous decomposition products	:	Carbon dioxide (CO2), (NOx), hydrogen chlorid smoke are all possible. degradation. As a gener after one hour at 177 °C and within 5 minutes at	de (HCl), other hazardo Prolonged heating may cal rule of thumb, degra (350 °F), after 10 minu	ous res dat	materials, and sult in product ion begins to occur

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
112945-52-5	Silica, amorphous, fumed, crystal-free	Irritant	Eyes, Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
112945-52-5	Silica, amorphous, fumed, crystal-free	Oral LD50	3,160 mg/kg	rat

12. ECOLOGICAL INFORMATION

Persistence and degradability

: Not readily biodegradable.

Environmental Toxicity

: Environmental toxicity has not been established for this mixture as a

PolyOne.

MATERIAL SAFETY DATA SHEET **S4601 BLUE GS SP HO**

Version Number 1.1 Revision Date 02/14/2007 Page 5 of 6 Print Date 11/26/2011

Bioaccumulation Potential	: No data available
Bioaccumulation Potential	
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. T generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste mater has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSC Inventory.
US. EPA CERCLA Hazardou	Substances (40 CFR 302)
Not applicable	
California Proposition 65	: Not applicable
SARA Title III Section 302 E	tramaly Hazardova Substance

PolyOne

MATERIAL SAFETY DATA SHEET S4601 BLUE GS SP HO

Version Number	er 1.1
Revision Date	02/14/2007

Page 6 of 6 Print Date 11/26/2011

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

Phthalocyanine blue			CAS-No.	Weight %	NPRI ID#
			147-14-8	1.00 - 5.00	71
WHMIS Classification	:	Not controlled.			
DSL	:	-	s of this product (DSL) or are exe	are on the Canadia empt.	n Domestic
tional Inventories:					
Australia AICS	:	Not determined			
China IECS	:	Not determined			
Europe EINECS	:	Listed			
Japan ENCS	:	Not determined			
Korea KECI	:	Not determined			
Philippines PICCS	:	Not determined			

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.