

# MATERIAL SAFETY DATA SHEET

# S495BSBK STRONG BLACK HS

Version Number 1.0 Revision Date 06/04/2003 Page 1 of 7 Print Date *11/11/2011* 

# 1. PRODUCT AND COMPANY IDENTIFICATION

### POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	S495BSBK STRONG BLACK HS
Product code	:	FO00007056
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Azodicarbonamide	123-77-3	1 - 5
Quartz	14808-60-7	0.1 - 1
Carbon black	1333-86-4	1 - 5
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5
Calcium carbonate	1317-65-3	10 - 30

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.



# MATERIAL SAFETY DATA SHEET

# S495BSBK STRONG BLACK HS

Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions	: None known.
Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases or doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available.
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>No data available.</li> <li>No data available.</li> <li>Not applicable.</li> <li>Carbon dioxide blanket, dry powder, foam, Water spray.</li> </ul>
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



# MATERIAL SAFETY DATA SHEET

# S495BSBK STRONG BLACK HS

Version Number 1.0 Revision Date 06/04/2003	Page 3 of 7 Print Date 11/11/2011
Handling :	Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
Storage :	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.
8. EXPOSU	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection :	Under normal handling conditions a respirator may not be required.
Eye/Face Protection :	Safety glasses with side-shields.
Hand protection :	Protective gloves.
Skin and body protection :	Long sleeved clothing.
Additional Protective : Measures	Safety shoes.
General Hygiene : Considerations	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures :	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	10 mg/m3	Time Weighted Average	Total dust.	ACGIH
		(TWA):		
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Carbon black	3.5 mg/m3	Time Weighted Average	Total dust. as carbon	ACGIH
		(TWA):	black	
Carbon black	3.5 mg/m3	PEL:	Total dust. as carbon	OSHA Z1
			black	
Quartz	0.05	Time Weighted Average	Respirable dust.	ACGIH
	mg/m3	(TWA):		
Quartz	0.05	Time Weighted Average		ACGIH
	mg/m3	(TWA):		
Quartz	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Silica, amorphous,	20 mppcf	PEL:	Total dust.	Z3
fumed, crystal-free				

# 9. PHYSICAL AND CHEMICAL PROPERTIES

# MATERIAL SAFETY DATA SHEET

# S495BSBK STRONG BLACK HS

Version Number 1.0 Revision Date 06/04/2003

Form

Color

Odor

Appearance

**Boiling Point:** 

Water solubility

R	bly	One	
	-		

: Liquid : Viscous, Liquid : BLACK : Very faint : Not applicable Melting point/range : Not applicable pН : Immiscible

Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density

Not established : Not determined : : Not applicable. : Not determined : Not determined : Not applicable.

Print Date 11/11/2011

Page 4 of 7

	10	. STABILITY AND REACTIVITY	
Stability	:	Stable.	
Hazardous Polymerization	:	Will not occur.	
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.	
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.	
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).	

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
123-77-3	Azodicarbonamide	sensitizer	Respiratory system.
14808-60-7	Quartz	Systemic effects	Eyes, Respiratory system.
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
112945-52-5	Silica, amorphous, fumed, crystal-free	Irritant	Eyes, Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

### LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species



### MATERIAL SAFETY DATA SHEET

# S495BSBK STRONG BLACK HS

Version Number 1.0 Revision Date 06/04/2003 Page 5 of 7 Print Date 11/11/2011

123-77-3	Azodicarbonamide	LC50	200 mg/l	rat
		Oral LD50	> 6,400 mg/kg	rat
		Dermal LD50	> 2,000 mg/kg	rabbit
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit
112945-52-5	Silica, amorphous, fumed,	Oral LD50	3,160 mg/kg	rat
	crystal-free			

#### Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1333-86-4	Carbon black	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

### Additional Health Hazard Information:

Azodicarbonamide 123-77-3 Sensitizer to the respiratory system with repeated minimal inhalation. While no chronic health problems have been identified, individuals with respiratory problems should avoid inhalation exposure to this material.

#### Additional Health Hazard Information:

Quartz 14808-60-7 This material in its free releasable form may cause respiratory tract irritation, and possibly silicosis which is a scarring of the lungs.

### Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

12. ECOLOGICAL INFORMATION			
: Not readily biodegradable.			
: Environmental toxicity has not been established for this mixture as a whole.			



MATERIAL SAFETY DATA SHEET

# S495BSBK STRONG BLACK HS

Version Number 1.0 Revision Date 06/04/2003 Page 6 of 7 Print Date 11/11/2011

Bioaccumulation Potential	:	No data available.
Additional advice	:	No data available.
	13	8. DISPOSAL CONSIDERATIONS
Product	:	Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	:	Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	1	4. TRANSPORT INFORMATION
U.S. DOT Classification	:	Refer to specific regulation.
ICAO/IATA	:	Refer to specific regulation.
IMO / IMDG	:	Refer to specific regulation.
	15	. REGULATORY INFORMATION
US Regulations:	15	. REGULATORY INFORMATION
US Regulations: OSHA Status	15 :	Classified as hazardous based on components.
-	15 : :	
OSHA Status	:	Classified as hazardous based on components. All components of this product are listed on or exempt from the TSCA Inventory.
OSHA Status TSCA Status	:	Classified as hazardous based on components. All components of this product are listed on or exempt from the TSCA Inventory.
OSHA Status TSCA Status US. EPA CERCLA Hazardou	:	Classified as hazardous based on components. All components of this product are listed on or exempt from the TSCA Inventory.
OSHA Status TSCA Status US. EPA CERCLA Hazardou	: : 15 Subs	Classified as hazardous based on components. All components of this product are listed on or exempt from the TSCA Inventory.
OSHA Status TSCA Status US. EPA CERCLA Hazardou Not applicable California Proposition	: is Subs	Classified as hazardous based on components. All components of this product are listed on or exempt from the TSCA Inventory. stances (40 CFR 302) WARNING! This product contains a chemical known to the State of California to cause cancer.
OSHA Status TSCA Status US. EPA CERCLA Hazardou Not applicable California Proposition 65	: is Subs	Classified as hazardous based on components. All components of this product are listed on or exempt from the TSCA Inventory. stances (40 CFR 302) WARNING! This product contains a chemical known to the State of California to cause cancer.
OSHA Status TSCA Status US. EPA CERCLA Hazardou Not applicable California Proposition 65 SARA Title III Section 302 E	: is Subs	Classified as hazardous based on components. All components of this product are listed on or exempt from the TSCA Inventory. stances (40 CFR 302) WARNING! This product contains a chemical known to the State of California to cause cancer.



MATERIAL SAFETY DATA SHEET

# S495BSBK STRONG BLACK HS

Version Number 1.0 Revision Date 06/04/2003 Page 7 of 7 Print Date *11/11/2011* 

11evision Dale 00/04/2003		1/11/2
SARA Title III Section 313 To	oxic Chemicals:	
Not applicable		
Canadian Regulations:		
WHMIS Classification	: D2A	
WHMIS Ingredient Disc	closure List	
CAS-No. 1333-86-4		
DSL	: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.	,
National Inventories:		
Australia AICS	: Listed.	
China IECS	: Listed.	
Europe EINECS	: Not determined.	
Japan ENCS	: Not determined.	
Korea KECI	: Not determined.	
Philippines PICCS	: Listed.	

# **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.