

MATERIAL SAFETY DATA SHEET

# V1622 LIGHT GRAY

Version Number 1.0 Revision Date 06/11/2002 Page 1 of 6 Print Date 11/5/2011

## 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	V1622 LIGHT GRAY
Product code	:	FO00007646
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	1 - 5

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Skin contact, Ingestion		
Acute exposure			
Inhalation Ingestion Eyes Skin	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Particulates, like other inert materials can be mechanically irritating.</li> <li>Experience shows no unusual dermatitis hazard from routine handling.</li> </ul>		
Chronic exposure Medical Conditions Aggravated by Exposure:	<ul><li>Refer to Section 11 for Toxicological Information.</li><li>None known.</li></ul>		
88 ···································			



MATERIAL SAFETY DATA SHEET

# V1622 LIGHT GRAY

sion Date 06/11/2002	Print Date 11/5/2
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases of doubt, seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not relevant</li> <li>Carbon dioxide blanket, Water spray, dry powder, foam.</li> </ul>
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of

## MATERIAL SAFETY DATA SHEET



#### V1622 LIGHT GRAY Version Number 1.0 Page 3 of 6 Revision Date 06/11/2002 Print Date 11/5/2011 these materials. : Keep containers dry and tightly closed to avoid moisture absorption Storage and contamination. Keep in a dry, cool place. 8. EXPOSURE CONTROLS / PERSONAL PROTECTION : No personal respiratory protective equipment normally required. If Respiratory protection dusty conditions occur wear appropriate respiratory protection. Eye/Face Protection : Safety glasses with side-shields. Hand protection : Protective gloves. Skin and body protection : Long sleeved clothing. Additional Protective Safety shoes. : Measures General Hygiene : Handle in accordance with good industrial hygiene and safety practice. Considerations Wash hands before breaks and at the end of workday. : Heat only in areas with appropriate exhaust ventilation. Provide Engineering measures appropriate exhaust ventilation at machinery. Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Titanium dioxide	10 mg/m3	Time Weighted Average	Total dust.	ACGIH
		(TWA):		
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1

9	. PHYSICAL AND CHE	MICAL PROPERTIES	
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	<ul> <li>Solid</li> <li>powder, granular</li> <li>GREY</li> <li>Very faint</li> <li>Not determined</li> <li>Not applicable</li> <li>Insoluble</li> </ul>	Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH	<ul> <li>Not applicable.</li> <li>Not determined</li> <li>Not determined</li> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> </ul>
	10. STABILITY AN	D REACTIVITY	
Stability	: Stable.		
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: To avoid thermal	decomposition, do not over	heat. Keep away from



#### MATERIAL SAFETY DATA SHEET

# V1622 LIGHT GRAY

Version Number 1.0 Revision Date 06/11/2002		Page 4 of 6 Print Date <i>11/5/2011</i>
		oxidizing agents and open flame.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

#### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

## Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

	1		CAL INFORMATION	J	
	1.	2. ECOLOGIC		<u> </u>	
Persistence and degrada	bility :	Not readily bi	odegradable.		
Environmental Toxicity		: Adverse ecological impact is not known or expected under normal use.			
Bioaccumulation Potential		: No data available.			
Additional advice	:	No data availa	able.		
	1	3. DISPOSAL	CONSIDERATIONS	\$	
Product	:	generator of v classification,	vaste material has the r	ed to disposal or incineration. The esponsibility for proper waste posal in accordance with nd local regulations.	
Contaminated packaging		: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
	]	4. TRANSPO	RT INFORMATION		
U.S. D.O.T. / CA T.D.C Classification (Non-bul		Not regulated	for transportation.		



# MATERIAL SAFETY DATA SHEET

# V1622 LIGHT GRAY

sion Number 1.0 sion Date 06/11/2002		Page 5 Print Date 11/5/2
ICAO/IATA	: Not regulated for transport	tation.
IMO / IMDG	: Not regulated for transport	
	15. REGULATORY INFOR	RMATION
US Regulations:		
OSHA Status	: Classified as hazardous ba	sed on components.
TSCA Status	: All components of this pro exempt.	oduct are listed on the TSCA inventory or are
US. EPA CERCLA Hazardous	Substances (40 CFR 302)	
Not applicable		
California Proposition 65	: WARNING! This product California to cause cancer.	t contains a chemical known in the State of
Canadian Regulations:		
WHMIS Classification	: D2B	
WHMIS Ingredient Dis	closure List	
CAS-No. 1333-86-4 1309-37-1 557-05-1 75-01-4		
DSL	: Listed.	
National Inventories:		
Australia AICS	: Listed.	
China IECS	: Listed.	
Europe EINECS	: Not determined.	
Japan ENCS	: Not determined.	
Korea KECI	: Listed.	

MATERIAL SAFETY DATA SHEET

# V1622 LIGHT GRAY

Version Number 1.0 Revision Date 06/11/2002

Philippines PICCS

: Not determined.

# **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.



Page 6 of 6 Print Date 11/5/2011