

#### MATERIAL SAFETY DATA SHEET

# V194 BRIGHT ORANGE

Version Number 1.0 Page 1 of 7
Revision Date 06/11/2002 Print Date 11/5/2011

## 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION

2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY : Product Stewardship, (314) 771-1800

TELEPHONE

Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure

number or accident).

Product name : V194 BRIGHT ORANGE

Product code : FO00007678 Chemical Name : Mixture CAS-No. : Mixture

Product Use : Industrial Applications

# 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

| Components                            | CAS-No.    | Weight % |
|---------------------------------------|------------|----------|
| Chrome yellow (Lead chromate pigment) | 1344-37-2  | 0.1 - 1  |
| Titanium dioxide                      | 13463-67-7 | 1 - 5    |

## 3. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

**Routes of Exposure:** : Inhalation, Skin contact, Ingestion

Acute exposure

Inhalation : Resin particles, like other inert materials, can be mechanically irritating.

Ingestion : May be harmful if swallowed.

Eyes : Particulates, like other inert materials can be mechanically irritating.
Skin : Experience shows no unusual dermatitis hazard from routine handling.

**Chronic exposure** : Refer to Section 11 for Toxicological Information.

**Medical Conditions** : None known.

**Aggravated by Exposure:** 

1/7



#### MATERIAL SAFETY DATA SHEET

# V194 BRIGHT ORANGE

 Version Number 1.0
 Page 2 of 7

 Revision Date 06/11/2002
 Print Date 11/5/2011

4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of fumes from

overheating or combustion. When symptoms persist, or in all cases of

doubt, seek medical advice.

Ingestion : Do not induce vomiting without medical advice. When symptoms

persist, or in all cases of doubt, seek medical advice.

Eyes : Rinse immediately with plenty of water, also under the eyelids, for at

least 15 minutes. If eye irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists seek

medical attention.

5. FIRE-FIGHTING MEASURES

Flash point : Not applicable

Flammable Limits

Upper explosion limit : Not applicable Lower explosion limit : Not applicable Autoignition temperature : Not relevant

Suitable extinguishing media : Carbon dioxide blanket, Water spray, dry powder, foam.

Special Fire Fighting

Procedures

Fullface self-contained breathing apparatus (SCBA) used in positive

pressure mode should be worn to prevent inhalation of airborne

contaminants.

Unusual Fire/Explosion

Hazards

May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under

fire conditions.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear appropriate personal protection during cleanup, such as

impervious gloves, boots and coveralls.

Environmental precautions : Should not be released into the environment. The product should not

be allowed to enter drains, water courses or the soil.

Methods for cleaning up : Clean up promptly by sweeping or vacuum. Package all material in

plastic, cardboard or metal containers for disposal. Refer to Section 13

of this MSDS for proper disposal methods.

7. HANDLING AND STORAGE

Handling : Take measures to prevent the build up of electrostatic charge. Heat

only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of



# MATERIAL SAFETY DATA SHEET

# V194 BRIGHT ORANGE

 Version Number 1.0
 Page 3 of 7

 Revision Date 06/11/2002
 Print Date 11/5/2011

these materials.

Storage : Keep containers dry and tightly closed to avoid moisture absorption

and contamination. Keep in a dry, cool place.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection : No personal respiratory protective equipment normally required. If

dusty conditions occur wear appropriate respiratory protection.

Eye/Face Protection : Safety glasses with side-shields.

Hand protection : Protective gloves.

Skin and body protection : Long sleeved clothing.

Additional Protective

Measures

Safety shoes.

General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice.

Wash hands before breaks and at the end of workday.

Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide

appropriate exhaust ventilation at machinery.

Exposure limit(s)



## MATERIAL SAFETY DATA SHEET

# V194 BRIGHT ORANGE

Version Number 1.0 Page 4 of 7
Revision Date 06/11/2002 Print Date 11/5/2011

| Components          | Value    | Exposure time             | Exposure type              | List:   |
|---------------------|----------|---------------------------|----------------------------|---------|
| Chrome yellow (Lead | 0.01     | Time Weighted Average     | ime Weighted Average as Cr |         |
| chromate pigment)   | mg/m3    | (TWA):                    |                            |         |
| Chrome yellow (Lead | 1 mg/m3  | Time Weighted Average     |                            | MX OEL  |
| chromate pigment)   |          | (TWA):                    |                            |         |
|                     | 1 mg/m3  | PEL:                      |                            | OSHA Z1 |
| Chrome yellow (Lead | 0.05     | Time Weighted Average     | as Pb                      | ACGIH   |
| chromate pigment)   | mg/m3    | (TWA):                    |                            |         |
| Chrome yellow (Lead | 0.05     | Time Weighted Average     |                            | OSHA    |
| chromate pigment)   | mg/m3    | (TWA):                    |                            |         |
|                     | 0.03     | OSHA Action level:        |                            | OSHA    |
|                     | mg/m3    |                           |                            |         |
| Chrome yellow (Lead | 0.15     | Time Weighted Average     | Dust and fume. as Pb       | MX OEL  |
| chromate pigment)   | mg/m3    | (TWA):                    |                            |         |
|                     | 0.45     | Short Term Exposure Limit | Dust and fume. as Pb       | MX OEL  |
|                     | mg/m3    | (STEL):                   |                            |         |
| Chrome yellow (Lead | 0.01     | Time Weighted Average     |                            | ACGIH   |
| chromate pigment)   | mg/m3    | (TWA):                    |                            |         |
| Chrome yellow (Lead | 0.05     | Time Weighted Average     |                            | ACGIH   |
| chromate pigment)   | mg/m3    | (TWA):                    |                            |         |
| Titanium dioxide    | 10 mg/m3 | Time Weighted Average     | Total dust.                | ACGIH   |
|                     |          | (TWA):                    |                            |         |
| Titanium dioxide    | 15 mg/m3 | PEL:                      | Total dust.                | OSHA Z1 |

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Evaporation rate Not applicable. Form : Solid powder, granular Specific Gravity Not determined Appearance **ORANGE** Bulk density Not determined Color : Very faint Vapor pressure Not applicable Odor Melting point/range : Not determined Vapor density Not applicable **Boiling Point:** : Not applicable pН : Not applicable

Water solubility : Insoluble

# 10. STABILITY AND REACTIVITY

Stability : Stable.

Hazardous Polymerization : Will not occur.

Conditions to avoid : To avoid thermal decomposition, do not overheat. Keep away from

oxidizing agents and open flame.

Incompatible Materials : Incompatible with strong acids and oxidizing agents. Avoid contact

with acetal homopolymers and acetal copolymers during processing.

Hazardous decomposition

products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and

smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392  $^{\circ}$ F (200  $^{\circ}$ C) or short term heating at 482  $^{\circ}$ F (250



#### MATERIAL SAFETY DATA SHEET

# V194 BRIGHT ORANGE

 Version Number 1.0
 Page 5 of 7

 Revision Date 06/11/2002
 Print Date 11/5/2011

°C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

# 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

# **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

| CAS-No.    | Chemical Name       | Effect           | Target Organ            |
|------------|---------------------|------------------|-------------------------|
| 1344-37-2  | Chrome yellow (Lead | Systemic effects | central nervous system, |
|            | chromate pigment)   |                  | reproductive system.    |
| 13463-67-7 | Titanium dioxide    | Systemic effects | Respiratory system.     |

### Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

| CAS-No.   | Chemical Name       | OSHA | IARC | NTP |
|-----------|---------------------|------|------|-----|
| 1344-37-2 | Chrome yellow (Lead | no   | 1    | no  |
|           | chromate pigment)   |      |      |     |

### IARC Carcinogen Classifications:

- 1 The component is carcinogenic to humans.
- 2A The component is probably carcinogenic to humans.
- 2B The component is possibly carcinogenic to humans.

## NTP Carcinogen Classifications:

- 1 The component is known to be a human carcinogen.
- 2 The component is reasonably anticipated to be a human carcinogen.

## **Additional Health Hazard Information:**

Chrome yellow (Lead chromate pigment) 1344-37-2 Systemic effects include neurotoxic, teratogenic, fetotoxic and reproductive with abdominal pain, anemia, pallor, decreased hand grip strength with characteristic "wrist drop".

## 12. ECOLOGICAL INFORMATION

Persistence and degradability : Not readily biodegradable.

Environmental Toxicity : Adverse ecological impact is not known or expected under normal use.

Bioaccumulation Potential : No data available.

Additional advice : No data available.

# 13. DISPOSAL CONSIDERATIONS



#### MATERIAL SAFETY DATA SHEET

# V194 BRIGHT ORANGE

 Version Number 1.0
 Page 6 of 7

 Revision Date 06/11/2002
 Print Date 11/5/2011

Product : Where possible, recycling is preferred to disposal or incineration. The

generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste material

has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial

and local regulations.

14. TRANSPORT INFORMATION

U.S. D.O.T. / CA T.D.G.

Classification (Non-bulk

ground)

ICAO/IATA

: Not regulated for transportation.

: Not regulated for transportation.

IMO / IMDG : Not regulated for transportation.

## 15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on the TSCA inventory or are

exempt.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

California Proposition

65

: WARNING! This product contains a chemical known in the State of California to cause cancer., WARNING! This product contains a

chemical known in the State of California to cause birth defects or

other reproductive harm.

Not applicable

SARA Title III Section 313 Toxic Chemicals:

| Chemical Name             | CAS-No.   | Weight % |
|---------------------------|-----------|----------|
| CHROMIUM VI COMPOUNDS     | 1344-37-2 | 0.75     |
| LEAD COMPOUNDS, INORGANIC |           |          |

Canadian Regulations:



# MATERIAL SAFETY DATA SHEET

# V194 BRIGHT ORANGE

 Version Number 1.0
 Page 7 of 7

 Revision Date 06/11/2002
 Print Date 11/5/2011

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

| CAS-No.   |
|-----------|
| 1344-37-2 |
| 50-00-0   |
| 75-01-4   |

DSL : Listed.

National Inventories:

Australia AICS : Listed.

China IECS : Not determined.

Europe EINECS : Not determined.

Japan ENCS : Not determined.

Korea KECI : Not determined.

Philippines PICCS : Not determined.

# 16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.