# MATERIAL SAFETY DATA SHEET VB5846 VBX3340 IVORY AUA

Version Number 1.2 Revision Date 05/02/2008 Page 1 of 6 Print Date 1/3/2012

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	VB5846 VBX3340 IVORY AUA
Product code	:	FO00007739
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

## 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	1 - 5

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion		
Acute exposure			
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.		
Ingestion	: May be harmful if swallowed.		
Eyes	: Particulates, like other inert materials can be mechanically irritating.		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		
Medical Conditions Aggravated by Exposure:	: None known.		

PolyOne.

# MATERIAL SAFETY DATA SHEET VB5846 VBX3340 IVORY AUA

Version Number 1.2 Revision Date 05/02/2008 Page 2 of 6 Print Date 1/3/2012

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not relevant</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> </ul>
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	5. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. Processing fume

POLYONE CORPORATION

PolvOne

# MATERIAL SAFETY DATA SHEET VB5846 VBX3340 IVORY AUA

Version Number 1.2 Revision Date 05/02/2008 Page 3 of 6 Print Date 1/3/2012

condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

Storage

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection	1 1 1	ctive equipment normally required. If appropriate respiratory protection.
Eye/Face Protection	Safety glasses with side-shiel	ds
Hand protection	Protective gloves	
Skin and body protection	Long sleeved clothing	
Additional Protective Measures	Safety shoes	
General Hygiene Considerations	6	ood industrial hygiene and safety breaks and at the end of workday.
Engineering measures	Heat only in areas with approappropriate exhaust ventilation	priate exhaust ventilation. Provide on at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
	_	(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average	as Ti	MX OEL
	_	(TWA):		
	20 mg/m3	Short Term Exposure Limit	as Ti	MX OEL
		(STEL):		

### 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odour Melting point/range Boiling Point: Water solubility
- Solid
  powder, granular
  WHITE
  Very faint
  Not determined
  Not applicable
  Insoluble
- Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH
- Not applicable
  Not determined
  Not determined
  Not applicable
  Not applicable
  Not applicable

## **10. STABILITY AND REACTIVITY**

3/6

blvUn<u>e</u>

## **MATERIAL SAFETY DATA SHEET** VB5846 VBX3340 IVORY AUA

Version Number 1.2 Revision Date 05/02/2008

Page 4 of 6 Print Date 1/3/2012

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	To avoid thermal decomposition, do not overheat. Keep away from oxidizing agents and open flame.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

#### **12. ECOLOGICAL INFORMATION**

Persistence and degradability

Environmental Toxicity

: Not readily biodegradable.

: Adverse ecological impact is not known or expected under normal

PolyOne.

# MATERIAL SAFETY DATA SHEET VB5846 VBX3340 IVORY AUA

Version Number 1.2 Revision Date 05/02/2008 Page 5 of 6 Print Date 1/3/2012

<b>Bioaccumulation Potential</b>	:	No data available
Additional advice	:	No data available
	1	3. DISPOSAL CONSIDERATIONS
Product	:	Where possible recycling is preferred to disposal or incineration. Th generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	:	Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	1	4. TRANSPORT INFORMATION
U.S. DOT Classification	:	Not regulated for transportation.
ICAO/IATA (air)	:	Not regulated for transportation.
IMO / IMDG (maritime)	:	Not regulated for transportation.
	15	5. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Sub	stances (40 CFR 302)
Not applicable		
California Proposition	:	Not applicable
65	-	
SARA Title III Section 302 Ext	rem	ely Hazardous Substance

PolyOne

# MATERIAL SAFETY DATA SHEET VB5846 VBX3340 IVORY AUA

Version Number 1.2	
Revision Date 05/02/2008	

Page 6 of 6 Print Date 1/3/2012

SARA Title III Section 313 Toxic Chemicals:					
Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation					
Canadian Regulations:					
National Pollutant Relea	se Ir	iventory (NPRI)			
Not applicable					
WHMIS Classification	:	D2A			
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.			
National Inventories:					
Australia AICS	:	Not determined			
China IECS	:	Not determined			
Europe EINECS	:	Not determined			
Japan ENCS	:	Not determined			
Korea KECI	:	Not determined			
Philippines PICCS	:	Not determined			
		16. OTHER INFORMATION	╈		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.