

MATERIAL SAFETY DATA SHEET

W4403WHITE GLOVE COATING WHITE

Version Number 1.0 Revision Date 06/10/2002 Page 1 of 6 Print Date 11/4/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	W4403WHITE GLOVE COATING WHITE
Product code	:	FO00007940
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	1 - 5
Calcium carbonate	1317-65-3	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion	
Acute exposure		
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.	
Ingestion	: May be harmful if swallowed.	
Eyes	: May cause eye/skin irritation.	
Skin	: Experience shows no unusual dermatitis hazard from routine handling.	
Chronic exposure	: Refer to Section 11 for Toxicological Information.	



MATERIAL SAFETY DATA SHEET

W4403WHITE GLOVE COATING WHITE

Medical Conditions	: None known.
Aggravated by Exposure:	. INDIE KIIOWII.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases of doubt, seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available.
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 No data available. No data available. Not applicable. Carbon dioxide blanket, dry powder, foam, Water spray.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binde universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing



MATERIAL SAFETY DATA SHEET

W4403WHITE GLOVE COATING WHITE

sion Number 1.0 ision Date 06/10/2002			Print	Page 3 0 Date 11/4/20
	Р	ime condensates may contain c eriodically clean hoods, ducts, ccumulation of these materials.	and other surfaces to m	
Storage		eep containers dry and tightly nd contamination. Store in a contamination.		e absorption
8. E	XPOSURE	CONTROLS / PERSONAL	PROTECTION	
Respiratory protection	: U	Inder normal handling conditio	ns a respirator is not rea	quired.
Eye/Face Protection	: S	afety glasses with side-shields.		
Hand protection	: P	rotective gloves.		
Skin and body protection	: L	ong sleeved clothing.		
Additional Protective Measures	: Safety shoes.			
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.			
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH
Calcium carbonate	5 mg/m3	PEL:	Respirable dust.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- : Liquid Viscous, Liquid : : WHITE : Very faint : Not applicable : Not applicable : Immiscible
- Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pН
- Not established : Not determined Not applicable. : Not determined : : Not determined : Not applicable.

:

10. STABILITY AND REACTIVITY



MATERIAL SAFETY DATA SHEET

W4403WHITE GLOVE COATING WHITE

Version Number 1.0 Revision Date 06/10/2002		Page 4 of 6 Print Date <i>11/4/2011</i>
Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).
ļ		

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

12. ECOLOGICAL INFORMATION

Persistence and degradability	: Not readily biodegradable.	
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as whole.	s a
Bioaccumulation Potential	: No data available.	
Additional advice	: No data available.	
	13. DISPOSAL CONSIDERATIONS	
Product	 13. DISPOSAL CONSIDERATIONS Where possible, recycling is preferred to disposal or incineration. generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. 	The



MATERIAL SAFETY DATA SHEET

W4403WHITE GLOVE COATING WHITE

Version Number 1.0 Revision Date 06/10/2002 Page 5 of 6 Print Date 11/4/2011

and disposal in accordance with applicable federal, state/provincial and local regulations. **14. TRANSPORT INFORMATION** U.S. D.O.T. / CA T.D.G. : Not regulated for transportation. Classification (Non-bulk ground) ICAO/IATA : Not regulated for transportation. IMO / IMDG Not regulated for transportation. : **15. REGULATORY INFORMATION US Regulations: OSHA Status** Classified as hazardous based on components. · **TSCA Status** : All components of this product are listed on the TSCA inventory or are exempt. US. EPA CERCLA Hazardous Substances (40 CFR 302) Not applicable California Proposition : WARNING! This product contains a chemical known in the State of California to cause cancer. 65 SARA Title III Section 313 Toxic Chemicals: Chemical Name CAS-No. Weight % POLYCHLORINATED ALKANES 61788-76-9 11.46 (C10 TO C13) Canadian Regulations: WHMIS Classification : D2A WHMIS Ingredient Disclosure List

CAS-No.	
14808-60-7	
7631-86-9	



MATERIAL SAFETY DATA SHEET

W4403WHITE GLOVE COATING WHITE

Version Number 1.0		Page 6 of 6	
Revision Date 06/10/2002		Print Date 11/4/2011	
DSL	: Listed.		
National Inventories:			
Australia AICS	: Listed.		
China IECS	: Not determined.		
Europe EINECS	: Not determined.		
Japan ENCS	: Not determined.		
Korea KECI	: Listed.		
Philippines PICCS	: Listed.		
16. OTHER INFORMATION			

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.