6800-EF EPOXY HARDENER

Version Number 1.3 Revision Date 03/28/2024



Page 1 of 16 Print Date 03/29/2024

SAFETY DATA SHEET

6800-EF EPOXY HARDENER

Section 1. Identification	n	
GHS product identifier	:	6800-EF EPOXY HARDENER
Chemical name	:	Mixture
CAS number	:	Mixture
Other means of identification	:	FO00008222
Product type	:	liquid
Relevant identified uses of the subst	tance	or mixture and uses advised against
Product use	:	Industrial applications. Plastics.
Supplier's details	:	AVIENT CORPORATION
		33587 Walker Road, Avon Lake, OH 44012
		1 (440) 930-1000 or 1 (844) 4AVIENT
		1 (11) 750 1000 1 10 (11) 17 (11) 11
Emergency telephone number (with hours of operation)	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status	:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	:	ACUTE TOXICITY (dermal) - Category 3 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A

GHS label elements

6800-EF EPOXY HARDENER

Version Number 1.3 Revision Date 03/28/2024

AVIENT

Page 2 of 16)
Print Date 03/29/2024	

Hazard pictograms	:	
Signal word Hazard statements	:	Danger Toxic in contact with skin. Causes skin irritation. Causes serious eye irritation.
Precautionary statements		
Prevention	:	Not applicable. Wear protective gloves and protective clothing. Wear eye or face protection. Wash thoroughly after handling.
Response	:	Take off immediately all contaminated clothing and wash it before reuse. IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. Wash with plenty of water. If skin irritation occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Storage	:	Store locked up.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	:	None known.
Hazards not otherwise classified	:	None known. Not available.

Section 3. Composition/information on ingredients

Substance/mixture Chemical name Other means of identification	:	Substance Mixture FO00008222
CAS number/other identifiers		

CAS number

Mixture

:

Ingredient name	%	CAS number
Triethylenetetramine	100	112-24-3

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the

6800-EF EPOXY HARDENER

Version Number 1.3 Revision Date 03/28/2024 **ÀVIENT**

Page 3 of 16 Print Date 03/29/2024

concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	:	Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Inhalation : Skin contact :	Causes serious eye irritation. No known significant effects or critical hazards. Toxic in contact with skin. Causes skin irritation. No known significant effects or critical hazards.
--------------------------------	---

6800-EF EPOXY HARDENER

Version Number 1.3 Revision Date 03/28/2024

AVIENT

Page 4 of 16 Print Date 03/29/2024

Over-exposure signs/symptoms		
Eye contact	:	Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	:	No specific data.
Skin contact	:	Adverse symptoms may include the following: irritation redness
Ingestion	:	No specific data.
Indication of immediate medica	al attentio	n and special treatment needed, if necessary
Notes to physician	:	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	:	No specific treatment.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media	:	In case of fire, use water spray (fog), foam, dry chemical or CO ₂ . None known.
Specific hazards arising from the chemical Hazardous thermal decomposition products	:	In a fire or if heated, a pressure increase will occur and the container may burst. Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides
Special protective actions for fire- fighters Special protective equipment for	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Fire-fighters should wear appropriate protective equipment and self-
fire-fighters	:	contained breathing apparatus (SCBA) with a full face-piece operated

6800-EF EPOXY HARDENER

Version Number 1.3 Revision Date 03/28/2024



Page 5 of 16 Print Date 03/29/2024

in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel For emergency responders	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for containmer	nt ar	d cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

:

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist.

6800-EF EPOXY HARDENER

Version Number 1.3 Revision Date 03/28/2024

ÀVIENT

Page 6 of 16
Print Date 03/29/2024

Advice on general occupational hygiene	:	Do not ingest. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Triethylenetetramine	OARS WEEL (1999-01-01) Absorbed through skin. TWA 1 ppm

Appropriate engineering controls	:	Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures		
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated
		6/16

6800-EF EPOXY HARDENER



Version Number 1.3 Revision Date 03/28/2024

Page 7 of 16 Print Date 03/29/2024

Eye/face protection	:	clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state	:	liquid [liquid]
Color	:	NO PIGMENT
Odor	:	Not available.
Odor threshold	:	Not available.
рН	:	Not available.
Melting point	:	Not available.
Boiling point	:	Not available.
Flash point	:	Not available.
Burning time	:	Not available.
Burning rate	:	Not available.
Evaporation rate	:	Not available.

6800-EF EPOXY HARDENER

Version Number 1.3 Revision Date 03/28/2024

ÀVIENT

Page 8 of 16 Print Date 03/29/2024

Flammability (solid, gas)	:	Not available.
Lower and upper explosive	:	Lower: Not available.
(flammable) limits		Upper: Not available.
Vapor pressure	:	Not available.
Vapor density	:	Not available.
Relative density	:	Not available.
Solubility	:	Not available.
Solubility in water	:	Not available.
Partition coefficient: n-	:	Not applicable.
octanol/water		
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
SADT	:	Not available.
Viscosity	:	Dynamic: Not available.
-		Kinematic: Not available.

Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	Keep away from extreme heat and oxidizing agents.
Incompatible materials	:	Keep away from strong acids. Oxidizer.
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
1,2-Ethanediamine, N1,N2-bis	(2-aminoethyl)-			
	LD50 Oral	Rat	2,500 mg/kg	-
	LD50 Dermal	Rabbit	805 mg/kg	-

Conclusion/Summary

: Mixture.Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
0/46					

6800-EF EPOXY HARDENER



Version Number 1.3 Revision Date 03/28/2024 Page 9 of 16 Print Date 03/29/2024

	1				I
1,2-Ethanediamine, N1,N2- bis(2-aminoethyl)-	Eyes - Moderate irritant	Rabbit	-	24 hrs	-
	Skin - Severe irritant	Rabbit	-		-
	Skin - Severe irritant	Rabbit	-	24 hrs	-
	Eyes - Severe irritant	Rabbit	-		-
Conclusion/Summary					
Skin		ot fully tested			
Eyes		ot fully tested			
Respiratory	: Mixture.No	ot fully tested	l.		
Sensitization					
Conclusion/Summary					
Skin		ot fully tested			
Respiratory	: Mixture.No	ot fully tested	1.		
Mutagenicity					
Conclusion/Summary	: Mixture.No	ot fully tested	l.		
Carcinogenicity					
Conclusion/Summary	: Mixture.No	ot fully tested	1.		
Reproductive toxicity					
Conclusion/Summary	: Mixture.No	ot fully tested	l.		
Teratogenicity					
Conclusion/Summary	: Mixture.No	ot fully tested	l.		
Specific target organ toxicit Not available.	<u>y (single exposure)</u>				
Specific target organ toxicit Not available.	y (repeated exposure)				

Aspiration hazard

Not available.

Information on the likely routes of : Not available. exposure

6800-EF EPOXY HARDENER

Version Number 1.3 Revision Date 03/28/2024

Potential acute health effects



Page 10 of 16
Print Date 03/29/2024

Eye contact Inhalation Skin contact Ingestion	:	Causes serious eye irritation. No known significant effects or critical hazards. Toxic in contact with skin. Causes skin irritation. No known significant effects or critical hazards.		
Symptoms related to the physical, che	emio			
Symptoms related to the physical, end		und tomeorogicur churacter iones		
Eye contact	:	Adverse symptoms may include the following: pain or irritation, watering, redness		
Inhalation	:	No specific data.		
Skin contact	÷	Adverse symptoms may include the following: irritation, redness		
Ingestion	:	No specific data.		
Delayed and immediate effects and al	lso c	hronic effects from short and long term exposure		
Short term exposure				
Potential immediate effects	:	Not available.		
Potential delayed effects	:	Not available.		
- -				
Long term exposure				
Potential immediate effects	:	Not available.		
Potential delayed effects	-	Not available.		
•				
Potential chronic health effects				
Conclusion/Summary	:	Mixture.Not fully tested.		
General	:	No known significant effects or critical hazards.		
Carcinogenicity	:	No known significant effects or critical hazards.		
Mutagenicity	:	No known significant effects or critical hazards.		
Teratogenicity	:	No known significant effects or critical hazards.		
Developmental effects	:	No known significant effects or critical hazards.		
Fertility effects	:	No known significant effects or critical hazards. No known significant		
		effects or critical hazards.		

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name Oral Derr	Inhalation (gases)	Inhalation (vapors)	Inhalation (dusts and mists)
-----------------------------------	-----------------------	------------------------	------------------------------------



6800-EF EPOXY HARDENER

Version Number 1.3 Revision Date 03/28/2024

Page 11 of 16 Print Date 03/29/2024

6800-EF EPOXY HARDENER	2500 mg/kg	805 mg/kg	N/A	N/A	N/A
1,2-Ethanediamine, N1,N2- bis(2-aminoethyl)-	2500 mg/kg	805 mg/kg	N/A	N/A	N/A

Other information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Section 12. Ecological information

:

Toxicity

Product/ingredient name	Result	Species	Exposure	
1,2-Ethanediamine, N1,N2-bis(2-aminoethyl)-				
	Acute LC50 0.0339 Mg/l Fresh	Daphnia - Daphnia magna	48 h	
	water			

Conclusion/Summary

: Not available.

Persistence and degradability

Conclusion/Summary : Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
1,2-Ethanediamine, N1,N2-bis(2-	-1.661.4	-	low
aminoethyl)-			

Mobility in soil

Soil/water partition coefficient (KOC)	:	Not available.
Other adverse effects	:	No known significant effects or critical hazards.

6800-EF EPOXY HARDENER

Version Number 1.3 Revision Date 03/28/2024

ÀVIENT

Page 12 of 16 Print Date 03/29/2024

Section 13. Disposal considerations

:

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

U.S.DOT 49CFR	
Ground/Air/Water	
Proper Shipping Name:	TRIETHYLENETETRAMINE
Technical Name:	
Hazard Class / Division	8
UN Number	UN2259
Packing Group	Π
Label Required	8
International Air ICAO/IATA	Consult mode specific transport rules
International Water IMO/IMDG	Consult mode specific transport rules

:

Section 15. Regulatory information

- **U.S. Federal regulations**
- United States TSCA 12(b) Chemical export notification: None of the components are listed.

12/16

6800-EF EPOXY HARDENER

Version Number 1.3 Revision Date 03/28/2024



Page 13 of 16 Print Date 03/29/2024

United States - TSCA 4(a) - Final Test Rules: Not listed United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 5(a)2 - Final significant new use rules: Not listed United States - TSCA 5(a)2 - Proposed significant new use rules: Not listed United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined United States - TSCA 8(a) - Preliminary assessment report (PAIR): Not listed United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Not listed United States - EPA Clean water act (CWA) section 311 -Hazardous substances: Not listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Not listed United States - Department of commerce - Precursor chemical: Not listed

Clean Air Act Section 112(b)	:	Not listed
Hazardous Air Pollutants (HAPs)		
Clean Air Act Section 602 Class I	:	Not listed
Substances		
Clean Air Act Section 602 Class II	:	Not listed
Substances		
DEA List I Chemicals (Precursor	:	Not listed
Chemicals)		
DEA List II Chemicals (Essential	:	Not listed
Chemicals)		

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312

6800-EF EPOXY HARDENER

:

Version Number 1.3 Revision Date 03/28/2024

AVIENT

Page 14 of 16 Print Date 03/29/2024

Classification

ACUTE TOXICITY - dermal - Category 3 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A

Composition/information on ingredients

Name	%	Classification
1,2-Ethanediamine, N1,N2-	100	ACUTE TOXICITY - dermal - Category 3
bis(2-aminoethyl)-		SKIN IRRITATION - Category 2
		EYE IRRITATION - Category 2A

Not applicable.

State regulations		
Massachusetts	:	The following components are listed: Triethylenetetramine
New York	:	None of the components are listed.
New Jersey	:	The following components are listed:
-		Triethylenetetramine
Pennsylvania	:	The following components are listed:
		Triethylenetetramine
<u>California Prop. 65</u>		
This product does not require a Safe H	larbo	warning under California Prop. 65.
United States inventory (TSCA 8b)	:	All components are active or exempted.
Canada inventory	:	All components are listed or exempted.
<u>International regulations</u> Inventory list		
Australia	:	All components are listed or exempted.
Canada	:	All components are listed or exempted.
China	:	All components are listed or exempted.
Eurasian Economic Union	:	Russian Federation inventory: All components are listed or
		exempted.
Japan	:	Japan inventory (CSCL): All components are listed or exempted.
		Japan inventory (ISHL): Not determined.
New Zealand	:	All components are listed or exempted.
Philippines	:	All components are listed or exempted.
Republic of Korea	:	All components are listed or exempted.
Taiwan	:	All components are listed or exempted.All components are listed or
		exempted.

6800-EF EPOXY HARDENER

Version Number 1.3 Revision Date 03/28/2024



Page 15 of 16 Print Date 03/29/2024

Thailand	:	Not determined.
Turkey	:	All components are listed or exempted.
United States	:	All components are active or exempted.
Viet Nam	:	All components are listed or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	/	2
Flammability		0
Physical hazards		0
e e e e e e e e e e e e e e e e e e e		

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual. History

HISLOFY		
Date of printing	:	03/29/2024
Date of issue/Date of revision	:	03/28/2024
Date of previous issue	:	06/17/2015
Version	:	1.3
Key to abbreviations	:	ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient
		MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations
References	:	Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that

6800-EF EPOXY HARDENER

Version Number 1.3 Revision Date 03/28/2024



Page 16 of 16 Print Date 03/29/2024

exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.