PolvOne

MATERIAL SAFETY DATA SHEET **S2000 WHITE NM**

Version Number 1.1 Revision Date 02/15/2007

Product Use

Page 1 of 7 Print Date 11/26/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

| Telephone Emergency telephone number | : | Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident). |
|--|---|--|
| Product name | : | S2000 WHITE NM |
| Product code | : | FO00008742 |
| Chemical Name | : | Mixture |
| CAS-No. | : | Mixture |

: Mixture : Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

| Components | CAS-No. | Weight % |
|--|-------------|----------|
| Silica, amorphous | 7631-86-9 | 1 - 5 |
| Silica, amorphous, fumed, crystal-free | 112945-52-5 | 1 - 5 |
| Alkenes, C12-24, chloro | 68527-02-6 | 1 - 5 |
| Titanium dioxide | 13463-67-7 | 10 - 30 |

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

| Routes of Exposure: | : Inhalation, Skin contact, Ingestion |
|----------------------------|--|
| Acute exposure | |
| Inhalation | : Inhalation of airborne droplets may cause irritation of the respiratory tract. |
| Ingestion | : May be harmful if swallowed. |
| Eyes | : May cause eye/skin irritation. |
| Skin | : Experience shows no unusual dermatitis hazard from routine handling. |
| Chronic exposure | : Refer to Section 11 for Toxicological Information. |

PolyOne.

MATERIAL SAFETY DATA SHEET **S2000 WHITE NM**

Version Number 1.1 Revision Date 02/15/2007 Page 2 of 7 Print Date 11/26/2011

| Medical Conditions Aggravated by Exposure: | : None known. |
|--|--|
| | 4. FIRST AID MEASURES |
| Inhalation | : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice. |
| Ingestion | : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. |
| Eyes | : Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention. |
| Skin | : Wash off with soap and plenty of water. If skin irritation persists see medical attention. |
| | 5. FIRE-FIGHTING MEASURES |
| Flash point | : No data available |
| Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media | No data available No data available Not applicable Carbon dioxide blanket, water spray, dry powder, foam. |
| Special Fire Fighting Procedures | : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. |
| Unusual Fire/Explosion Hazards | May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible. |
| | 6. ACCIDENTAL RELEASE MEASURES |
| Personal precautions | : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. |
| Environmental precautions | : The product should not be allowed to enter drains, water courses or th soil. Should not be released into the environment. |
| Methods for cleaning up | : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods. |



MATERIAL SAFETY DATA SHEET **S2000 WHITE NM**

Version Number 1.1 Revision Date 02/15/2007 Page 3 of 7 Print Date 11/26/2011

| Handling | : | Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials. |
|-----------------------------------|-------|--|
| Storage | : | Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place. |
| 8. EXF | POSUE | RE CONTROLS / PERSONAL PROTECTION |
| Respiratory protection | : | No personal respiratory protective equipment normally required. |
| Eye/Face Protection | : | Safety glasses with side-shields. |
| Hand protection | : | Protective gloves. |
| Skin and body protection | : | Long sleeved clothing. |
| Additional Protective Measures | : | Safety shoes. |
| General Hygiene Considerations | : | Handle in accordance with good industrial hygiene and safety practice Wash hands before breaks and at the end of workday. |
| Engineering measures | : | Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. |

PolvOne

MATERIAL SAFETY DATA SHEET S2000 WHITE NM

Version Number 1.1 Revision Date 02/15/2007

Page 4 of 7 Print Date 11/26/2011

| Components | Value | Exposure time | Exposure type | List: |
|---|-----------|-----------------------------------|------------------------|---------|
| Silica, amorphous | 20 mppcf | PEL: | Total dust. | OSHA |
| | 20 mppcf | PEL: | Total dust. | Z3 |
| | 0.8 mg/m3 | Time Weighted Average (TWA): | | Z3 |
| | 10 mg/m3 | Time Weighted Average (TWA): | | MX OEL |
| | 10 mg/m3 | Time Weighted Average (TWA): | Inhalable particulate. | MX OEL |
| | 3 mg/m3 | Time Weighted Average (TWA): | Respirable dust. | MX OEL |
| Silica, amorphous, fumed, crystal-free | 20 mppcf | PEL: | Total dust. | Z3 |
| | 0.8 mg/m3 | Time Weighted Average (TWA): | | Z3 |
| | 10 mg/m3 | Time Weighted Average (TWA): | Inhalable particulate. | MX OEL |
| | 3 mg/m3 | Time Weighted Average (TWA): | Respirable dust. | MX OEL |
| Titanium dioxide | 10 mg/m3 | Time Weighted Average (TWA): | | ACGIH |
| | 15 mg/m3 | PEL: | Total dust. | OSHA Z1 |
| | 20 mg/m3 | Short Term Exposure Limit (STEL): | as Ti | MX OEL |

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odor Melting point/range **Boiling Point:** Water solubility

:

:

:

:

:

:

WHITE

Very faint

Immiscible

Not applicable

Not applicable

Evaporation rate : liquid Viscous, liquid Specific Gravity:

- Bulk density Vapor pressure Vapour density pН
- : Not established Not determined
- : Not applicable :
- Not determined :
- Not determined :
- Not applicable :

10. STABILITY AND REACTIVITY Stability : Stable. Hazardous Polymerization Will not occur. : Conditions to avoid Keep away from oxidizing agents and open flame. To avoid thermal : decomposition, do not overheat. Incompatible Materials Incompatible with strong acids and oxidizing agents., Avoid contact : with acetal homopolymers and acetal copolymers during processing. Hazardous decomposition : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen products (NOx), hydrogen chloride (HCl), other hazardous materials, and

MATERIAL SAFETY DATA SHEET S2000 WHITE NM

Version Number 1.1 Revision Date 02/15/2007

Page 5 of 7 Print Date 11/26/2011

smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

| CAS-No. | Chemical Name | Effect | Target Organ |
|-------------|--|------------------|---------------------------|
| 7631-86-9 | Silica, amorphous | Irritant | Eyes, Respiratory system. |
| 112945-52-5 | Silica, amorphous, fumed, crystal-free | Irritant | Eyes, Respiratory system. |
| 13463-67-7 | Titanium dioxide | Systemic effects | Respiratory system. |

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

| CAS-No. | Chemical Name | Route | Value | Species |
|-------------|---------------------------|-----------|-------------|----------|
| 7631-86-9 | Silica, amorphous | Oral | 15,000 | mouserat |
| | | LD50Oral | mg/kg22,500 | |
| | | LD50 | mg/kg | |
| 112945-52-5 | Silica, amorphous, fumed, | Oral LD50 | 3,160 mg/kg | rat |
| | crystal-free | | | |

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

| CAS-No. | Chemical Name | OSHA | IARC | NTP |
|------------|------------------|------|------|-----|
| 13463-67-7 | Titanium dioxide | no | 2B | no |

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

Persistence and degradability

: Not readily biodegradable.

Environmental Toxicity

: Environmental toxicity has not been established for this mixture as a

PolyOne.

MATERIAL SAFETY DATA SHEET **S2000 WHITE NM**

Version Number 1.1 Revision Date 02/15/2007 Page 6 of 7 Print Date 11/26/2011

| Bioaccumulation Potential | : No data available |
|------------------------------|---|
| | |
| Additional advice | : No data available |
| | 13. DISPOSAL CONSIDERATIONS |
| Product | : Where possible recycling is preferred to disposal or incineration. T generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. |
| Contaminated packaging | : Recycling is preferred when possible. The generator of waste mater has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. |
| | 14. TRANSPORT INFORMATION |
| | |
| U.S. DOT Classification | : Refer to specific regulation. |
| ICAO/IATA (air) | : Refer to specific regulation. |
| IMO / IMDG (maritime) | : Refer to specific regulation. |
| | 15. REGULATORY INFORMATION |
| US Regulations: | |
| OSHA Status | : Classified as hazardous based on components. |
| TSCA Status | : All components of this product are listed on or exempt from the TSO Inventory. |
| US. EPA CERCLA Hazardou | as Substances (40 CFR 302) |
| Not applicable | |
| | |
| California Proposition 65 | 1 : Not applicable |
| SARA Title III Section 302 E | Extremely Hazardous Substance |

PolyOne

MATERIAL SAFETY DATA SHEET **S2000 WHITE NM**

| Version Number 1.1 | Page 7 of 7 |
|--------------------------|-----------------------|
| Revision Date 02/15/2007 | Print Date 11/26/2011 |
| | |

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

| Chemical Name | | | CAS-No. | Weight % | NPRI ID# |
|----------------------------|---|----------------|--------------------------------------|-----------------------------|------------|
| Bis (2-ethylhexyl) adipate | | | 103-23-1 | 1.00 - 5.00 | 24 |
| WHMIS Classification | : | All components | s of this product (DSL) or are ex | are on the Canadia empt. | n Domestic |
| tional Inventories: | | | | | |
| Australia AICS | : | Not determined | | | |
| China IECS | : | Not determined | | | |
| Europe EINECS | : | Listed | | | |
| Japan ENCS | : | Not determined | | | |
| Korea KECI | : | Not determined | | | |
| Philippines PICCS | : | Not determined | | | |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.