

MATERIAL SAFETY DATA SHEET

THICK2CAL THICKENER #2

Version Number 1.0 Revision Date 05/12/2003 Page 1 of 6 Print Date 11/11/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	THICK2CAL THICKENER #2
Product code	:	FO00008764
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous, fumed, crystal-free	112945-52-5	60 - 100

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion			
Acute exposure				
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.			
Ingestion	: May be harmful if swallowed.			
Eyes	: May cause eye/skin irritation.			
Skin	: Experience shows no unusual dermatitis hazard from routine handling.			
Chronic exposure	: Refer to Section 11 for Toxicological Information.			
Medical Conditions Aggravated by Exposure:	: None known.			



MATERIAL SAFETY DATA SHEET

THICK2CAL THICKENER #2

Version Number 1.0 Revision Date 05/12/2003 Page 2 of 6 Print Date 11/11/2011

	4. FIRST AID MEASURES	
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.	of
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.	
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If e irritation persists, seek medical attention.	eye
Skin	: Wash off with soap and plenty of water. If skin irritation persists se medical attention.	eek
	5. FIRE-FIGHTING MEASURES	
Flash point	: No data available.	
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature	 No data available. No data available. Not applicable. 	
Suitable extinguishing media	: Carbon dioxide blanket, dry powder, foam, Water spray.	
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) und fire conditions. 	
	5. ACCIDENTAL RELEASE MEASURES	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	: Should not be released into the environment. The product should n be allowed to enter drains, water courses or the soil.	ot
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid bind universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for prope disposal methods.	
	7. HANDLING AND STORAGE	
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize	5



MATERIAL SAFETY DATA SHEET

THICK2CAL THICKENER #2

	a	ccumulation of these m	naterials.			
Storage		Leep containers dry and nd contamination. Stor			moisture	absorption
8. F	XPOSURE	CONTROLS / PERS	ONAL]	PROTECTIO	N	
Respiratory protection	: U	Inder normal handling	conditio	ns a respirator 1	may not l	be required.
Eye/Face Protection	: S	afety glasses with side	-shields.			
Hand protection	: P	rotective gloves.				
Skin and body protection	: L	ong sleeved clothing.				
Additional Protective Measures	: S	afety shoes.				
General Hygiene Considerations		landle in accordance wa Vash hands before brea				afety practice
Engineering measures		: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)						
Components	Value	Exposure time		Exposure	type	List:
Silica, amorphous, fumed, crystal-free	20 mppcf	PEL:		Total du	st.	Z3
	9. PHYSIC	CAL AND CHEMICA	AL PRO	PERTIES		
	: Liqu	id	Evapor	ation rate	: Not	established
Form	. Liqu					
Appearance	: Visc	ous, Liquid		c Gravity	. 1.00	determined
Appearance Color	: Visc : NOT	APPLICABLE	Bulk de	c Gravity ensity	: Not	applicable.
Appearance Color Odor	: Visc : NOT : Very	CAPPLICABLE faint	Bulk de Vapor	c Gravity ensity pressure	: Not : Not	applicable. determined
Appearance Color	: Visc : NOT : Very : Not	APPLICABLE	Bulk de Vapor	c Gravity ensity	: Not : Not : Not	applicable.
Appearance Color Odor Melting point/range	: Visc : NOT : Very : Not	APPLICABLE faint applicable applicable	Bulk de Vapor Vapor	c Gravity ensity pressure	: Not : Not : Not	applicable. determined determined
Appearance Color Odor Melting point/range Boiling Point:	: Visc : NOT : Very : Not : Not : Imm	APPLICABLE faint applicable applicable	Bulk de Vapor Vapor pH	c Gravity ensity pressure density	: Not : Not : Not	applicable. determined determined
Appearance Color Odor Melting point/range Boiling Point:	: Visc : NOT : Very : Not : Not : Imm 10. S	APPLICABLE faint applicable applicable iscible	Bulk de Vapor Vapor pH	c Gravity ensity pressure density	: Not : Not : Not	applicable. determined determined
Appearance Color Odor Melting point/range Boiling Point: Water solubility	: Visc : NOT : Very : Not : Not : Imm 10. S : S	APPLICABLE faint applicable applicable iscible STABILITY AND RE	Bulk de Vapor Vapor pH	c Gravity ensity pressure density	: Not : Not : Not	applicable. determined determined



MATERIAL SAFETY DATA SHEET

THICK2CAL THICKENER #2

Version Number 1.0 Revision Date 05/12/2003		Page 4 of 6 Print Date 11/11/2011				
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.				
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).				
	11. TOXICOLOGICAL INFORMATION					

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
112945-52-5	Silica, amorphous, fumed, crystal-free	Irritant	Eyes, Respiratory system.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
112945-52-5	Silica, amorphous, fumed, crystal-free	Oral LD50	3,160 mg/kg	rat

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	:	No data available.
Additional advice	:	No data available.
	1.	3. DISPOSAL CONSIDERATIONS
Product	:	Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	:	Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial



MATERIAL SAFETY DATA SHEET

THICK2CAL THICKENER #2

sion Number 1.0 ision Date 05/12/2003		Page 5 Print Date 11/11/2
	and local regulations.	
	14. TRANSPORT INFORM	IATION
U.S. DOT Classification	: Refer to specific regulation	
ICAO/IATA	: Refer to specific regulation	
IMO / IMDG	: Refer to specific regulation	
	15. REGULATORY INFOR	
US Regulations:	15. REGULATORT INFOR	MATION
OSHA Status	: Classified as hazardous ba	sed on components.
TSCA Status		duct are listed on or exempt from the TSCA
US. EPA CERCLA Hazardo	-	
Not applicable	us Subsunces (40 CFR 502)	
California Proposition 65	n : This product does not cont	ain a substance listed by California Prop 65.
	Extremely Hazardous Substance	
Not applicable		
SARA Title III Section 313	Toxic Chemicals:	
Not applicable		
Canadian Regulations:		
	on : Not controlled.	
Canadian Regulations:		oduct are on the Canadian Domestic are exempt.
Canadian Regulations: WHMIS Classificatio	: All components of this pro	



MATERIAL SAFETY DATA SHEET

THICK2CAL THICKENER #2

Version Number 1.0 Revision Date 05/12/2003 Page 6 of 6 Print Date 11/11/2011

China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Listed.
Philippines PICCS	:	Listed.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.