



# POLYONE CORPORATION

## MATERIAL SAFETY DATA SHEET

### 2200043 VBX3340 SGDA WILLOW GREEN PWD

Version Number 1.0  
Revision Date 10/10/2003

Page 1 of 6  
Print Date 11/12/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

**POLYONE CORPORATION**  
2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE : Product Stewardship (314) 771-1800  
**Emergency telephone number** : **CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).**

Product name : 2200043 VBX3340 SGDA WILLOW GREEN PWD  
Product code : FO00011101  
Chemical Name : Mixture  
CAS-No. : Mixture  
Product Use : Industrial Applications

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	1 - 5

#### 3. HAZARDS IDENTIFICATION

##### EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

##### POTENTIAL HEALTH EFFECTS

**Routes of Exposure:** : Inhalation, Skin contact, Ingestion

##### Acute exposure

Inhalation : Resin particles, like other inert materials, can be mechanically irritating.  
Ingestion : May be harmful if swallowed.  
Eyes : Particulates, like other inert materials can be mechanically irritating.  
Skin : Experience shows no unusual dermatitis hazard from routine handling.

**Chronic exposure** : Refer to Section 11 for Toxicological Information.

**Medical Conditions** : None known.

**Aggravated by Exposure:**

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**2200043 VBX3340 SGDA WILLOW GREEN PWD**

Version Number 1.0  
Revision Date 10/10/2003

Page 2 of 6  
Print Date 11/12/2011

**4. FIRST AID MEASURES**

- Inhalation : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
- Ingestion : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
- Eyes : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
- Skin : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

**5. FIRE-FIGHTING MEASURES**

- Flash point : Not applicable
- Flammable Limits
  - Upper explosion limit : Not applicable
  - Lower explosion limit : Not applicable
- Autoignition temperature : Not relevant
- Suitable extinguishing media : Carbon dioxide blanket, water spray, dry powder, foam.
- Special Fire Fighting Procedures : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
- Unusual Fire/Explosion Hazards : May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.

**6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
- Environmental precautions : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
- Methods for cleaning up : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

**7. HANDLING AND STORAGE**

- Handling : Take measures to prevent the build up of electrostatic charge Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**2200043 VBX3340 SGDA WILLOW GREEN PWD**

Version Number 1.0  
Revision Date 10/10/2003

Page 3 of 6  
Print Date 11/12/2011

these materials.

Storage : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

Respiratory protection : No personal respiratory protective equipment normally required. If dusty conditions occur wear appropriate respiratory protection.

Eye/Face Protection : safety glasses with side-shields

Hand protection : protective gloves

Skin and body protection : long sleeved clothing

Additional Protective Measures : safety shoes

General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1

**9. PHYSICAL AND CHEMICAL PROPERTIES**

Form	: Solid	Evaporation rate	: Not applicable
Appearance	: powder, granular	Specific Gravity	: Not determined
Color	: GREEN	Bulk density	: Not determined
Odor	: Very faint	Vapor pressure	: Not applicable
Melting point/range	: Not determined	Vapour density	: Not applicable
Boiling Point:	: Not applicable	pH	: Not applicable
Water solubility	: Insoluble		

**10. STABILITY AND REACTIVITY**

Stability : Stable.

Hazardous Polymerization : Will not occur.

Conditions to avoid : To avoid thermal decomposition, do not overheat. Keep away from

**POLYONE CORPORATION****MATERIAL SAFETY DATA SHEET****2200043 VBX3340 SGDA WILLOW GREEN PWD**Version Number 1.0  
Revision Date 10/10/2003Page 4 of 6  
Print Date 11/12/2011

oxidizing agents and open flame.

Incompatible Materials : Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.

Hazardous decomposition products : Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

**11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

**12. ECOLOGICAL INFORMATION**

Persistence and degradability : Not readily biodegradable.

Environmental Toxicity : Adverse ecological impact is not known or expected under normal use.

Bioaccumulation Potential : No data available

Additional advice : No data available

**13. DISPOSAL CONSIDERATIONS**

Product : Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

**14. TRANSPORT INFORMATION**

U.S. DOT Classification : Not regulated for transportation.



# POLYONE CORPORATION

## MATERIAL SAFETY DATA SHEET

### 2200043 VBX3340 SGDA WILLOW GREEN PWD

Version Number 1.0  
Revision Date 10/10/2003

Page 5 of 6  
Print Date 11/12/2011

ICAO/IATA (air) : Not regulated for transportation.  
IMO / IMDG (maritime) : Not regulated for transportation.

#### 15. REGULATORY INFORMATION

##### US Regulations:

OSHA Status : Classified as hazardous based on components.  
TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

##### US. EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

California Proposition 65 : WARNING! This product contains a chemical known to the State of California to cause cancer.

##### SARA Title III Section 302 Extremely Hazardous Substance

Not applicable

##### SARA Title III Section 313 Toxic Chemicals:

Not applicable  
Canadian Regulations:

##### National Pollutant Release Inventory (NPRI)

Not applicable

WHMIS Classification : D2B  
DSL : All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

##### National Inventories:

Australia AICS : Listed  
China IECS : Listed  
Europe EINECS : Not determined  
Japan ENCS : Not determined



**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**2200043 VBX3340 SGDA WILLOW GREEN PWD**

Version Number 1.0  
Revision Date 10/10/2003

Page 6 of 6  
Print Date 11/12/2011

Korea KECI : Not determined  
Philippines PICCS : Listed

**16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.