

MATERIAL SAFETY DATA SHEET

WB180 CLEAR

 Version Number 1.0
 Page 1 of 6

 Revision Date 06/13/2002
 Print Date 11/5/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION

2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY : Product Stewardship, (314) 771-1800

TELEPHONE

Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure

number or accident).

Product name : WB180 CLEAR
Product code : FO00011322
Chemical Name : Mixture
CAS-No. : Mixture

Product Use : Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

There are no known hazardous components above regulatory thresholds in this product.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This product is a water based mixture with an ammonia odor. The mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. The product is not combustible, but it will burn if involved in a fire, releasing hydrocarbon products of combustion. Inhalation of the ammonia from this product may cause respiratory irritation, coughing, sore throat, and labored breathing

POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Skin contact, Inhalation, Ingestion

Acute exposure

Inhalation : Symptoms of breathing ammonia vapor concentrated from this product

may include laryngitis, tracheitis, pulmonary edema, dyspnea, bronchospasms, and chest pains or pneumonitis. Symptoms are

typically reversible.

Ingestion : No known effects.

Eyes : Liquid, aerosol, or vapors of this product are irritating and may cause

tearing, reddening, and swelling accompanied by a stinging sensation

and/or a feeling like that of fine dust in the eyes.

Skin : Skin contact may cause redness, irritation, and burns.

Chronic exposure : Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET

WB180 CLEAR

 Version Number 1.0
 Page 2 of 6

 Revision Date 06/13/2002
 Print Date 11/5/2011

Medical Conditions Aggravated by Exposure: : None known.

4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of vapors or fumes

from overheating or combustion. When symptoms persist, or in all

cases of doubt, seek medical advice.

Ingestion : Obtain medical attention. Never give anything by mouth to an

unconscious person.

Eyes : Rinse immediately with plenty of water for at least 15 minutes. If eye

irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists seek

medical attention.

5. FIRE-FIGHTING MEASURES

Flash point : Greater than 400 °F

Flammable Limits

Upper explosion limit : No data available.

Lower explosion limit : No data available.

Autoignition temperature : No data available.

Suitable extinguishing media : carbon dioxide (CO2), water, foam, dry chemical.

Special Fire Fighting

Procedures

: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne

contaminants. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water courses.

Unusual Fire/Explosion

Hazards

Burning dry latex produces dense black smoke with the possibility of toxic vapors. Empty drums containing residual latex material may

decompose when burned producing toxic or irritating fumes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Ensure response personnel are properly protected (see section 8 for

respiratory or other protection guidelines.) Use caution as floors may

be slippery.

Environmental precautions : The product should not be allowed to enter drains, water courses or the

soil.

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder,

universal binder, sawdust). Sweep up and shovel into suitable

containers for disposal.



MATERIAL SAFETY DATA SHEET

WB180 CLEAR

 Version Number 1.0
 Page 3 of 6

 Revision Date 06/13/2002
 Print Date 11/5/2011

7. HANDLING AND STORAGE

Handling : Use only in area provided with appropriate exhaust ventilation.

Prolonged heating may result in product degradation. Material may settle during storage. Careful mixing without introduction of air may

be necessary before use.

Storage : Containers which are opened must be carefully resealed and kept

upright to prevent leakage. Keep in a dry, cool place. Keep from

freezing and temperature extremes.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection : A respirator is normally not required for routine handling of product in

areas of good general ventilation and adequate local exhaust at processing equipment during routine operation. If using a cartridge respirator, an ammonia cartridge is required to filter out potential

excess ammonia vapors.

Eye/Face Protection : Safety glasses with side-shields. Wear goggles or face shield during

operations that present a splash potential.

Hand protection : Impervious gloves such as rubber or PVC

Skin and body protection : Long sleeved shirts and long pants are adequate for normal handling.

Where operations present a splash or spill potential, employees should

wear chemically resistant clothing, boots, gloves, and eye/face

protection.

Additional Protective

Measures

: Safety shoes

General Hygiene

Considerations

: Wash hands before breaks and immediately after handling the product. Handle in accordance with good industrial hygiene and safety

practices.

Engineering measures : Adequate ventilation and/or appropriate respiratory protection may

also be necessary to minimize employee exposure to processing

vapors.

Exposure limit(s)

There are no known hazardous components above regulatory thresholds in this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form : Liquid Evaporation rate : Slower than Butyl

Acetate

Appearance : Liquid Specific Gravity : Not determined Color : TRANSPARENT Bulk density : Not applicable.



MATERIAL SAFETY DATA SHEET

WB180 CLEAR

 Version Number 1.0
 Page 4 of 6

 Revision Date 06/13/2002
 Print Date 11/5/2011

Odor : Slight ammonia Vapor pressure : Not established
Melting point/range : Not applicable Vapor density : Heavier than air.
Boiling Point: : Not applicable pH : Not determined

Water solubility : Completely miscible

10. STABILITY AND REACTIVITY

Stability : Stable.

Hazardous Polymerization : Will not occur.

Conditions to avoid : Extremes of temperature and direct sunlight. Keep from freezing.

Incompatible Materials : Acids, metal salts, and solvents

Hazardous decomposition

products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

There are no known hazardous components above regulatory thresholds in this product.

12. ECOLOGICAL INFORMATION

11. TOXICOLOGICAL INFORMATION

Persistence and degradability : No data available.

Environmental Toxicity : No data available.

Bioaccumulation Potential : No data available.

Additional advice : No data available.

13. DISPOSAL CONSIDERATIONS

Product : Where possible, recycling is preferred to disposal or incineration. The

generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation

and disposal in accordance with applicable federal, state/provincial

and local regulations.

14. TRANSPORT INFORMATION

U.S. D.O.T. / CA T.D.G. Classification (Non-bulk

ground)

: Not regulated for transportation.



MATERIAL SAFETY DATA SHEET

WB180 CLEAR

 Version Number 1.0
 Page 5 of 6

 Revision Date 06/13/2002
 Print Date 11/5/2011

ICAO/IATA : Not regulated for transportation.

IMO / IMDG : Not regulated for transportation.

15. REGULATORY INFORMATION

US Regulations:

OSHA Status : There are no known hazardous components above regulatory

thresholds in this product.

TSCA Status : All components of this product are listed on the TSCA inventory or are

exempt.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	% in Product	RQ for component	RQ for
				Mixture/Product
Ammonia,	7664-41-7	0.07	100lbs	131,752 LB
anhydrous				

California Proposition : WARNING! This product contains a chemical known in the State of

65

California to cause cancer.

Not applicable Canadian Regulations:

WHMIS Classification : Not controlled.

DSL : Listed.

National Inventories:

Australia AICS : Listed.

China IECS : Listed.

Europe EINECS : Not determined.

Japan ENCS : Not determined.

Korea KECI : Listed.

Philippines PICCS : Not determined.

16. OTHER INFORMATION



MATERIAL SAFETY DATA SHEET

WB180 CLEAR

V R

ersion Number 1.0 Levision Date 06/13/2002	Page 6 of 6 Print Date 11/5/2011
The information provided in this Safety Data Sheet is correct to the best of or belief at the date of its publication. The information given is designed only as processing, storage, transportation, disposal and release and is not to be consispecification. The information relates only to the specific material designated material used in combination with any other materials or in any process, unless	a guidance for safe handling, use, dered a warranty or quality and may not be valid for such