

# MATERIAL SAFETY DATA SHEET

#### F519 NEUTRAL FROG

Version Number 1.0 Revision Date 03/04/2004 Page 1 of 6 Print Date 11/14/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	F519 NEUTRAL FROG
Product code	:	FO00011326
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
1,2-Benzenedicarboxylic acid, butyl	85-68-7	30 - 60
phenylmethylester		

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



## MATERIAL SAFETY DATA SHEET F519 NEUTRAL FROG

Version Number 1.0 Revision Date 03/04/2004 Page 2 of 6 Print Date 11/14/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>No data available</li> <li>No data available</li> <li>Not applicable</li> <li>Carbon dioxide blanket, water spray, dry powder, foamnone.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



# MATERIAL SAFETY DATA SHEET **F519 NEUTRAL FROG**

ion Number 1.0 sion Date 03/04/2004		Page 3 Print Date 11/14/2
Handling	fume condensate	as with appropriate exhaust ventilation. Processing es may contain combustible or toxic residue. an hoods, ducts, and other surfaces to minimize these materials.
Storage		dry and tightly closed to avoid moisture absorption on. Store in a cool dry place.
8. EXP	OSURE CONTROLS	/ PERSONAL PROTECTION
Respiratory protection	: Under normal ha	andling conditions a respirator may not be required.
Eye/Face Protection	: Safety glasses w	/ith side-shields.
Hand protection	: Protective glove	·8.
Skin and body protection	: Long sleeved cle	othing.
Additional Protective Measures	: Safety shoes.	
General Hygiene Considerations		dance with good industrial hygiene and safety practic ore breaks and at the end of workday.
Engineering measures		as with appropriate exhaust ventilation. Provide aust ventilation at machinery.
Exposure limit(s)		
9.	PHYSICAL AND CH	EMICAL PROPERTIES
Form	: liquid	Evaporation rate : Not established
Appearance	: Viscous, liquid	Specific Gravity: : Not determined
Color	: NO PIGMENT	Bulk density : Not applicable
Odor	: Very faint	Vapor pressure : Not determined
	: Not applicable	Vapour density : Not determined
Melting point/range	: Not applicable	pH : Not applicable
Melting point/range Boiling Point: Water solubility	: Immiscible	
Boiling Point:	: Immiscible	AND REACTIVITY
Boiling Point:	: Immiscible	
Boiling Point: Water solubility Stability	: Immiscible 10. STABILITY A	
Boiling Point: Water solubility	<ul> <li>: Immiscible</li> <li>10. STABILITY A</li> <li>: Stable.</li> <li>: Will not occur.</li> </ul>	ND REACTIVITY



# MATERIAL SAFETY DATA SHEET **F519 NEUTRAL FROG**

Version Number 1.0 Revision Date 03/04/2004

Page 4 of 6 Print Date 11/14/2011

Incompatible Materials	:	Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

#### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
85-68-7	1,2-Benzenedicarboxylic acid, butyl phenylmethylester	Irritant	Eyes, Skin.
		Systemic effects	Liver, reproductive system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
85-68-7	1,2-Benzenedicarboxylic acid, butyl phenylmethylester	Oral LD50 Dermal LD50	2,330 mg/kg > 10 gm/kg	rat rabbit

#### **12. ECOLOGICAL INFORMATION**

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: No data available
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

POLYONE CORPOR	RATION		I	<u>olyOne</u>
MATERIAL SAFETY DATA				
F519 NEUTRAL FRO				
Version Number 1.0 Revision Date 03/04/2004				Page 5 of 6 Print Date 11/14/2011
Contaminated packaging	has the and dis	responsibility for	r proper waste classifi	nerator of waste material ication, transportation deral, state/provincial
	14. TRA	NSPORT INFO	RMATION	
U.S. DOT Classification Proper Shipping Name: Technical Name: Hazard Class / Division UN Number Packing Group Label Required Hazardous Substance Reportable quantity:	9 UN3082 III 9	ntally hazardous : yl phthalate	substances, liquid, n.c	).S.
ICAO/IATA (air)	Refer to sp	ecific regulation.		
IMO / IMDG (maritime)	Refer to sp	ecific regulation.		
	15. REGU	LATORY INFO	ORMATION	
US Regulations: OSHA Status TSCA Status		mponents of this j	based on components	r exempt from the TSCA
US. EPA CERCLA Hazard	ous Substances (	(40 CFR 302)		
Chemical Name	CAS-No.	% in Product	RQ for component	RQ for Mixture/Product
1,2-Benzenedicarb oxylic acid, butyl phenylmethylester	85-68-7	50.9970	100 lbs	196 LB

California Proposition 65

 WARNING! This product contains a chemical known to the State of California to cause cancer., WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

SARA Title III Section 302 Extremely Hazardous Substance

PolyOne

### MATERIAL SAFETY DATA SHEET F519 NEUTRAL FROG

Version Number 1.0 Revision Date 03/04/2004

Page 6 of 6 Print Date 11/14/2011

Not applicable

SARA Title III Section 313 Toxic Chemicals:

Not applicable Canadian Regulations:

Lead Stearate			7428-48-0	0.43	246
1,2-Benzenedicarboxylic	acid, bu	tyl	85-68-7	50.99	37
phenylmethylester					
WHMIS Classification	n : E	2B			
WHMIS Ingredient Dis	sclosure	List			
CAS-No.					
85-68-7					
DSL	•	All components of	f this product are of	n the Canadia	n Domestic
DOL		ubstances List (D			n Domestie
		1051111005 <u>2151</u> (2	SL) of are exempt.		
onal Inventories:			ost) of are exempt.		
onal Inventories: Australia AICS		ot determined	(SL) of are exempt.		
	: N		(SL) of are exempt.		
Australia AICS	: N : N	ot determined	(SL) of are exempt.		
Australia AICS China IECS	: N : N : N	ot determined	(SL) of are exempt.		
Australia AICS China IECS Europe EINECS	: N : N : N : N	ot determined ot determined ot determined	(SL) of are exempt.		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.