

MATERIAL SAFETY DATA SHEET

F520 BLACK FOAM

Version Number 1.1 Revision Date 03/04/2004 Page 1 of 7 Print Date *11/14/2011*

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	F520 BLACK FOAM
Product code	:	FO00011327
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Azodicarbonamide	123-77-3	1 - 5
1,2-Benzenedicarboxylic acid, butyl	85-68-7	10 - 30
phenylmethylester		

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET **F520 BLACK FOAM**

Version Number 1.1 Revision Date 03/04/2004 Page 2 of 7 Print Date 11/14/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 No data available No data available Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



MATERIAL SAFETY DATA SHEET F520 BLACK FOAM

ion Number 1.1 sion Date 03/04/2004		Pa Print Date 11/	ge 3 /1 <i>4/2</i>
Handling	fume condensates n	with appropriate exhaust ventilation. Process hay contain combustible or toxic residue. oods, ducts, and other surfaces to minimize se materials.	ng
Storage		and tightly closed to avoid moisture absorpt Store in a cool dry place.	ion
8. EXP	OSURE CONTROLS / PI	ERSONAL PROTECTION	
Respiratory protection	: Under normal hand	ing conditions a respirator may not be requir	ed.
Eye/Face Protection	: Safety glasses with	side-shields.	
Hand protection	: Protective gloves.		
Skin and body protection	: Long sleeved clothi	ng.	
Additional Protective Measures	: Safety shoes.		
General Hygiene Considerations		e with good industrial hygiene and safety pra breaks and at the end of workday.	ctice
Engineering measures		vith appropriate exhaust ventilation. Provide ventilation at machinery.	
Exposure limit(s)			
9.	PHYSICAL AND CHEM	ICAL PROPERTIES	
Form	: liquid	Evaporation rate : Not establish	
Appearance	: Viscous, liquid	Specific Gravity: : Not determine Built density : Not applied	
Color Odor	: BLACK : Very faint	Bulk density: Not applicatVapor pressure: Not determine	
Melting point/range	: Not applicable	Vapour density : Not determine	
Boiling Point:	: Not applicable	pH : Not applicat	le
Water solubility	: Immiscible		
	10. STABILITY AND	REACTIVITY	
Stability	: Stable.		
Stability Hazardous Polymerization	Stable.Will not occur.		
·	: Will not occur.	idizing agents and open flame. To avoid the not overheat.	mal



MATERIAL SAFETY DATA SHEET **F520 BLACK FOAM**

Version Number 1.1 Revision Date 03/04/2004

Page 4 of 7 Print Date 11/14/2011

Incompatible Materials	:	Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
123-77-3	Azodicarbonamide	sensitizer	Respiratory system.
85-68-7	1,2-Benzenedicarboxylic acid, butyl phenylmethylester	Irritant	Eyes, Skin.
		Systemic effects	Liver, reproductive system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
123-77-3	Azodicarbonamide	LC50	200 mg/l	rat
		Oral LD50	> 6,400 mg/kg	rat
		Dermal LD50	> 2,000 mg/kg	rabbit
85-68-7	1,2-Benzenedicarboxylic	Oral LD50	2,330 mg/kg	rat
	acid, butyl	Dermal LD50	> 10 gm/kg	rabbit
	phenylmethylester		_	

Additional Health Hazard Information:

Azodicarbonamide 123-77-3 Sensitizer to the respiratory system with repeated minimal inhalation. While no chronic health problems have been identified, individuals with respiratory problems should avoid inhalation exposure to this material.

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	:	No data available



MATERIAL SAFETY DATA SHEET **F520 BLACK FOAM**

Version Number 1.1 Revision Date 03/04/2004 Page 5 of 7 Print Date 11/14/2011

Additional advice : No data available					
	13. DISI	POSAL CONSIDE	RATIONS		
Product	genera classi	ator of waste mater fication, transportat	is preferred to disposibility of the second se	cordance with	
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				
	14. TRA	NSPORT INFOR	MATION		
U.S. DOT Classification Proper Shipping Name: Technical Name:		entally hazardous s	ubstances, liquid, n.o.	s.	
Hazard Class / Division UN Number	9 UN3082				
Packing Group	III				
Label Required	9				
Hazardous Substance		zyl phthalate			
Reportable quantity:	608 LB				
ICAO/IATA (air)	Refer to s	pecific regulation.			
IMO / IMDG (maritime)	Refer to specific regulation.				
	15. REG	ULATORY INFO	RMATION		
US Regulations:					
OSHA Status	: Classi	fied as hazardous t	ased on components.		
TSCA Status	: All co Inven	1 1	roduct are listed on or	exempt from the TSCA	
US. EPA CERCLA Hazard	ous Substances	(40 CFR 302)			
Chemical Name	CAS-No.	% in Product	RQ for component	RQ for Mixture/Product	
1,2-Benzenedicarb oxylic acid, butyl phenylmethylester	85-68-7	16.4475	100 lbs	608 LB	

POLYONE	CORPOR	ATION



MATERIAL SAFETY DATA SHEET **F520 BLACK FOAM**

Version Number 1.1 Revision Date 03/04/2004 Page 6 of 7 Print Date 11/14/2011

California Proposition : WARNING! This product contains a chemical known to the State of 65 California to cause cancer., WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

SARA Title III Section 302 Extremely Hazardous Substance

Not applicable

SARA Title III Section 313 Toxic Chemicals:

Not applicable Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
1,2-Benzenedicarboxylic acid, butyl	85-68-7	16.44	37
phenylmethylester			

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
85-68-7	

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

- Australia AICS : Not determined
- China IECS : Not determined
- Europe EINECS : Not determined

:

- Japan ENCS : Not determined
- Korea KECI : Not determined
- Philippines PICCS : Not determined

16. OTHER INFORMATION



MATERIAL SAFETY DATA SHEET **F520 BLACK FOAM**

Version Number 1.1 Revision Date 03/04/2004

Page 7 of 7 Print Date 11/14/2011

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.