

#### A1423 BROWN

Version Number 1.8 Page 1 of 20 Print Date 06/15/2021 Revision Date 06/14/2021

# SAFETY DATA SHEET

#### A1423 BROWN

### **Section 1. Identification**

A1423 BROWN **GHS** product identifier

Chemical name Mixture CAS number Mixture Other means of identification FO00011328 **Product type** liquid

Relevant identified uses of the substance or mixture and uses advised against

Product use Industrial applications. Plastics.

Supplier's details AVIENT CORPORATION

33587 Walker Road, Avon Lake, OH 44012

1 (440) 930-1000 or 1 (844) 4AVIENT

**Emergency telephone number** 

CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or (with hours of operation)

accident).

## Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

**OSHA/HCS status** This material is considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200).

Classification of the substance or

mixture

FLAMMABLE LIQUIDS - Category 2 SKIN IRRITATION - Category 2

EYE IRRITATION - Category 2A **CARCINOGENICITY - Category 2** 

#### **GHS** label elements



#### A1423 BROWN

Version Number 1.8 Revision Date 06/14/2021 Page 2 of 20 Print Date 06/15/2021

Hazard pictograms



Signal word : Danger

**Hazard statements**: Highly flammable liquid and vapor.

Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer.

**Precautionary statements** 

: Not applicable.

**Prevention** : Obtain special instructions before use. Wear protective gloves. Wear

protective clothing. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating or lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Keep container tightly closed. Wash thoroughly after

handling.

**Response**: IF exposed or concerned: Get medical advice or attention. Take off

contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or

attention.

Storage : Store in a well-ventilated place. Keep cool.

**Disposal** : Dispose of contents and container in accordance with all local,

regional, national and international regulations.

Supplemental label elements Hazards not otherwise classified None known.

None known.

Not available.

## Section 3. Composition/information on ingredients

Substance/mixture: MixtureChemical name: MixtureOther means of identification: FO00011328

CAS number/other identifiers

T 10	0.7	CAC 1
Ingredient name	1 %	CAS number



#### A1423 BROWN

Version Number 1.8 Revision Date 06/14/2021 Page 3 of 20 Print Date 06/15/2021

Methyl ethyl ketone	>= 25 - <= 40	78-93-3
Furan, tetrahydro-	>= 25 - <= 37	109-99-9
Bis(2,6-diisopropylphenyl)carbodiimide	>= 1 - <= 2.5	2162-74-5
Titanium dioxide	> 0 - <= 0.3	13463-67-7
Carbon black	> 0 - <= 0.3	1333-86-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

#### **Description of necessary first aid measures**

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	:	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get



#### A1423 BROWN

Version Number 1.8 Page 4 of 20 Revision Date 06/14/2021 Print Date 06/15/2021

medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact** : Causes skin irritation.

**Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

**Eye contact** : Adverse symptoms may include the following:

pain or irritation

watering

redness

**Inhalation** : No specific data.

**Skin contact** : Adverse symptoms may include the following:

irritation redness

**Ingestion** : No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

**Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms

may be delayed. The exposed person may need to be kept under

medical surveillance for 48 hours.

**Specific treatments** : No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without

suitable training. It may be dangerous to the person providing aid to

give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

#### **Extinguishing media**

**Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

**Unsuitable extinguishing media** : Do not use water jet.



#### A1423 BROWN

Version Number 1.8 Revision Date 06/14/2021

Page 5 of 20 Print Date 06/15/2021

Specific hazards arising from the chemical

Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

Hazardous thermal decomposition products Decomposition products may include the following materials: carbon dioxide

carbon monoxide nitrogen oxides

Special protective actions for firefighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fireexposed containers cool.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel No action shall be taken involving any personal risk or without

> suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is

inadequate. Put on appropriate personal protective equipment. For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

See also the information in "For non-emergency personnel".

**Environmental precautions** Avoid dispersal of spilled material and runoff and contact with soil,

waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil

or air).

#### Methods and materials for containment and cleaning up

Stop leak if without risk. Move containers from spill area. Use spark-Small spill

> proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Stop leak if without risk. Move containers from spill area. Use spark-

Large spill



#### A1423 BROWN

Version Number 1.8 Revision Date 06/14/2021 Page 6 of 20 Print Date 06/15/2021

proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

#### **Precautions for safe handling**

#### **Protective measures**

Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

# Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.



## A1423 BROWN

Version Number 1.8 Revision Date 06/14/2021 Page 7 of 20 Print Date 06/15/2021

# Section 8. Exposure controls/personal protection

#### **Control parameters**

#### Occupational exposure limits

Ingredient name	Exposure limits
Methyl ethyl ketone	OSHA PEL 1989 (1989-03-01) TWA 590 mg/m3 200 ppm STEL 885 mg/m3 300 ppm OSHA PEL (1993-06-30) TWA 590 mg/m3 200 ppm NIOSH REL (1994-06-01) TWA 590 mg/m3 200 ppm STEL 885 mg/m3 300 ppm ACGIH TLV (1994-09-01) TWA 590 mg/m3 200 ppm STEL 885 mg/m3 300 ppm STEL 885 mg/m3 300 ppm
Furan, tetrahydro-	OSHA PEL 1989 (1989-03-01) TWA 590 mg/m3 200 ppm STEL 735 mg/m3 250 ppm OSHA PEL (1993-06-30) TWA 590 mg/m3 200 ppm NIOSH REL (1994-06-01) TWA 590 mg/m3 200 ppm STEL 735 mg/m3 250 ppm ACGIH TLV (2005-01-01) Absorbed through skin. TWA 50 ppm STEL 100 ppm
Bis(2,6-diisopropylphenyl)carbodiimide	None.
Titanium dioxide	OSHA PEL 1989 (1989-03-01) TWA 10 mg/m3 Form: Total dust OSHA PEL (1993-06-30) TWA 15 mg/m3 Form: Total dust ACGIH TLV (1996-05-18) TWA 10 mg/m3
Carbon black	OSHA PEL 1989 (1989-03-01) TWA 3.5 mg/m3 OSHA PEL (1993-06-30)



#### A1423 BROWN

Version Number 1.8 Revision Date 06/14/2021 Page 8 of 20 Print Date 06/15/2021

TWA 3.5 mg/m3

NIOSH REL (1994-06-01)

TWA 3.5 mg/m3

NIOSH REL (1994-06-01) TWA 0.1 mgPAH/m<sup>3</sup> ACGIH TLV (2010-12-06)

TWA 3 mg/m3 Form: Inhalable fraction

**Appropriate engineering controls** 

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Environmental exposure controls** 

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

#### **Skin protection**

**Hand protection** 

chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves



#### A1423 BROWN

Version Number 1.8 Revision Date 06/14/2021 Page 9 of 20 Print Date 06/15/2021

cannot be accurately estimated.

**Body protection**: Personal protective equipment for the body should be selected based

on the task being performed and the risks involved and should be approved by a specialist before handling this product., When there is a risk of ignition from static electricity, wear anti-static protective clothing., For the greatest protection from static discharges, clothing

should include anti-static overalls, boots and gloves.

Other skin protection : Appropriate footwear and any additional skin protection measures

should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this

product.

**Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that

meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper

fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

#### **Appearance**

Physical state
Color
BROWN
Odor
Not available.
Odor threshold
pH
Not available.
Melting point
Not available.
Not available.
Not available.
Not available.

Flash point : Closed cup: -9 °C (16 °F)

Burning time: Not available.Burning rate: Not available.Evaporation rate: Not available.Flammability (solid, gas): Not available.

Lower and upper explosive : Lower: Not available. (flammable) limits : Upper: Not available.

Vapor pressure

Vapor density

Relative density

Solubility

Solubility in water

Partition coefficient: n
Not available.

Not available.

Not available.

Not available.

Not available.

octanol/water

Auto-ignition temperature: Not available.Decomposition temperature: Not available.SADT: Not available.

Viscosity : Dynamic: Not available.



#### A1423 BROWN

Version Number 1.8 Revision Date 06/14/2021 Page 10 of 20 Print Date 06/15/2021

**Kinematic:** Not available.

Aerosol product

**Heat of combustion** : Not available.

**Ignition distance** : Not available. **Enclosed space ignition - Time** : Not available.

equivalent

**Enclosed space ignition -**

**Deflagration density** 

Flame height : Not available. Flame duration : Not available.

## Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or

its ingredients.

Not available.

Chemical stability : Stable under recommended storage and handling conditions (see

Section 7)

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will

not occur.

Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not

pressurize, cut, weld, braze, solder, drill, grind or expose containers to

heat or sources of ignition.

**Incompatible materials** : Reactive or incompatible with the following materials:

oxidizing materials

**Hazardous decomposition** 

products

: Under normal conditions of storage and use, hazardous decomposition

products should not be produced.

## Section 11. Toxicological information

#### Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
2-Butanone				
	LD50 Oral	Rat	2,737 mg/kg	-
	LD50 Dermal	Rabbit	6,480 mg/kg	-
Furan, tetrahydro-				
	LD50 Oral	Rat	1,650 mg/kg	-
Benzenamine, N,N'-methanete	etraylbis[2,6-bis(1-me	ethylethyl)-		
	LD50 Oral	Rat	200 mg/kg	-
Titanium oxide				
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h

10/20



#### A1423 BROWN

Version Number 1.8 Revision Date 06/14/2021 Page 11 of 20 Print Date 06/15/2021

	Dusts and mists			
	LD50 Dermal	Rabbit	> 5,000 mg/kg	=
Carbon black				
	LD50 Oral	Rat	15,400 mg/kg	-

**Conclusion/Summary**: Mixture.Not fully tested.

#### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-Butanone	Skin - Mild irritant	Rabbit	-	24 hrs	-
	Skin - Moderate irritant	Rabbit	-	24 hrs	-
	Skin - Mild irritant	Rabbit	-	24 hrs	-
Titanium oxide	Skin - Mild irritant	Human	-	72 hrs	-

**Conclusion/Summary** 

Skin: Mixture.Not fully tested.Eyes: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

#### Sensitization

Conclusion/Summary

Skin: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

**Mutagenicity** 

**Conclusion/Summary** : Mixture.Not fully tested.

**Carcinogenicity** 

Conclusion/Summary : Mixture.Not fully tested.

#### Classification

Product/ingredient name	OSHA	IARC	NTP
Furan, tetrahydro-	-	2B	-
Titanium oxide	-	2B	-
Carbon black	-	2B	-

#### **Reproductive toxicity**

**Conclusion/Summary**: Mixture.Not fully tested.



#### A1423 BROWN

Version Number 1.8 Page 12 of 20 Revision Date 06/14/2021 Print Date 06/15/2021

#### **Teratogenicity**

**Conclusion/Summary** : Mixture.Not fully tested.

#### Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Not available.

**Information on the likely routes of** : Not available.

exposure

#### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact** : Causes skin irritation.

**Ingestion** : No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following: pain or irritation,

watering, redness

**Inhalation** : No specific data.

**Skin contact**: Adverse symptoms may include the following: irritation, redness

**Ingestion** : No specific data.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

#### **Short term exposure**

Potential immediate effects : Not available.

Potential delayed effects : Not available.

#### Long term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

#### **Potential chronic health effects**

Conclusion/Summary : Mixture.Not fully tested.



#### A1423 BROWN

Version Number 1.8 Page 13 of 20 Revision Date 06/14/2021 Print Date 06/15/2021

**General** : No known significant effects or critical hazards.

Carcinogenicity: Suspected of causing cancer. Risk of cancer depends on duration and

level of exposure.

Mutagenicity: No known significant effects or critical hazards.Teratogenicity: No known significant effects or critical hazards.Developmental effects: No known significant effects or critical hazards.Fertility effects: No known significant effects or critical hazards.

#### **Numerical measures of toxicity**

#### **Acute toxicity estimates**

Product/ingredient name	Oral	Dermal	Inhalation (gases)	Inhalation (vapors)	Inhalation (dusts and mists)
A1423 BROWN	2,632.9 mg/kg	N/A	N/A	N/A	N/A
2-Butanone	2,737 mg/kg	6,480 mg/kg	N/A	N/A	N/A
Furan, tetrahydro-	1,650 mg/kg	N/A	N/A	N/A	N/A
Benzenamine, N,N'- methanetetraylbis[2,6-bis(1- methylethyl)-	200 mg/kg	N/A	N/A	N/A	N/A
Titanium oxide	N/A	N/A	N/A	N/A	6.82 Mg/l
Carbon black	15,400 mg/kg	N/A	N/A	N/A	N/A

**Other information**: This mixture has not been evaluated as a whole for health effects.

Exposure effects listed are based on existing health data for the

individual components which comprise the mixture.

# Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
2-Butanone			
	Acute LC50 3,220 Mg/l Fresh	Fish - Pimephales promelas	96 h
	water		
	Acute EC50 5.091 Mg/l Fresh	Daphnia - Daphnia magna	48 h
	water		
	Acute EC50 > 500 Mg/l Marine	Algae - Skeletonema costatum	96 h



#### A1423 BROWN

Version Number 1.8 Revision Date 06/14/2021 Page 14 of 20 Print Date 06/15/2021

	water		
Furan, tetrahydro-			•
	Acute LC50 2,160 Mg/l Fresh	Fish - Pimephales promelas	96 h
	water		
	Chronic NOEC 367 Mg/l Fresh	Fish - Pimephales promelas	33 d
	water		
Titanium oxide			
	Acute LC50 > 1,000 Mg/l	Fish - Fundulus heteroclitus	96 h
	Marine water		
	Acute LC50 3 Mg/l Fresh water	Crustaceans - Ceriodaphnia	48 h
	_	dubia	
	Acute LC50 6.5 Mg/l Fresh	Daphnia - Daphnia pulex	48 h
	water		
Carbon black			
	Acute EC50 37.563 Mg/l Fresh	Daphnia - Daphnia magna	48 h
	water		

**Conclusion/Summary** : Not available.

Persistence and degradability

**Conclusion/Summary** : Not available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
2-Butanone	0.29	-	low
Furan, tetrahydro-	0.45	-	low

#### **Mobility in soil**

Soil/water partition coefficient

(KOC)

Not available.

Other adverse effects : No known significant effects or critical hazards.

# Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever

possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable



#### A1423 BROWN

Version Number 1.8 Revision Date 06/14/2021 Page 15 of 20 Print Date 06/15/2021

products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

#### United States - RCRA Acute hazardous waste "P" List: Not listed

#### United States - RCRA Toxic hazardous waste "U" List: Listed

Ingredient	CAS#	Status	Reference number
Methyl ethyl ketone	78-93-3	Listed	
Furan, tetrahydro-	109-99-9	Listed	

# **Section 14. Transport information**

U.S.DOT 49CFR

Ground/Air/Water

Proper Shipping Name: Coating solution

Technical Name:

Hazard Class / Division 3

UN Number UN1139
Packing Group II
Label Required 3

Hazardous Substance	RQ for
	Mixture/Product
tetrahydrofuran	

International Air ICAO/IATA

Consult mode specific transport rules

International Water

IMO/IMDG

Consult mode specific transport rules



#### A1423 BROWN

Version Number 1.8 Revision Date 06/14/2021 Page 16 of 20 Print Date 06/15/2021

## Section 15. Regulatory information

U.S. Federal regulations

**United States - TSCA 12(b) - Chemical export notification:** None of the components are listed.

United States - TSCA 4(a) - Final Test Rules: Not listed United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 5(a)2 - Final significant new use rules: Not listed

United States - TSCA 5(a)2 - Proposed significant new use rules: Not listed

United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined

United States - TSCA 8(a) - Preliminary assessment report (PAIR): Listed Furan, tetrahydro-

2,6-Diisopropylphenyl isocyanate

United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed

United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed Benzene, methyl-

United States - EPA Clean water act (CWA) section 311 -

Hazardous substances: Listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Flammable substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Toxic substances: Not listed

**United States - Department of commerce - Precursor chemical:** 

Not listed

Clean Air Act Section 112(b)
Hazardous Air Pollutants (HAPs)
Clean Air Act Section 602 Clean I

Clean Air Act Section 602 Class I

Not listed

Listed

**Substances** 

Not listed

Substances

Not listed

**DEA List I Chemicals (Precursor** 

Clean Air Act Section 602 Class II



### A1423 BROWN

Version Number 1.8 Revision Date 06/14/2021 Page 17 of 20 Print Date 06/15/2021

**Chemicals**)

**DEA List II Chemicals (Essential** 

**Chemicals**)

#### US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	RQ for component
Furan, tetrahydro-	109-99-9	1,000 lb(s) 454 kg
Methyl ethyl ketone	78-93-3	5,000 lb(s) 2,270 kg 2,270 kg 5,000 lb(s)

Listed

#### **SARA 311/312**

Classification : FLAMMABLE LIQUIDS - Category 2

SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A CARCINOGENICITY - Category 2

#### **Composition/information on ingredients**

Name	%	Classification
2-Butanone	>= 25 - <= 40	FLAMMABLE LIQUIDS - Category 2 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A
Furan, tetrahydro-	>= 25 - <= 37	FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY - oral - Category 4 CARCINOGENICITY - Category 2
Benzenamine, N,N'- methanetetraylbis[2,6-bis(1- methylethyl)-	>= 1 - <= 2.5	ACUTE TOXICITY - oral - Category 3
Titanium oxide	> 0 - <= 0.3	CARCINOGENICITY - Category 2
Carbon black	> 0 - <= 0.3	CARCINOGENICITY - Category 2



#### A1423 BROWN

Version Number 1.8 Page 18 of 20 Revision Date 06/14/2021 Print Date 06/15/2021

Not applicable.

**State regulations** 

Massachusetts: None of the components are listed.New York: The following components are listed:

Methyl ethyl ketone Furan, tetrahydro-

**New Jersey** : The following components are listed:

Methyl ethyl ketone Furan, tetrahydro-Titanium dioxide Carbon black

**Pennsylvania** : The following components are listed:

Methyl ethyl ketone

Furan, tetrahydro-

Titanium dioxide

Carbon black

#### California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, which are known to the State of California to cause cancer, and Benzene, methyl-, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Titanium dioxide	-	-
Benzene, methyl-	-	Yes.
Carbon black	-	-

**United States inventory (TSCA 8b)** : All components are active or exempted.

**Canada inventory** : All components are listed or exempted.

**International regulations** 

#### **Inventory list**

Australia: All components are listed or exempted.Canada: All components are listed or exempted.China: All components are listed or exempted.Europe inventory: All components are listed or exempted.Japan: Not determined.New Zealand: All components are listed or exempted.



#### A1423 BROWN

Version Number 1.8 Page 19 of 20 Revision Date 06/14/2021 Print Date 06/15/2021

Philippines: All components are listed or exempted.Republic of Korea: All components are listed or exempted.Taiwan: All components are listed or exempted.

Turkey : Not determined.

**United States** : All components are active or exempted.

## Section 16. Other information

#### Hazardous Material Information System (U.S.A.)

Health	*	2
Flammability		3
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

#### **History**

Date of printing: 06/15/2021Date of issue/Date of revision: 06/14/2021Date of previous issue: 11/07/2018

Version : 1.8

**Key to abbreviations**: ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of

Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

 $MARPOL = International \ Convention \ for \ the \ Prevention \ of \ Pollution \ From$ 

Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine

pollution)

UN = United Nations
Not available

**References** : Not available.

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the



### A1423 BROWN

Version Number 1.8 Revision Date 06/14/2021 Page 20 of 20 Print Date 06/15/2021

sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.