PolvOne

MATERIAL SAFETY DATA SHEET 10940-3 GRAY ELECTRICAL PLASTISOL

Version Number 1.6 Revision Date 11/01/2006 Page 1 of 7 Print Date 11/25/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

| Telephone Emergency telephone number | : | Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident). |
|--|---|--|
| Product name | : | 10940-3 GRAY ELECTRICAL PLASTISOL |
| Product code | : | FO00011871 |
| Chemical Name | : | Mixture |
| CAS-No. | : | Mixture |
| Product Use | : | Industrial Applications |

2. COMPOSITION/INFORMATION ON INGREDIENTS

| Components | CAS-No. | Weight % |
|-----------------------------------|---------------|----------|
| Miscellaneous Irritant | Not Available | 1 - 5 |
| Trimethylopropane trimethacrylate | 3290-92-4 | 5 - 10 |
| Antimony trioxide | 1309-64-4 | 0.1 - 1 |
| Titanium dioxide | 13463-67-7 | 0.1 - 1 |
| Miscellaneous Barium Compounds | Not Available | 1 - 5 |

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

| Routes of Exposure: | : Inhalation, Skin contact, Ingestion |
|---------------------|--|
| Acute exposure | |
| Inhalation | : Inhalation of airborne droplets may cause irritation of the respiratory tract. |
| Ingestion | : May be harmful if swallowed. |
| Eyes | : May cause eye/skin irritation. |
| Skin | : Experience shows no unusual dermatitis hazard from routine handling. |

PolyOne.

MATERIAL SAFETY DATA SHEET 10940-3 GRAY ELECTRICAL PLASTISOL

Version Number 1.6 Revision Date 11/01/2006 Page 2 of 7 Print Date 11/25/2011

| Medical Conditions Aggravated by Exposure: | : None known. |
|---|---|
| | 4. FIRST AID MEASURES |
| Inhalation | : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice. |
| Ingestion | : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. |
| Eyes | : Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention. |
| Skin | : Wash off with soap and plenty of water. If skin irritation persists seel medical attention. |
| | 5. FIRE-FIGHTING MEASURES |
| Flash point | : No data available |
| Flammable Limits | |
| Upper explosion limit | : No data available |
| Lower explosion limit | : No data available |
| Autoignition temperature | : Not applicable |
| Suitable extinguishing media | : Carbon dioxide blanket, water spray, dry powder, foam. |
| Special Fire Fighting Procedures | : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne |
| | contaminants. |
| Unusual Fire/Explosion | : May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under |
| Hazards | fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. |
| | 6. ACCIDENTAL RELEASE MEASURES |
| Personal precautions | : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. |
| Environmental precautions | : The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment. |
| Methods for cleaning up | : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods. |

<u>PolyOne</u>.

MATERIAL SAFETY DATA SHEET 10940-3 GRAY ELECTRICAL PLASTISOL

Version Number 1.6 Revision Date 11/01/2006

_

-

Page 3 of 7 Print Date 11/25/2011

| | 7. | HANDLING AND STORAG | E | | | |
|-----------------------------------|-----------|--|-----------------------|---------------|--|--|
| Handling | fi P | Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials. | | | | |
| Storage | | Keep containers dry and tightly on contamination. Store in a co | | re absorption | | |
| 8. I | EXPOSURE | CONTROLS / PERSONAL | PROTECTION | | | |
| Respiratory protection | : N | to personal respiratory protective | ve equipment normally | required. | | |
| Eye/Face Protection | : S | afety glasses with side-shields. | | | | |
| Hand protection | : P | Protective gloves. | | | | |
| Skin and body protection | : L | Long sleeved clothing. | | | | |
| Additional Protective Measures | : S | Safety shoes. | | | | |
| General Hygiene Considerations | | Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. | | | | |
| Engineering measures | | leat only in areas with appropri ppropriate exhaust ventilation a | | Provide | | |
| Exposure limit(s) | | | | | | |
| Components | Value | Exposure time | Exposure type | List: | | |
| Antimony trioxide | 0.5 mg/m3 | PEL: | as Sb | OSHA Z1 | | |
| | 0.5 mg/m3 | Time Weighted Average (TWA): | as Sb | ACGIH | | |
| Titanium dioxide | 10 mg/m3 | Time Weighted Average (TWA): | | ACGIH | | |
| | 15 mg/m3 | PEL: | Total dust. | OSHA Z1 | | |
| | 20 mg/m3 | Short Term Exposure Limit | as Ti | MX OEL | | |

| | 20 mg/m3 | Short Term Exposure Limit | as Ti | MX OEL |
|----------------------|-----------|---------------------------|-------|---------|
| | | (STEL): | | |
| Miscellaneous Barium | 0.5 mg/m3 | Time Weighted Average | as Ba | ACGIH |
| Compounds | | (TWA): | | |
| | 0.5 mg/m3 | PEL: | as Ba | OSHA Z1 |
| | | | | |

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance liquidViscous, liquid

Evaporation rate Specific Gravity: Not establishedNot determined

MATERIAL SAFETY DATA SHEET 10940-3 GRAY ELECTRICAL PLASTISOL

: GREY

: Very faint

Version Number 1.6 Revision Date 11/01/2006

Color

Odor

| Melting point/range Boiling Point: Water solubility | : Not applicable : Not applicable : Immiscible | Vapour density pH | : Not determined : Not applicable |
|---|---|--|--|
| | 10. STABILITY AN | ND REACTIVITY | |
| Stability | : Stable. | | |
| Hazardous Polymerization | : Will not occur. | | |
| Conditions to avoid | : Keep away from decomposition, de | oxidizing agents and open ont overheat. | flame. To avoid thermal |
| Incompatible Materials | 1 | n strong acids and oxidizin polymers and acetal copoly | |
| Hazardous decomposition products | (NOx), hydrogen smoke are all pos degradation. As a | CO2), carbon monoxide (C chloride (HCl), other haza sible. Prolonged heating n a general rule of thumb, de 177 °C (350 °F), after 10 m | rdous materials, and may result in product gradation begins to occur |

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

and within 5 minutes at 232 °C (450 °F).

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

| CAS-No. | Chemical Name | Effect | Target Organ |
|---------------|--------------------------------------|------------------|---------------------------|
| Not Available | Miscellaneous Irritant | sensitizer | Skin. |
| | | Irritant | Eyes, Skin. |
| 3290-92-4 | Trimethylopropane trimethacrylate | Irritant | Eyes, Skin. |
| 1309-64-4 | Antimony trioxide | Systemic effects | Eyes, Respiratory system. |
| | | sensitizer | Skin. |
| 13463-67-7 | Titanium dioxide | Systemic effects | Respiratory system. |
| Not Available | Miscellaneous Barium Compounds | Irritant | Respiratory system, Eyes. |
| | | Systemic effects | Respiratory system. |

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

| CAS-No. | Chemical Name | Route | Value | Species |
|-----------|-------------------|-----------|----------------|---------|
| 1309-64-4 | Antimony trioxide | Oral LD50 | > 34,600 mg/kg | rat |
| | | | | |

Page 4 of 7

: Not applicable : Not determined

Print Date 11/25/2011



Bulk density

Vapor pressure



MATERIAL SAFETY DATA SHEET 10940-3 GRAY ELECTRICAL PLASTISOL

Version Number 1.6 Revision Date 11/01/2006 Page 5 of 7 Print Date 11/25/2011

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

| CAS-No. | Chemical Name | OSHA | IARC | NTP |
|------------|-------------------|------|------|-----|
| 1309-64-4 | Antimony trioxide | no | 2B | no |
| 13463-67-7 | Titanium dioxide | no | 2B | no |

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Antimony trioxide 1309-64-4 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

| | 12. ECOLOGICAL INFORMATION |
|-------------------------------|--|
| Persistence and degradability | : Not readily biodegradable. |
| Environmental Toxicity | : Environmental toxicity has not been established for this mixture as a whole. |
| Bioaccumulation Potential | : No data available |
| Additional advice | : No data available |
| | 13. DISPOSAL CONSIDERATIONS |
| Product | : Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. |
| Contaminated packaging | : Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. |
| | 14. TRANSPORT INFORMATION |
| U.S. DOT Classification | : Refer to specific regulation. |

PolyOne.

MATERIAL SAFETY DATA SHEET 10940-3 GRAY ELECTRICAL PLASTISOL

| ion Number 1.6 sion Date 11/01/2006 | | | | | | Pri | nt Date | Page 6 11/25/2 |
|--|--------|----------------------------------|-------------|-------------------------------------|----------|-----------------------------|------------|-------------------|
| | | | | | | | | |
| ICAO/IATA (air) | : | Refer to specific | regulatio | on. | | | | |
| IMO / IMDG (maritime) | : | Refer to specific | regulatio | on. | | | | |
| | 15 | 5. REGULATOR | Y INFO | RMATION | N | | | |
| US Regulations: | | | | | | | | |
| OSHA Status | : | Classified as haz | ardous b | ased on con | mponen | ts. | | |
| TSCA Status | : | All components Inventory. | of this p | oduct are l | isted on | or exem | pt from th | ne TSCA |
| US. EPA CERCLA Hazardous | Sub | stances (40 CFR 3 | 302) | | | | | |
| Not applicable | | | | | | | | |
| California Proposition 65 | : | WARNING! Th California to cau | - | | a chemi | cal knov | wn to the | State of |
| SARA Title III Section 302 Ex | trem | ely Hazardous Sul | bstance | | | | | |
| Unless specific chemicals are id | denti | fied under this sec | ction, this | product is | Not Ap | plicable | under thi | is regula |
| SARA Title III Section 313 To Unless specific chemicals are is Chemical Name BARIUM COMPOUNDS | | | ction, this | product is CAS-No. Not Availa | Î | plicable Weigh 0.10 - | t % | is regula |
| Canadian Regulations: | | | | | | | | |
| National Pollutant Relea | ise Ii | nventory (NPRI) | | | | | | |
| Chemical Name | | | CAS-N | | Weigh | | NPRI I | D# |
| Antimony trioxide | | | 1309-64 | | 0.10 - | | 17 | |
| Miscellaneous Zinc Compou | nas | | Not Av | | 0.10 - | 1.00 | 241 | |
| WHMIS Classification | : | D2A | | | | | | |
| WHMIS Ingredient Disc | closu | ire List | | | | | | |
| | | | | | | | | |
| | | | | | | | | |

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET 10940-3 GRAY ELECTRICAL PLASTISOL

| Version Number 1.6 Revision Date 11/01/2006 | | Page 7 of 7 Print Date <i>11/25/2011</i> |
|--|---|---|
| CAS-No. Not Available DSL | : | All of the components of this product are listed on the Canadian Inventories or are exempt. However, at least one component of this product is on the Canadian Non-Domestic Substances List (NDSL). Quantity use in Canada is restricted by regulations. |
| National Inventories: | | |
| Australia AICS | : | Not determined |
| China IECS | : | Not determined |
| Europe EINECS | : | Not determined |
| Japan ENCS | : | Not determined |
| Korea KECI | : | Not determined |
| Philippines PICCS | : | Not determined |
| 16. OTHER INFORMATION | | |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.