

### MATERIAL SAFETY DATA SHEET

## 90410MP SUPER FLUO. PINK

Version Number 1.0 Page 1 of 7
Revision Date 02/27/2003 Print Date 11/10/2011

## 1. PRODUCT AND COMPANY IDENTIFICATION

### POLYONE CORPORATION

2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY : Product Stewardship, (314) 771-1800

TELEPHONE

Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure

number or accident).

Product name : 90410MP SUPER FLUO. PINK

Product code : FO00012382 Chemical Name : Mixture CAS-No. : Mixture

Product Use : Industrial Applications

## 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

| Components                             | CAS-No.     | Weight % |
|--|-------------|----------|
| Silica, amorphous, fumed, crystal-free | 112945-52-5 | 1 - 5    |
| Titanium dioxide                       | 13463-67-7  | 1 - 5    |
| Calcium carbonate                      | 471-34-1    | 10 - 30  |
| Zinc oxide                             | 1314-13-2   | 10 - 30  |

# 3. HAZARDS IDENTIFICATION

## **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

## POTENTIAL HEALTH EFFECTS

**Routes of Exposure:** : Inhalation, Skin contact, Ingestion

Acute exposure

Inhalation : Inhalation of airborne droplets may cause irritation of the respiratory

tract.

Ingestion : May be harmful if swallowed. Eyes : May cause eye/skin irritation.

Skin : Experience shows no unusual dermatitis hazard from routine handling.

**Chronic exposure** : Refer to Section 11 for Toxicological Information.



### MATERIAL SAFETY DATA SHEET

## 90410MP SUPER FLUO. PINK

 Version Number 1.0
 Page 2 of 7

 Revision Date 02/27/2003
 Print Date 11/10/2011

Medical Conditions Aggravated by Exposure: : None known.

## 4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of fumes from

overheating or combustion. When symptoms persist or in all cases of

doubt seek medical advice.

Ingestion : Do not induce vomiting without medical advice. When symptoms

persist or in all cases of doubt seek medical advice.

Eyes : Rinse immediately with plenty of water for at least 15 minutes. If eye

irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists seek

medical attention.

## **5. FIRE-FIGHTING MEASURES**

Flash point : No data available.

Flammable Limits

Upper explosion limit : No data available.

Lower explosion limit : No data available.

Autoignition temperature : Not applicable.

Suitable extinguishing media : Carbon dioxide blanket, dry powder, foam, Water spray.

Special Fire Fighting

Procedures

: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne

contaminants.

Unusual Fire/Explosion

Hazards

: May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under

fire conditions.

## 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear appropriate personal protection during cleanup, such as

impervious gloves, boots and coveralls.

Environmental precautions : Should not be released into the environment. The product should not

be allowed to enter drains, water courses or the soil.

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder,

universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper

disposal methods.

## 7. HANDLING AND STORAGE



### MATERIAL SAFETY DATA SHEET

# 90410MP SUPER FLUO. PINK

 Version Number 1.0
 Page 3 of 7

 Revision Date 02/27/2003
 Print Date 11/10/2011

Handling : Heat only in areas with appropriate exhaust ventilation. Processing

fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize

accumulation of these materials.

Storage : Keep containers dry and tightly closed to avoid moisture absorption

and contamination. Store in a cool dry place.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection : Under normal handling conditions a respirator may not be required.

Eye/Face Protection : Safety glasses with side-shields.

Hand protection : Protective gloves.

Skin and body protection : Long sleeved clothing.

Additional Protective

Measures

Safety shoes.

General Hygiene

Considerations

: Handle in accordance with good industrial hygiene and safety practice.

Wash hands before breaks and at the end of workday.

Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide

appropriate exhaust ventilation at machinery.

Exposure limit(s)



### MATERIAL SAFETY DATA SHEET

# 90410MP SUPER FLUO. PINK

 Version Number 1.0
 Page 4 of 7

 Revision Date 02/27/2003
 Print Date 11/10/2011

| Components                             | Value    | Exposure time                     | Exposure type          | List:   |
|--|----------|-----------------------------------|------------------------|---------|
| Calcium carbonate                      | 5 mg/m3  | PEL: Respirable fraction.         |                        | OSHA Z1 |
|  | 15 mg/m3 | PEL:                              | Total dust.            | OSHA Z1 |
|  | 5 mg/m3  | PEL:                              | Respirable fraction.   | OSHA Z1 |
|  | 15 mg/m3 | PEL:                              | Total dust.            | OSHA Z1 |
| Silica, amorphous, fumed, crystal-free | 20 mppcf | PEL:                              | Total dust.            | Z3      |
| Titanium dioxide                       | 10 mg/m3 | Time Weighted Average (TWA):      | Dust.                  | ACGIH   |
| Titanium dioxide                       | 15 mg/m3 | PEL:                              | Total dust.            | OSHA Z1 |
| Zinc oxide                             | 10 mg/m3 | Time Weighted Average (TWA):      | Total dust. as Zn      | ACGIH   |
|  | 5 mg/m3  | PEL:                              | Respirable dust. as Zn | OSHA Z1 |
|  | 15 mg/m3 | PEL:                              | Total dust. as Zn      | OSHA Z1 |
| Zinc oxide                             | 5 mg/m3  | Time Weighted Average (TWA):      | Fume.                  | MX OEL  |
|  | 10 mg/m3 | Time Weighted Average (TWA):      | Dust.                  | MX OEL  |
|  | 10 mg/m3 | Short Term Exposure Limit (STEL): | Fume.                  | MX OEL  |

## 9. PHYSICAL AND CHEMICAL PROPERTIES

: Liquid Evaporation rate Not established Form Viscous, Liquid Specific Gravity Not determined Appearance **PINK** Bulk density Color Not applicable. Very faint Vapor pressure Not determined Odor Not applicable Melting point/range Vapor density Not determined **Boiling Point:** Not applicable pН : Not applicable.

Water solubility : Immiscible

## 10. STABILITY AND REACTIVITY

Stability : Stable.

Hazardous Polymerization : Will not occur.

Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal

decomposition, do not overheat.

Incompatible Materials : Incompatible with strong acids and oxidizing agents. Avoid contact

with acetal homopolymers and acetal copolymers during processing.

Hazardous decomposition

products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product

degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F),

and within 5 minutes at 232 °C (450 °F).



### MATERIAL SAFETY DATA SHEET

## 90410MP SUPER FLUO. PINK

 Version Number 1.0
 Page 5 of 7

 Revision Date 02/27/2003
 Print Date 11/10/2011

## 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

| CAS-No.     | Chemical Name             | Effect           | Target Organ              |
|-------------|---------------------------|------------------|---------------------------|
| 112945-52-5 | Silica, amorphous, fumed, | Irritant         | Eyes, Respiratory system. |
|             | crystal-free              |                  |                           |
| 13463-67-7  | Titanium dioxide          | Systemic effects | Respiratory system.       |
| 471-34-1    | Calcium carbonate         | Irritant         | Eyes, Skin.               |
| 1314-13-2   | Zinc oxide                | Systemic effects | Respiratory system.       |

#### LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

| CAS-No.     | Chemical Name             | Route     | Value       | Species |
|-------------|---------------------------|-----------|-------------|---------|
| 112945-52-5 | Silica, amorphous, fumed, | Oral LD50 | 3,160 mg/kg | rat     |
|             | crystal-free              |           |             |         |
| 471-34-1    | Calcium carbonate         | Oral LD50 | 6,450 mg/kg | rat     |
| 1314-13-2   | Zinc oxide                | LC50      | 2500 mg/m3  | mouse   |
|             |                           | Oral LD50 | 7,950 mg/kg | mouse   |

## 12. ECOLOGICAL INFORMATION

Persistence and degradability : Not readily biodegradable.

Environmental Toxicity : Environmental toxicity has not been established for this mixture as a

whole.

Bioaccumulation Potential : No data available.

Additional advice : No data available.

## 13. DISPOSAL CONSIDERATIONS

Product : Where possible, recycling is preferred to disposal or incineration. The

generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste material

has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial

and local regulations.

## 14. TRANSPORT INFORMATION



## MATERIAL SAFETY DATA SHEET

# 90410MP SUPER FLUO. PINK

 Version Number 1.0
 Page 6 of 7

 Revision Date 02/27/2003
 Print Date 11/10/2011

U.S. DOT Classification : Refer to specific regulation.

ICAO/IATA : Refer to specific regulation.

IMO / IMDG : Refer to specific regulation.

## 15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on or exempt from the TSCA

Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

California Proposition : WARNING! This product contains a chemical known to the State of

65 California to cause cancer.

SARA Title III Section 302 Extremely Hazardous Substance

Not applicable

SARA Title III Section 313 Toxic Chemicals:

| Chemical Name  | CAS-No.    | Weight % |
|----------------|------------|----------|
| ZINC COMPOUNDS | 1314-13-2  | 12.06    |
| ZINC COMPOUNDS | 73398-89-7 | 00.13    |

## Canadian Regulations:

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No. 1314-13-2

DSL : All components of this product are on the Canadian Domestic



# MATERIAL SAFETY DATA SHEET

# 90410MP SUPER FLUO. PINK

Version Number 1.0 Page 7 of 7
Revision Date 02/27/2003 Print Date 11/10/2011

Substances List (DSL) or are exempt.

National Inventories:

Australia AICS : Listed.

China IECS : Not determined.

Europe EINECS : Not determined.

Japan ENCS : Not determined.

Korea KECI : Not determined.

Philippines PICCS : Not determined.

## 16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.