

MATERIAL SAFETY DATA SHEET

SX400BK BLACK REFLECTIVE

Version Number 1.0 Revision Date 03/04/2003 Page 1 of 7 Print Date *11/10/2011*

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	SX400BK BLACK REFLECTIVE
Product code	:	FO00012769
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Carbon black	1333-86-4	0.1 - 1

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

SX400BK BLACK REFLECTIVE

Version Number 1.0 Revision Date 03/04/2003 Page 2 of 7 Print Date 11/10/2011

	4. FIRST AID MEASURES	
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.	of
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.	
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If e irritation persists, seek medical attention.	ye
Skin	: Wash off with soap and plenty of water. If skin irritation persists se medical attention.	ek
	5. FIRE-FIGHTING MEASURES	
Flash point	: No data available.	
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 No data available. No data available. Not applicable. Carbon dioxide blanket, dry powder, foam, Water spray. 	
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) und fire conditions. 	
	5. ACCIDENTAL RELEASE MEASURES	
	, ACCIDENTAL RELEASE MEASURES	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.	ot
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid bind universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.	
	7. HANDLING AND STORAGE	
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize	



MATERIAL SAFETY DATA SHEET

SX400BK BLACK REFLECTIVE

				ate 11/10/2
	ac	cumulation of these materia	ls.	
Storage		eep containers dry and tightland contamination. Store in a		absorption
8. E	XPOSURE	CONTROLS / PERSONA	L PROTECTION	
Respiratory protection	: U	nder normal handling condit	ions a respirator may not b	e required.
Eye/Face Protection	: Sa	afety glasses with side-shield	ls.	
Hand protection	: Pı	otective gloves.		
Skin and body protection	: Le	ong sleeved clothing.		
Additional Protective Measures	: Sa	afety shoes.		
General Hygiene Considerations		andle in accordance with goo ash hands before breaks and		afety practice
Engineering measures		eat only in areas with appropropriate exhaust ventilation		Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Carbon black	3.5 mg/m3	Time Weighted Average (TWA):	Total dust. as carbon black	ACGIH
Carbon black	3.5 mg/m3	PEL:	Total dust. as carbon black	OSHA Z1
	9. PHYSIC	CAL AND CHEMICAL PR	OPERTIES	
Form	: Liqui			established
Form Appearance	: Liqui : Visco	d Evap	poration rate : Not	established determined
Color	: Visco : BLA	d Evap ous, Liquid Spec CK Bulk	ooration rate : Not ific Gravity : Not density : Not	determined applicable.
Appearance Color Odor	: Visco : BLA : Very	d Evap ous, Liquid Spec CK Bulk faint Vapo	ooration rate : Not ific Gravity : Not density : Not or pressure : Not	determined applicable. determined
Appearance Color Odor Melting point/range	: Visco : BLA : Very : Not a	d Evap ous, Liquid Spec CK Bulk faint Vapo .pplicable Vapo	poration rate: Notific Gravity: Notdensity: Notor pressure: Notor density: Not	determined applicable. determined determined
Appearance Color Odor Melting point/range Boiling Point:	: Visco : BLA : Very : Not a : Not a	d Evap ous, Liquid Spec CK Bulk faint Vapo pplicable Vapo pplicable pH	poration rate: Notific Gravity: Notdensity: Notor pressure: Notor density: Not	determined applicable. determined
Appearance Color Odor Melting point/range	: Visco : BLA : Very : Not a	d Evap ous, Liquid Spec CK Bulk faint Vapo pplicable Vapo pplicable pH	poration rate: Notific Gravity: Notdensity: Notor pressure: Notor density: Not	determined applicable. determined determined
Appearance Color Odor Melting point/range Boiling Point:	: Visco : BLA : Very : Not a : Not a : Immi	d Evap ous, Liquid Spec CK Bulk faint Vapo pplicable Vapo pplicable pH	ooration rate: Notific Gravity: Notdensity: Notor pressure: Notor density: Not: Not	determined applicable. determined determined
Appearance Color Odor Melting point/range Boiling Point:	: Visco : BLA : Very : Not a : Not a : Immi 10. S	d Evap ous, Liquid Spec CK Bulk faint Vapo pplicable Vapo pplicable pH scible	ooration rate: Notific Gravity: Notdensity: Notor pressure: Notor density: Not: Not	determined applicable. determined determined
Appearance Color Odor Melting point/range Boiling Point: Water solubility	: Visco : BLA : Very : Not a : Not a : Immi 10. S : St	d Evap ous, Liquid Spec CK Bulk faint Vapo pplicable Vapo pplicable pH scible TABILITY AND REACT	ooration rate: Notific Gravity: Notdensity: Notor pressure: Notor density: Not: Not	determined applicable. determined determined

3/7



MATERIAL SAFETY DATA SHEET

SX400BK BLACK REFLECTIVE

Version Number 1.0 Revision Date 03/04/2003		Page 4 of 7 Print Date 11/10/2011
		decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1333-86-4	Carbon black	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:



MATERIAL SAFETY DATA SHEET

SX400BK BLACK REFLECTIVE

Version Number 1.0 Revision Date 03/04/2003 Page 5 of 7 Print Date 11/10/2011

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: No data available.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA	: Refer to specific regulation.
IMO / IMDG	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
	: Classified as hazardous based on components.
OSHA Status	. Classified as hazardous based on components.

5/7



MATERIAL SAFETY DATA SHEET

SX400BK BLACK REFLECTIVE

Version Number 1.0 Revision Date 03/04/2003 Page 6 of 7 Print Date 11/10/2011

		Inventory.			
US. EPA CERCLA Hazardous Substances (40 CFR 302)					
Not applicable					
California Proposition 65	:	WARNING! This product contains a chemical known to the State of California to cause cancer.			
SARA Title III Section 302 Extr	em	ely Hazardous Substance			
Not applicable					
		N 1 - 1			
SARA Title III Section 313 Tox	10 C	Inemicals:			
Canadian Regulations:					
-					
WHMIS Classification					
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.			
National Inventories:					
Australia AICS	:	Listed.			
China IECS	:	Listed.			
Europe EINECS	:	Not determined.			
Japan ENCS	:	Not determined.			
Korea KECI	:	Not determined.			
Philippines PICCS	:	Listed.			

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.



MATERIAL SAFETY DATA SHEET

SX400BK BLACK REFLECTIVE

Version Number 1.0 Revision Date 03/04/2003 Page 7 of 7 Print Date 11/10/2011