

POLYONE CORPORATION**MATERIAL SAFETY DATA SHEET****P1128 WHITE**Version Number 1.2
Revision Date 03/12/2014Page 1 of 11
Print Date 3/17/2014**1. PRODUCT AND COMPANY IDENTIFICATION****POLYONE CORPORATION**
8155 Cobb Center Drive, Kennesaw, GA 30152Telephone : 1 (440) 930-1000 or 1 (866) POLYONE
Emergency telephone : **CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure**
number : **or accident).**Product name : P1128 WHITE
Product code : FO00012856
Chemical Name : Mixture
CAS-No. : Mixture
Product Use : Industrial Applications**2. COMPOSITION/INFORMATION ON INGREDIENTS**

Components	CAS-No.	Weight percent
Acetone	67-64-1	1 - 5
Ethyl acetate	141-78-6	1 - 5
Toluene	108-88-3	10 - 30
Ethyl alcohol	64-17-5	10 - 30
Methyl isobutyl ketone	108-10-1	10 - 30
Cyclohexanone	108-94-1	10 - 30
Methyl ethyl ketone	78-93-3	10 - 30

3. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW**

Flammable. May be harmful if inhaled. Harmful if swallowed. May cause skin irritation.
Flammable liquid and vapor. Vapors may be irritating to eyes and respiratory tract. This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. In addition, heating or processing this material may result in product degradation or byproduct formation creating additional hazards. See Sections 8 and 11 for additional details.

POTENTIAL HEALTH EFFECTS**Routes of Exposure:** : Inhalation, Skin contact, Ingestion**Acute exposure**

Inhalation : Excessive inhalation of product vapors may cause respiratory irritation, headaches, dizziness, and/or nausea.

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

P1128 WHITE

Version Number 1.2
Revision Date 03/12/2014

Page 2 of 11
Print Date 3/17/2014

- Ingestion : May be harmful if swallowed. May cause nausea, abdominal spasms and irritation of the mucous membranes.
- Eyes : Liquid, aerosol, or vapors of this product are irritating and may cause tearing, reddening, and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.
- Skin : Prolonged or repeated skin contact can cause de-fatting and drying of the skin which may result in skin irritation and dermatitis (rash).

Chronic exposure : Refer to Section 11 for Toxicological Information.

Medical Conditions Aggravated by Exposure: : Individuals with chronic respiratory disorders (i.e. asthma, chronic bronchitis, etc.) may be adversely affected by any airborne contaminant.

4. FIRST AID MEASURES

- Inhalation : Move to fresh air in case of accidental inhalation of vapours or decomposition products. Seek medical attention after significant exposure.
- Ingestion : Do not induce vomiting without medical advice. If conscious, drink plenty of water. Seek medical attention if necessary.
- Eyes : Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
- Skin : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

5. FIREFIGHTING MEASURES

- Flash point : Less than 75 °F (24 °C)
- Flammable Limits
 - Upper explosion limit : no data available
 - Lower explosion limit : no data available
- Auto-ignition temperature : no data available
- Suitable extinguishing media : Carbon dioxide blanket, Water, Foam, Dry chemical.
- Special Fire Fighting Procedures : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
- Unusual Fire/Explosion Hazards : Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), other hazardous materials, and smoke are all possible.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

P1128 WHITE

Version Number 1.2
Revision Date 03/12/2014

Page 3 of 11
Print Date 3/17/2014

- Environmental precautions : The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

7. HANDLING AND STORAGE

- Handling : Flammable liquid. Keep away from flames, hot surfaces, and sources of ignition. Use of non-sparking or explosion-proof equipment may be necessary. Never use compressed air for transferring product. Ensure all equipment is electrically grounded before beginning transfer operations. Take measures to prevent the build up of static electricity. Use only in area provided with appropriate exhaust ventilation.
- Storage : Store below 120 °F (49 °C) Keep containers tightly closed in a cool, well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Flammable Liquid. Check local fire regulations for sprinkler or explosion proof storage location requirements.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- Respiratory protection : Airborne contaminant levels should be maintained below the occupational exposure guidelines. When respiratory protection is required, use an approved air-purifying or positive pressure supplied-air respirator, depending upon potential airborne contaminant concentrations. Employees using respirators must be properly trained.
- Eye/Face Protection : Wear goggles or face shield during operations that present a splash potential.
- Hand protection : Protective gloves. Refer to equipment supplier to ensure protection.
- Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Additional Protective Measures : Safety shoes
- General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Ensure adequate ventilation, especially in confined areas.
- Engineering measures : Provide general and/or local exhaust ventilation to control airborne



POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

P1128 WHITE

Version Number 1.2
Revision Date 03/12/2014

Page 4 of 11
Print Date 3/17/2014

contaminant levels below the exposure guidelines.

Exposure limit(s)

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

P1128 WHITE

Version Number 1.2
Revision Date 03/12/2014

Page 5 of 11
Print Date 3/17/2014

Components	Value	Exposure time	Exposure type	List:	
Acetone	500 ppm	Time Weighted Average (TWA):		ACGIH	
	750 ppm	Short Term Exposure Limit (STEL):		ACGIH	
	1,000 ppm 2,400 mg/m3	PEL:		OSHA Z1	
	1,000 ppm 2,400 mg/m3	Time Weighted Average (TWA):		MX OEL	
	1,260 ppm 3,000 mg/m3	Short Term Exposure Limit (STEL):		MX OEL	
	200 ppm	Time Weighted Average (TWA):		ACGIH NIC	
Toluene	500 ppm	Short Term Exposure Limit (STEL):		ACGIH NIC	
	20 ppm	Time Weighted Average (TWA):		ACGIH	
	100 ppm 375 mg/m3	Recommended exposure limit (REL):		NIOSH	
	150 ppm 560 mg/m3	Short Term Exposure Limit (STEL):		NIOSH	
	200 ppm	Time Weighted Average (TWA):		OSHA Z2	
	300 ppm	Ceiling Limit Value:		OSHA Z2	
	500 ppm	Maximum concentration:		OSHA Z2	
	100 ppm 375 mg/m3	Time Weighted Average (TWA):		OSHA Z1A	
	150 ppm 560 mg/m3	Short Term Exposure Limit (STEL):		OSHA Z1A	
	50 ppm 188 mg/m3	Time Weighted Average (TWA):		MX OEL	
	Ethyl alcohol	1,000 ppm 1,900 mg/m3	PEL:		OSHA Z1
		1,000 ppm 1,900 mg/m3	Time Weighted Average (TWA):		MX OEL
		1,000 ppm	Short Term Exposure Limit (STEL):		ACGIH
Methyl isobutyl ketone	20 ppm	Time Weighted Average (TWA):		ACGIH	
	75 ppm	Short Term Exposure Limit (STEL):		ACGIH	
	50 ppm 205 mg/m3	Recommended exposure limit (REL):		NIOSH	

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

P1128 WHITE

Version Number 1.2
Revision Date 03/12/2014

Page 6 of 11
Print Date 3/17/2014

	75 ppm 300 mg/m3	Short Term Exposure Limit (STEL):		NIOSH
	100 ppm 410 mg/m3	PEL:		OSHA Z1
	50 ppm 205 mg/m3	Time Weighted Average (TWA):		OSHA Z1A
	75 ppm 300 mg/m3	Short Term Exposure Limit (STEL):		OSHA Z1A
	50 ppm 205 mg/m3	Time Weighted Average (TWA):		MX OEL
	75 ppm 307 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Cyclohexanone	20 ppm	Time Weighted Average (TWA):		ACGIH
	50 ppm 200 mg/m3	PEL:	Vapor and aerosol.	OSHA Z1
	50 ppm	Short Term Exposure Limit (STEL):		ACGIH
Ethyl acetate	400 ppm	Time Weighted Average (TWA):		ACGIH
	400 ppm 1,400 mg/m3	Recommended exposure limit (REL):		NIOSH
	400 ppm 1,400 mg/m3	PEL:		OSHA Z1
	400 ppm 1,400 mg/m3	Time Weighted Average (TWA):		OSHA Z1A
	400 ppm 1,400 mg/m3	Time Weighted Average (TWA):		MX OEL
Methyl ethyl ketone	200 ppm	Time Weighted Average (TWA):		ACGIH
	300 ppm	Short Term Exposure Limit (STEL):		ACGIH
	200 ppm 590 mg/m3	Recommended exposure limit (REL):		NIOSH
	300 ppm 885 mg/m3	Short Term Exposure Limit (STEL):		NIOSH
	200 ppm 590 mg/m3	PEL:		OSHA Z1
	200 ppm 590 mg/m3	Time Weighted Average (TWA):		OSHA Z1A
	300 ppm 885 mg/m3	Short Term Exposure Limit (STEL):		OSHA Z1A
	200 ppm 590 mg/m3	Time Weighted Average (TWA):		MX OEL

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

P1128 WHITE

Version Number 1.2
Revision Date 03/12/2014

Page 7 of 11
Print Date 3/17/2014

	300 ppm 885 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
--	----------------------	--------------------------------------	--	--------

9. PHYSICAL AND CHEMICAL PROPERTIES

Form	: liquid	Evaporation rate	: Faster than Butyl Acetate
Appearance	: liquid	Specific Gravity	: Not determined
Colour	: WHITE	Bulk density	: Not applicable
Odour	: solvent-like	Vapour pressure	: not determined
Melting point/range	: Not applicable	Vapour density	: Heavier than air.
Boiling Point:	: no data available	pH	: not determined
Water solubility	: negligible		

10. STABILITY AND REACTIVITY

Stability	: The product is stable if stored and handled as prescribed.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. Heat, flames and sparks.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	: Carbon dioxide (CO ₂), carbon monoxide (CO), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
67-64-1	Acetone	Irritant	Eyes, Skin, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system, central nervous system (CNS).
141-78-6	Ethyl acetate	Systemic effects	Eyes, Skin, Respiratory system.
108-88-3	Toluene	Systemic effects	central nervous system (CNS), Liver, Kidney, urinary system.
		Irritant	Skin, Eyes.
64-17-5	Ethyl alcohol	Systemic effects	Liver, heart or circulatory system, central nervous system (CNS), reproductive system.

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

P1128 WHITE

Version Number 1.2

Revision Date 03/12/2014

Page 8 of 11

Print Date 3/17/2014

108-10-1	Methyl isobutyl ketone	Systemic effects	central nervous system (CNS), reproductive system.
		Irritant	Eyes.
108-94-1	Cyclohexanone	Systemic effects	Eyes, Skin, Respiratory system, Liver, Kidney, central nervous system (CNS).
78-93-3	Methyl ethyl ketone	Irritant	Eyes, Skin, Respiratory system.
		Systemic effects	central nervous system (CNS).

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
67-64-1	Acetone	LC50	50100 mg/m ³	rat
		LC50		rat
		Oral	5,800	rat
		LD50Oral	mg/kg5,800	rabbit
		LD50	mg/kg	rabbit
141-78-6	Ethyl acetate	LC50	45 gm/m ³	mouse
		Oral LD50	5,620 mg/kg	rat
108-88-3	Toluene	LC50	49 gm/m ³	rat
		Oral LD50	636 mg/kg	rat
		Dermal LD50	14100 ul/kg	rabbit
64-17-5	Ethyl alcohol	LC50	20000 ppm	rat
		LC50		rat
		Oral	3,450	mouse
		LD50Oral	mg/kg3,450	mouse
108-10-1	Methyl isobutyl ketone	LC50	100 gm/m ³	rat
		LC50		rat
		Oral LD50	2,080 mg/kg	rat
		Dermal LD50	16,000 mg/kg	rabbit
108-94-1	Cyclohexanone	LC50	8000 ppm	rat
		Oral LD50	1620 ul/kg	rat
78-93-3	Methyl ethyl ketone	LC50	32 gm/m ³	mouse
		Oral LD50	4,050 mg/kg	mouse
		Dermal LD50	6,480 mg/kg	rabbit

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
108-10-1	Methyl isobutyl ketone	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

POLYONE CORPORATION**MATERIAL SAFETY DATA SHEET****P1128 WHITE**Version Number 1.2
Revision Date 03/12/2014Page 9 of 11
Print Date 3/17/2014

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

- 1 - The component is known to be a human carcinogen.
- 2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

Persistence and degradability : no data available

Environmental Toxicity : no data available

Bioaccumulation Potential : no data available

Additional advice : no data available

13. DISPOSAL CONSIDERATIONS

Product : Dispose of properly. Do not dump into sewers, on the ground, or into any body of water. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

14. TRANSPORT INFORMATION

U.S. DOT Classification
Proper Shipping Name: Flammable liquids, n.o.s.
Technical Name: Methyl ethyl ketone
Hazard Class / Division: 3
UN Number: UN1993
Packing Group: II
Label Required: 3

ICAO/IATA: Refer to specific regulation.

IMO/IMDG (maritime): Refer to specific regulation.

15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

P1128 WHITE

Version Number 1.2
Revision Date 03/12/2014

Page 10 of 11
Print Date 3/17/2014

TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

California Proposition 65 : WARNING! This product contains a chemical known to the State of California to cause cancer., WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	% in Product	RQ for component
Phenol	108-95-2	0.10 - 1.00	1,000 lbs

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	Weight percent
TOLUENE	108-88-3	10.00 - 30.00
METHYL ISOBUTYL KETONE	108-10-1	10.00 - 30.00

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight percent	NPRI ID#
Methyl alcohol	67-56-1	0.10 - 1.00	
2-Propenoic acid, 2-methyl-, methyl ester	80-62-6	0.10 - 1.00	
Toluene	108-88-3	10.00 - 30.00	
Phenol	108-95-2	0.10 - 1.00	
Methyl isobutyl ketone	108-10-1	10.00 - 30.00	
Methyl ethyl ketone	78-93-3	10.00 - 30.00	

WHMIS Classification : D1B, B2, D1B

WHMIS Ingredient Disclosure List

POLYONE CORPORATION**MATERIAL SAFETY DATA SHEET****P1128 WHITE**Version Number 1.2
Revision Date 03/12/2014Page 11 of 11
Print Date 3/17/2014

CAS-No.
67-64-1
108-88-3
64-17-5
108-10-1
108-94-1
141-78-6
78-93-3

DSL : All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS : Not determined
China IECS : Not determined
Europe EINECS : Listed
Japan ENCS : Not determined
Korea KECI : Not determined
Philippines PICCS : Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.