

P1241 ADHESIVE KIT

Version Number 1.0
Revision Date 07/17/2002

Page 1 of 7
Print Date 11/5/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION
2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE : Product Stewardship, (314) 771-1800
Emergency telephone number : **CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).**

Product name : P1241 ADHESIVE KIT
Product code : FO00012857
Chemical Name : Mixture
CAS-No. : Mixture
Product Use : Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Methyl ethyl ketone	78-93-3	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Flammable. May be harmful if inhaled. Harmful if swallowed. May cause skin irritation. Flammable liquid and vapor. Vapors may be irritating to eyes and respiratory tract. This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. In addition, heating or processing this material may result in product degradation or byproduct formation creating additional hazards. See Sections 8 and 11 for additional details.

POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Inhalation, Skin contact, Ingestion

Acute exposure

Inhalation : Excessive inhalation of product vapors may cause respiratory irritation, headaches, dizziness, and/or nausea.

Ingestion : May be harmful if swallowed. May cause nausea, abdominal spasms and irritation of the mucous membranes.

Eyes : Liquid, aerosol, or vapors of this product are irritating and may cause tearing, reddening, and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

Skin : Prolonged or repeated skin contact can cause de-fatting and drying of the skin which may result in skin irritation and dermatitis (rash).

MATERIAL SAFETY DATA SHEET

P1241 ADHESIVE KIT

Version Number 1.0

Page 2 of 7

Revision Date 07/17/2002

Print Date 11/5/2011

Chronic exposure : Refer to Section 11 for Toxicological Information.

Medical Conditions Aggravated by Exposure: : Individuals with chronic respiratory disorders (i.e. asthma, chronic bronchitis, etc.) may be adversely affected by any airborne contaminant.

4. FIRST AID MEASURES

- Inhalation** : Move to fresh air in case of accidental inhalation of vapours or decomposition products. Seek medical attention after significant exposure.
- Ingestion** : Do not induce vomiting without medical advice. If conscious, drink plenty of water. Seek medical attention if necessary.
- Eyes** : Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
- Skin** : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

5. FIRE-FIGHTING MEASURES

- Flash point** : Less than 75 °F (24 °C)
- Flammable Limits**
- Upper explosion limit : No data available.
 - Lower explosion limit : No data available.
- Autoignition temperature** : No data available.
- Suitable extinguishing media** : foam, dry chemical, carbon dioxide (CO₂), Water spray.
- Special Fire Fighting Procedures** : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
- Unusual Fire/Explosion Hazards** : None

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions** : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
- Environmental precautions** : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
- Methods for cleaning up** : Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

P1241 ADHESIVE KIT

Version Number 1.0
Revision Date 07/17/2002

Page 3 of 7
Print Date 11/5/2011

7. HANDLING AND STORAGE

- Handling : Flammable liquid. Keep away from flames, hot surfaces, and sources of ignition. Use of non-sparking or explosion-proof equipment may be necessary. Never use compressed air for transferring product. Ensure all equipment is electrically grounded before beginning transfer operations. Take measures to prevent the build up of static electricity. Use only in area provided with appropriate exhaust ventilation.
- Storage : Store below 120 °F (49 °C) Keep containers tightly closed in a cool, well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Flammable Liquid. Check local fire regulations for sprinkler or explosion proof storage location requirements.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- Respiratory protection : Airborne contaminant levels should be maintained below the occupational exposure guidelines. When respiratory protection is required, use an approved air-purifying or positive pressure supplied-air respirator, depending upon potential airborne contaminant concentrations. Employees using respirators must be properly trained. Employers must follow applicable regulations such as OSHA 29 CFR 1910.134.
- Eye/Face Protection : Wear goggles or face shield during operations that present a splash potential.
- Hand protection : Protective gloves.
- Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Additional Protective Measures : Safety shoes.
- General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Ensure adequate ventilation, especially in confined areas.
- Engineering measures : Provide general and/or local exhaust ventilation to control airborne contaminant levels below the exposure guidelines.

Exposure limit(s)

MATERIAL SAFETY DATA SHEET

P1241 ADHESIVE KIT

Version Number 1.0

Page 4 of 7

Revision Date 07/17/2002

Print Date 11/5/2011

Components	Value	Exposure time	Exposure type	List:
Methyl ethyl ketone	200 ppm	Time Weighted Average (TWA):	Vapor.	ACGIH
	300 ppm	Short Term Exposure Limit (STEL):	Vapor.	ACGIH

9. PHYSICAL AND CHEMICAL PROPERTIES

Form	: Liquid	Evaporation rate	: Faster than Butyl Acetate
Appearance	: Liquid	Specific Gravity	: Not determined
Color	: NOT APPLICABLE	Bulk density	: Not applicable.
Odor	: Solvent	Vapor pressure	: Not determined
Melting point/range	: Not applicable.	Vapor density	: Heavier than air.
Boiling Point:	: No data available.	pH	: Not determined
Water solubility	: Negligible		

10. STABILITY AND REACTIVITY

Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. Heat, flames and sparks.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	: Carbon dioxide (CO ₂), carbon monoxide (CO), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
78-93-3	Methyl ethyl ketone	Irritant	Eyes, Skin, Respiratory system.
		Systemic effects	central nervous system.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
78-93-3	Methyl ethyl ketone	LC50	32 gm/m ³	mouse
		Oral LD50	4,050 mg/kg	mouse
		Dermal LD50	6,480 mg/kg	rabbit

MATERIAL SAFETY DATA SHEET

P1241 ADHESIVE KIT

Version Number 1.0
Revision Date 07/17/2002

Page 5 of 7
Print Date 11/5/2011

12. ECOLOGICAL INFORMATION

Persistence and degradability : No data available.

Environmental Toxicity : Adverse ecological impact is not known or expected under normal use.

Bioaccumulation Potential : No data available.

Additional advice : No data available.

13. DISPOSAL CONSIDERATIONS

Product : Dispose of properly. Do not dump into sewers, on the ground, or into any body of water. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

14. TRANSPORT INFORMATION

U.S. DOT Classification
Proper Shipping Name: Methyl ethyl ketone, mixture
Technical Name:
Hazard Class / Division 3
UN Number UN1193
Packing Group II
Label Required 3
Hazardous Substance Methyl ethyl ketone
Reportable quantity: 12,653 LB

ICAO/IATA Refer to specific regulation.

IMO / IMDG Refer to specific regulation.

15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on the TSCA inventory or are exempt.

MATERIAL SAFETY DATA SHEET

P1241 ADHESIVE KIT

Version Number 1.0

Page 6 of 7

Revision Date 07/17/2002

Print Date 11/5/2011

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	% in Product	RQ for component	RQ for Mixture/Product
Methyl ethyl ketone	78-93-3	39.51	5,000 lbs	12,653 LB

California Proposition : This product does not contain a substance listed by California Prop 65.
65

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
METHYL ETHYL KETONE	78-93-3	39.51

Canadian Regulations:

WHMIS Classification : D2A, B2

WHMIS Ingredient Disclosure List

CAS-No.
78-93-3

DSL : Listed.

National Inventories:

Australia AICS : Listed.

China IECS : Listed.

Europe EINECS : Not determined.

Japan ENCS : Not determined.

Korea KECI : Not determined.

Philippines PICCS : Listed.

16. OTHER INFORMATION

POLYONE CORPORATION



MATERIAL SAFETY DATA SHEET

P1241 ADHESIVE KIT

Version Number 1.0

Revision Date 07/17/2002

Page 7 of 7

Print Date 11/5/2011

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.