## PD4001 YELLOW DIP COATING

Version Number 1.1 Revision Date 05/22/2024



Page 1 of 17 Print Date 05/23/2024

# SAFETY DATA SHEET

#### PD4001 YELLOW DIP COATING

Section 1. Identification		
GHS product identifier	:	PD4001 YELLOW DIP COATING
Chemical name	:	Mixture
CAS number	:	Mixture
Other means of identification	:	FO00016297
Product type	:	liquid
		•
Relevant identified uses of the subs	tance	e or mixture and uses advised against
Product use	:	Industrial applications. Plastics.
Supplier's details	:	AVIENT CORPORATION
••		33587 Walker Road, Avon Lake, OH 44012
		1 (440) 930-1000 or 1 (844) 4AVIENT
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or
(with hours of operation)		accident).


# Section 2. Hazards identification

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

OSHA/HCS status	:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	:	EYE IRRITATION - Category 2B CARCINOGENICITY - Category 1A

#### **GHS label elements**

## PD4001 YELLOW DIP COATING



# **ÀVIENT**

Page 2 of 17 Print Date 05/23/2024

Hazard pictograms	:	
Signal word Hazard statements	:	Danger Causes eye irritation.
		May cause cancer.
Precautionary statements		
Prevention	:	Not applicable. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Wash thoroughly after handling.
Response	:	IF exposed or concerned: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Storage	:	Store locked up.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	:	None known.
Hazards not otherwise classified	:	None known. Not available.

# Section 3. Composition/information on ingredients

Substance/mixture	: Mixture	
Chemical name	: Mixture	
Other means of identification	: FO0001	6297

#### CAS number/other identifiers

Ingredient name	%	CAS number
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters,	>= 25 - <= 50	68515-48-0
C9-rich		
Distillates (petroleum), hydrotreated light	>= 1 - <= 3	64742-47-8
Titanium dioxide	>= 0.3 - <= 1	13463-67-7
Quartz	> 0 - <= 0.3	14808-60-7

## PD4001 YELLOW DIP COATING

**ÀVIENT** 

Version Number 1.1 Revision Date 05/22/2024

Page 3 of 17 Print Date 05/23/2024

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

Description of necessary first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	:	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

Potential acute health effects		
Eye contact	:	Causes eye irritation.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	No known significant effects or critical hazards.

Revision Date 05/22/2024

## PD4001 YELLOW DIP COATING





Page 4 of 17 Print Date 05/23/2024

Ingestion	:	No known significant effects or critical hazards.
Over-exposure signs/symptoms		
Eye contact	:	Adverse symptoms may include the following: irritation watering redness
Inhalation	:	No specific data.
Skin contact	:	No specific data.
Ingestion	:	No specific data.
<u>Indication of immediate medical</u> Notes to physician Specific treatments	<u>attentio</u> : :	n and special treatment needed, if necessary Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. No specific treatment.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
See toxicological information (Se	ection 11	)

# Section 5. Fire-fighting measures

#### **Extinguishing media**

Suitable extinguishing media Unsuitable extinguishing media	:	In case of fire, use water spray (fog), foam, dry chemical or CO <sub>2</sub> . None known.
Specific hazards arising from the chemical Hazardous thermal decomposition products	:	In a fire or if heated, a pressure increase will occur and the container may burst. May emit Hydrogen Chloride (HCl). Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds metal oxide/oxides
Special protective actions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. 4/17

## PD4001 YELLOW DIP COATING



Version Number 1.1 Revision Date 05/22/2024 Page 5 of 17 Print Date 05/23/2024

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures


#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel For emergency responders	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for containment	nt ar	nd cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non- combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

#### Precautions for safe handling

## PD4001 YELLOW DIP COATING



# **ÀVIENT**

Page 6 of 17 Print Date 05/23/2024

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

#### **Occupational exposure limits**

Ingredient name	Exposure limits	
1,2-Benzenedicarboxylic acid, di-C8-10- branched alkyl esters, C9-rich	None.	
Distillates (petroleum), hydrotreated light	ACGIH TLV (2003-01-01) Absorbed through skin. TWA 200 mg/m3 (Calculated as total hydrocarbon vapor)	
Titanium dioxide	OSHA PEL 1989 (1989-03-01) TWA 10 mg/m3 Form: Total dust OSHA PEL (1993-06-30) TWA 15 mg/m3 Form: Total dust ACGIH TLV (2022-01-06) TWA 0.2 mg/m3 Form: respirable fraction, nanoscale particles TWA 2.5 mg/m3 Form: respirable fraction, finescale particles	
6/17		

## PD4001 YELLOW DIP COATING

Version Number 1.1 Revision Date 05/22/2024

# **ÀVIENT**

Page 7 of 17 Print Date 05/23/2024

Quartz		OSHA PEL 1989 (1989-03-01) TWA 0.1 mg/m3 (Calculated as Quartz) Form: Respirable dust OSHA PEL Z3 (1997-09-03) TWA 250 MPPCF / (%SiO2+5) Form: Respirable TWA 10 MG /M3 / (%SiO2+2) Form: Respirable OSHA PEL Z3 (1997-09-03) TWA 30 MG /M3 / (%SiO2+2) Form: Total dust NIOSH REL (1994-06-01) TWA 0.05 mg/m3 Form: Respirable dust ACGIH TLV (2005-12-09) TWA 0.025 mg/m3 Form: Respirable fraction OSHA PEL (2016-06-23) TWA 0.05 mg/m3 Form: Respirable dust
Appropriate engineering controls Environmental exposure controls	   1	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Emissions from ventilation or work process equipment should be
		checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
ndividual protection measures		
Hygiene measures	]	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	]	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the



## PD4001 YELLOW DIP COATING

Version Number 1.1					
Revision Date	05/22/2024				

Page 8 of 17
Print Date 05/23/2024

	parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

# Section 9. Physical and chemical properties

#### Appearance

		1
Physical state	:	liquid [Paste.]
Color	:	YELLOW
Odor	:	Not available.
Odor threshold	:	Not available.
рН	:	Not available.
Melting point	:	Not available.
Boiling point	:	Not available.
Flash point	:	Not available.
Burning time	:	Not available.
Burning rate	:	Not available.
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive	:	Lower: Not available.
Lower and upper explosive (flammable) limits	:	<b>Lower:</b> Not available. <b>Upper:</b> Not available.
	:	
(flammable) limits Vapor pressure	:	<b>Upper:</b> Not available.
(flammable) limits	:	<b>Upper:</b> Not available. Not available.
(flammable) limits Vapor pressure Vapor density	:	<b>Upper:</b> Not available. Not available. Not available.
(flammable) limits Vapor pressure Vapor density Relative density	:	<b>Upper:</b> Not available. Not available. Not available. Not available.
(flammable) limits Vapor pressure Vapor density Relative density Solubility	:	Upper: Not available. Not available. Not available. Not available. Not available. Not available.
(flammable) limits Vapor pressure Vapor density Relative density Solubility Solubility in water		Upper: Not available. Not available. Not available. Not available. Not available. Not available. Not available.
(flammable) limits Vapor pressure Vapor density Relative density Solubility Solubility in water Partition coefficient: n-		Upper: Not available. Not available. Not available. Not available. Not available. Not available. Not available.
(flammable) limits Vapor pressure Vapor density Relative density Solubility Solubility in water Partition coefficient: n- octanol/water	:	Upper: Not available. Not available. Not available. Not available. Not available. Not available. Not available. Not applicable.
(flammable) limits Vapor pressure Vapor density Relative density Solubility Solubility in water Partition coefficient: n- octanol/water Auto-ignition temperature	:	Upper: Not available. Not available. Not available. Not available. Not available. Not available. Not available. Not available.

## PD4001 YELLOW DIP COATING



Version Number 1.1 Revision Date 05/22/2024 Page 9 of 17 Print Date 05/23/2024

Viscosity	:	<b>Dynamic:</b> Not available. <b>Kinematic:</b> Not available.
<u>Aerosol product</u>		
Heat of combustion	:	Not available.
Ignition distance	:	Not available.
Enclosed space ignition - Time equivalent	:	Not available.
Enclosed space ignition -	:	Not available.
Deflagration density		
Flame height	:	Not available.
Flame duration	:	Not available.

# Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	Keep away from extreme heat and oxidizing agents.
Incompatible materials	:	Avoid contact with acetal homopolymers and acetyl homopolymers during processing.
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Section 11. Toxicological information

#### Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure			
1,2-Benzenedicarboxylic acid, o	1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich						
	LD50 Oral	Rat	10,000 mg/kg	-			
Titanium oxide (TiO2)							
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h			
	Dusts and mists						
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-			

**Conclusion/Summary** 

: Mixture.Not fully tested.

#### **Irritation/Corrosion**

## PD4001 YELLOW DIP COATING



Version Number 1.1 Revision Date 05/22/2024 Page 10 of 17 Print Date 05/23/2024

Product/ingredient name	Result	Species	Score	Exposure	Observation
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	Eyes - Mild irritant	Rabbit	-		-
Conclusion/Summary					
Skin		ot fully tested.			
Eyes		ot fully tested.			
Respiratory	: Mixture.N	ot fully tested.			
Sensitization					
<b>Conclusion/Summary</b>					
Skin		ot fully tested.			
Respiratory	: Mixture.N	ot fully tested.			
Mutagenicity					
Conclusion/Summary	: Mixture.N	ot fully tested.			
<b>Carcinogenicity</b>					
Conclusion/Summary	: Mixture.N	ot fully tested.			

#### **Classification**

Product/ingredient name	OSHA	IARC	NTP
Titanium oxide (TiO2)	-	2B	-
Quartz (SiO2)	-	1	Known to be a human carcinogen.

#### **Reproductive toxicity**

Conclusion/Summary :		Mixture.Not fully tested.
----------------------	--	---------------------------

#### **Teratogenicity**

Conclusion/Summary

: Mixture.Not fully tested.

#### Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs	
Quartz (SiO2)	Category 1	-	-	

## PD4001 YELLOW DIP COATING



Version Number 1.1 Revision Date 05/22/2024 Page 11 of 17 Print Date 05/23/2024

#### **Aspiration hazard**

Name		Result
Distillates (petroleum), hydrotreated li	ight	ASPIRATION HAZARD - Category 1
Information on the likely routes of exposure	:	Not available.
Potential acute health effects		
Eye contact	:	Causes eye irritation.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	No known significant effects or critical hazards.
Ingestion	:	No known significant effects or critical hazards.
Symptoms related to the physical, cl	hemi	cal and toxicological characteristics
Eye contact	:	Adverse symptoms may include the following: irritation, watering, redness
Inhalation	:	No specific data.
Skin contact	-	No specific data.
Ingestion	:	No specific data.
Delayed and immediate effects and a	also (	chronic effects from short and long term exposure
<u>Short term exposure</u>		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Long term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Potential chronic health effects		
Conclusion/Summary	:	Mixture.Not fully tested.
General	:	No known significant effects or critical hazards.
Carcinogenicity	:	May cause cancer. Risk of cancer depends on duration and level of
Mutagenicity	:	exposure. No known significant effects or critical hazards.
Teratogenicity	:	No known significant effects or critical hazards.
Developmental effects	:	No known significant effects or critical hazards.
Fertility effects	:	No known significant effects or critical hazards. No known significant
•		11/17

## PD4001 YELLOW DIP COATING





Version Number 1.1 Revision Date 05/22/2024

Page 12 of 17 Print Date 05/23/2024

effects or critical hazards.

#### Numerical measures of toxicity

#### Acute toxicity estimates

Product/ingredient name	Oral	Dermal	Inhalation (gases)	Inhalation (vapors)	Inhalation (dusts and mists)
PD4001 YELLOW DIP COATING	N/A	N/A	N/A	728.4 Mg/l	N/A
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	10000 mg/kg	N/A	N/A	N/A	N/A
Distillates (petroleum), hydrotreated light	N/A	N/A	N/A	11 Mg/l	N/A
Titanium oxide (TiO2)	N/A	N/A	N/A	N/A	6.82 Mg/l

#### **Other information**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

# Section 12. Ecological information

:

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Distillates (petroleum), hydrotr	eated light		
	Acute LC50 2.2 Mg/l Fresh	Fish - Lepomis macrochirus	96 h
	water		
Titanium oxide (TiO2)			
	Acute LC50 > 1,000 Mg/l	Fish - Fundulus heteroclitus	96 h
	Marine water		
	Acute LC50 3 Mg/l Fresh water	Crustaceans - Ceriodaphnia	48 h
		dubia	
	Acute LC50 6.5 Mg/l Fresh	Daphnia - Daphnia pulex	48 h
	water		

**Conclusion/Summary** 

Not available.

:

## PD4001 YELLOW DIP COATING

Version Number 1.1 Revision Date 05/22/2024 **AVIENT** 

Page 13 of 17

Print Date 05/23/2024

#### Persistence and degradability

**Conclusion/Summary** : Not available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
1,2-Benzenedicarboxylic acid, di-C8-	8.8	3.00	low
10-branched alkyl esters, C9-rich			

#### Mobility in soil

Soil/water partition coefficient (KOC)		Not available.	
Other adverse effects	:	No known significant effects or critical hazards.	

:

## Section 13. Disposal considerations

**Disposal methods** 

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

## **Section 14. Transport information**

U.S.DOT 49CFR Ground/Air/Water : Not regulated for transportation.

13/17

## PD4001 YELLOW DIP COATING

Version Number 1.1 Revision Date 05/22/2024



Page 14 of 17 Print Date 05/23/2024

International Air : Consult mode specific transport rules ICAO/IATA

International Water IMO/IMDG : Consult mode specific transport rules

# Section 15. Regulatory information

U.S. Federal regulations	:	<b>United States - TSCA 12(b) - Chemical export notification:</b> None of the components are listed.
		United States - TSCA 4(a) - Final Test Rules: Listed 1,2-
		Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich
		Denzeneureur boxyne uelu, ur eo 10 bruneneu urkyresters, e> rien
		United States - TSCA 4(a) - ITC Priority list: Not listed
		United States - TSCA 4(a) - Proposed test rules: Not listed
		United States - TSCA 4(f) - Priority risk review: Not listed
		United States - TSCA 5(a)2 - Final significant new use rules: Not
		listed
		United States - TSCA 5(a)2 - Proposed significant new use rules:
		Not listed
		United States - TSCA 5(e) - Substances consent order: Not listed
		United States - TSCA 6 - Final risk management: Not listed
		United States - TSCA 6 - Proposed risk management: Not listed
		United States - TSCA 8(a) - Chemical risk rules: Not listed
		United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed
		United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not
		determined
		United States - TSCA 8(a) - Preliminary assessment report
		(PAIR): Listed Acetaldehyde
		(1111)/ 210000 1200000000000000000000000000000
		United States - TSCA 8(c) - Significant adverse reaction (SAR):
		Not listed
		United States - TSCA 8(d) - Health and safety studies: Not listed
		United States - EPA Clean water act (CWA) section 307 - Priority
		pollutants: Listed Vinyl chloride monomer
		United States - EPA Clean water act (CWA) section 311 -
		Hazardous substances: Listed
		United States - EPA Clean air act (CAA) section 112 - Accidental
		release prevention - Flammable substances: Not listed
		United States - EPA Clean air act (CAA) section 112 - Accidental
		release prevention - Toxic substances: Not listed
		United States - Department of commerce - Precursor chemical:
		- ····································

## PD4001 YELLOW DIP COATING

Version Number 1.1 Revision Date 05/22/2024



Page 15 of 17 Print Date 05/23/2024

#### Not listed

Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)	:	Listed
Clean Air Act Section 602 Class I	:	Not listed
Substances		Not listed
Clean Air Act Section 602 Class II Substances	:	Not fisted
DEA List I Chemicals (Precursor	:	Not listed
Chemicals)		Not listed
DEA List II Chemicals (Essential Chemicals)	:	Not listed
Chemicals)		

#### US. EPA CERCLA Hazardous Substances (40 CFR 302)

:

:

not applicable

#### SARA 311/312

Classification

EYE IRRITATION - Category 2B CARCINOGENICITY - Category 1A

#### **Composition/information on ingredients**

Name	%	Classification
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	>= 25 - <= 50	EYE IRRITATION - Category 2B
Distillates (petroleum), hydrotreated light	>= 1 - <= 3	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY - inhalation - Category 4 SKIN IRRITATION - Category 2 ASPIRATION HAZARD - Category 1
Titanium oxide (TiO2)	>= 0.3 - <= 1	CARCINOGENICITY - Category 2
Quartz (SiO2)	> 0 - <= 0.3	CARCINOGENICITY - inhalation - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

Not applicable.

<u>State regulations</u> Massachusetts

The following components are listed: Calcium carbonate

15/17

## PD4001 YELLOW DIP COATING



Version Number 1.1 Revision Date 05/22/2024 Page 16 of 17 Print Date 05/23/2024

New York	:	None of the components are listed.
New Jersey	:	The following components are listed:
		Ethene, chloro-, homopolymer
		Calcium carbonate
		Quartz
Pennsylvania	:	The following components are listed: Calcium carbonate

#### California Prop. 65

**WARNING:** This product can expose you to chemicals including 1,2-Benzenedicarboxylic acid, di-C8-10branched alkyl esters, C9-rich, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
1,2-Benzenedicarboxylic acid, di-C8-10- branched alkyl esters, C9-rich	Yes.	-
Titanium dioxide	-	-
Quartz	-	-

United States inventory (TSCA 8b)	:	All components are active or exempted.
Canada inventory	:	At least one component is not listed in DSL but all such components are listed in NDSL.
<u>International regulations</u> <u>Inventory list</u>		
Australia	:	Not determined.
Canada	:	At least one component is not listed in DSL but all such components are listed in NDSL.
China	:	All components are listed or exempted.
Eurasian Economic Union	:	Russian Federation inventory: Not determined.
Japan	:	Japan inventory (CSCL): Not determined.
		Japan inventory (ISHL): Not determined.
New Zealand	:	Not determined.
Philippines	:	Not determined.
Republic of Korea	:	All components are listed or exempted.
Taiwan	:	All components are listed or exempted.
Thailand	:	Not determined.
Turkey	:	Not determined.
United States	:	All components are active or exempted.
Viet Nam	:	Not determined.

# Section 16. Other information

## PD4001 YELLOW DIP COATING



Version Number 1.1 Revision Date 05/22/2024 Page 17 of 17 Print Date 05/23/2024

Hazardous Material Information System (U.S.A.)

Health	*	1
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual. History

<u>HISTOLA</u>		
Date of printing	:	05/23/2024
Date of issue/Date of revision	:	05/22/2024
Date of previous issue	:	05/17/2024
Version	:	1.1
Key to abbreviations	:	ATE = Acute Toxicity Estimate
		BCF = Bioconcentration Factor
		GHS = Globally Harmonized System of Classification and Labelling of
		Chemicals
		IATA = International Air Transport Association
		IBC = Intermediate Bulk Container
		IMDG = International Maritime Dangerous Goods
		LogPow = logarithm of the octanol/water partition coefficient
		MARPOL = International Convention for the Prevention of Pollution From
		Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine
		pollution)
		UN = United Nations
References	:	Not available.

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.