

## WS7568 WB-S BARK RFU

Version Number 1.0 Page 1 of 22 Revision Date 06/10/2020 Print Date 06/11/2020

# SAFETY DATA SHEET

### WS7568 WB-S BARK RFU

# **Section 1. Identification**

**GHS product identifier** : WS7568 WB-S BARK RFU

Chemical name: MixtureCAS number: MixtureOther means of identification: FO00016940Product type: liquid

Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Industrial applications. Plastics.

Supplier's details : POLYONE CORPORATION

33587 Walker Road, Avon Lake, OH 44012

1 (440) 930-1000 or 1 (866) POLYONE

Emergency telephone number

(with hours of operation)

CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or

accident).

# Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200).

Classification of the substance or

mixture

SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A

TOXIC TO REPRODUCTION (Fertility) - Category 2

#### **GHS** label elements



### WS7568 WB-S BARK RFU

 Version Number 1.0
 Page 2 of 22

 Revision Date 06/10/2020
 Print Date 06/11/2020

Hazard pictograms

 $\bigcirc$ 

Signal word : Warning

**Hazard statements** : Causes serious eye irritation.

Causes skin irritation.

Suspected of damaging fertility.

**Precautionary statements** 

General : Not applicable.

**Prevention**: Obtain special instructions before use. Do not handle until all safety

precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Wash hands

thoroughly after handling.

**Response** : IF exposed or concerned: Get medical attention. IF ON SKIN: Wash

with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye

irritation persists: Get medical attention.

**Storage** : Store locked up.

**Disposal** : Dispose of contents and container in accordance with all local,

regional, national and international regulations.

Supplemental label elements

**Hazards not otherwise classified** : None known.

Not available.

None known.

# Section 3. Composition/information on ingredients

Substance/mixture: MixtureChemical name: MixtureOther means of identification: FO00016940

**CAS** number/other identifiers

Ingredient name	<b>%</b>	CAS number
Titanium dioxide	5 - 10	13463-67-7



# WS7568 WB-S BARK RFU

Version Number 1.0 Page 3 of 22 Revision Date 06/10/2020 Print Date 06/11/2020

1,2-Propanediol	5 - 10	57-55-6
Diethylene glycol	3 - 5	111-46-6
Urea	3 - 5	57-13-6
		0,100
Triethanolamine	1 - 3	102-71-6
Octamethylcyclotetrasiloxane	0 - 0.3	556-67-2
Carbon black	0 - 0.3	1333-86-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

# Section 4. First aid measures

## Description of necessary first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	:	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly



### WS7568 WB-S BARK RFU

Version Number 1.0 Page 4 of 22 Revision Date 06/10/2020 Print Date 06/11/2020

before reuse.

**Ingestion**: Wash out mouth with water. Remove dentures if any. Remove victim

to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing

such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact** : Causes skin irritation.

**Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

**Eye contact**: Adverse symptoms may include the following:

pain or irritation

watering

redness

**Inhalation** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact** : Adverse symptoms may include the following:

irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

**Ingestion**: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms



### WS7568 WB-S BARK RFU

 Version Number 1.0
 Page 5 of 22

 Revision Date 06/10/2020
 Print Date 06/11/2020

may be delayed. The exposed person may need to be kept under

medical surveillance for 48 hours.

**Specific treatments** : No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without

suitable training. It may be dangerous to the person providing aid to

give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

# **Section 5. Firefighting measures**

### **Extinguishing media**

Suitable extinguishing media Unsuitable extinguishing media In case of fire, use water spray (fog), foam, dry chemical or  $CO_2$ .

: None known.

Specific hazards arising from the chemical

Hazardous thermal decomposition products

In a fire or if heated, a pressure increase will occur and the container

may burst.

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides

halogenated compounds metal oxide/oxides

Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any

personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated

in positive pressure mode.

# Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without

suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note



### WS7568 WB-S BARK RFU

Version Number 1.0 Revision Date 06/10/2020 Page 6 of 22 Print Date 06/11/2020

of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### **Environmental precautions**

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

#### Precautions for safe handling

**Protective measures** 

Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.



## WS7568 WB-S BARK RFU

Version Number 1.0 Revision Date 06/10/2020 Page 7 of 22 Print Date 06/11/2020

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# Section 8. Exposure controls/personal protection

### **Control parameters**

## **Occupational exposure limits**

Ingredient name	Exposure limits
1,2-Propanediol	AIHA WEEL (1999-01-01) TWA 10 mg/m3
Titanium dioxide	OSHA PEL 1989 (1989-03-01) TWA 10 mg/m3 Form: Total dust OSHA PEL (1993-06-30) TWA 15 mg/m3 Form: Total dust ACGIH TLV (1996-05-18) TWA 10 mg/m3
Urea	AIHA WEEL (1999-01-01) TWA 10 mg/m3
Diethylene glycol	AIHA WEEL (1999-01-01) TWA 10 mg/m3
Triethanolamine	ACGIH TLV (1994-09-01) TWA 5 mg/m3
Carbon black	OSHA PEL 1989 (1989-03-01) TWA 3.5 mg/m3 OSHA PEL (1993-06-30) TWA 3.5 mg/m3 NIOSH REL (1994-06-01)

7/22



### WS7568 WB-S BARK RFU

Version Number 1.0 Revision Date 06/10/2020 Page 8 of 22 Print Date 06/11/2020

	TWA 3.5 mg/m3  NIOSH REL (1994-06-01)  TWA 0.1 mgPAH/m³  ACGIH TLV (2010-12-06)  TWA 3 mg/m3 Form: Inhalable fraction
Octamethylcyclotetrasiloxane	AIHA WEEL (2018-05-07) TWA 10 ppm

**Appropriate engineering controls** 

If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to

keep worker exposure to airborne contaminants below any

recommended or statutory limits.

**Environmental exposure controls** 

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

#### **Skin protection**

**Hand protection** 

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves



### WS7568 WB-S BARK RFU

 Version Number 1.0
 Page 9 of 22

 Revision Date 06/10/2020
 Print Date 06/11/2020

cannot be accurately estimated.

**Body protection**: Personal protective equipment for the body should be selected based

on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures

should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this

product.

**Respiratory protection**: Based on the hazard and potential for exposure, select a respirator that

meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper

fitting, training, and other important aspects of use.

# Section 9. Physical and chemical properties

#### **Appearance**

**Physical state** liquid [liquid] **BROWN** Color Odor Not available. **Odor threshold** Not available. Not available. **Melting point** Not available. **Boiling point** Not available. Flash point Not available. **Burning time** Not available. Not available. **Burning rate** Not available. **Evaporation rate** Flammability (solid, gas) Not available.

Lower and upper explosive : Lower: Not available. (flammable) limits : Upper: Not available.

Vapor pressure

Vapor density

Relative density

Solubility

Solubility in water

Partition coefficient: n
Not available.

Not available.

Not available.

Not available.

Not available.

octanol/water

Auto-ignition temperature: Not available.Decomposition temperature: Not available.SADT: Not available.

Viscosity : Dynamic: Not available.

Kinematic: Not available.

#### Aerosol product



### WS7568 WB-S BARK RFU

 Version Number 1.0
 Page 10 of 22

 Revision Date 06/10/2020
 Print Date 06/11/2020

**Heat of combustion** : Not available.

**Ignition distance** : Not available. **Enclosed space ignition - Time** : Not available.

equivalent

**Enclosed space ignition -**

**Deflagration density** 

Flame height : Not available.
Flame duration : Not available.

# Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or

its ingredients.

Not available.

Chemical stability : Stable under recommended storage and handling conditions (see

Section 7).

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will

not occur.

**Conditions to avoid** : Keep away from extreme heat and oxidizing agents.

**Incompatible materials** : Keep away from strong acids.

Oxidizer.

**Hazardous decomposition**: Under normal conditions of storage and use, hazardous decomposition

products should not be produced.

# Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Information on toxicological effects**

### **Acute toxicity**

products

Product/ingredient name	Result	Species	Dose	Exposure
Octamethylcyclotetrasiloxane				
	LD50 Oral	Rat	1,540 mg/kg	-
	LC50 Inhalation	Rat	36 Mg/l	4 h
	LD50 Dermal	Rat	1,770 mg/kg	-
Carbon black				
	LD50 Oral	Rat	15,400 mg/kg	-
Remarks - Inhalation:	No applicable toxicity data			
Remarks - Dermal:	No applicable toxicity data			



# WS7568 WB-S BARK RFU

Version Number 1.0 Revision Date 06/10/2020 Page 11 of 22 Print Date 06/11/2020

Triethanolamine						
	LD50 Oral	Rat	7,390 mg/kg	-		
Remarks - Inhalation:	No applicable toxi	city data				
Remarks - Dermal:	No applicable toxi	city data				
Diethylene glycol						
	LD50 Oral	Rat	12,000 mg/kg	-		
Remarks - Inhalation:	No applicable toxic	city data				
	LD50 Dermal	Rabbit	11,890 mg/kg	-		
Urea						
	LD50 Oral	Rat	8,471 mg/kg	-		
Remarks - Inhalation:	No applicable toxic	No applicable toxicity data				
Remarks - Dermal:	No applicable toxic	No applicable toxicity data				
Titanium dioxide						
Remarks - Oral:	No applicable toxic	city data				
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h		
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-		
1,2-Propanediol						
	LD50 Oral	Rat	20,000 mg/kg	-		
Remarks - Inhalation:	No applicable toxic	city data				
	LD50 Dermal	Rabbit	20,800 mg/kg	-		

Conclusion/Summary

Mixture.Not fully tested.

## **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
Octamethylcyclotetrasiloxan	Eyes - Mild	Rabbit		24 hrs	-
e	irritant				
	Skin - Mild	Rabbit		24 hrs	-
	irritant				
Triethanolamine	Skin - Severe	Mouse			-
	irritant				
	Skin - Mild	Human		72 hrs	-
	irritant				
	Skin - Mild	Rabbit		24 hrs	-
	irritant				
	Eyes - Severe	Rabbit			-
	irritant				
	Eyes - Mild	Rabbit			-
	irritant				
Diethylene glycol	Eyes - Mild	Rabbit			-
	irritant				
	Skin - Mild	Human		72 hrs	-
	irritant				
	Skin - Mild	Rabbit			-
	Skin - Mild	Rabbit			-



# WS7568 WB-S BARK RFU

Version Number 1.0 Revision Date 06/10/2020 Page 12 of 22 Print Date 06/11/2020

	irritant			
Urea	Skin - Moderate irritant	Human	24 hrs	-
	Skin - Mild irritant	Human	72 hrs	-
Titanium dioxide	Skin - Mild irritant	Human	72 hrs	-
1,2-Propanediol	Skin - Mild irritant	Woman	96 hrs	-
	Skin - Mild irritant	Human	168 hrs	-
	Skin - Moderate irritant	Human	72 hrs	-
	Eyes - Mild irritant	Rabbit		-
	Eyes - Mild irritant	Rabbit	24 hrs	-
	Skin - Moderate irritant	Child	96 hrs	-

Conclusion/Summary

Skin: Mixture.Not fully tested.Eyes: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

## **Sensitization**

Conclusion/Summary

Skin: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

**Mutagenicity** 

**Conclusion/Summary**: Mixture.Not fully tested.

Carcinogenicity

**Conclusion/Summary** : Mixture. Not fully tested.

Classification

Product/ingredient name	OSHA	IARC	NTP
Carbon black	-	2B	-



## WS7568 WB-S BARK RFU

Version Number 1.0 Page 13 of 22 Revision Date 06/10/2020 Print Date 06/11/2020

	Triethanolamine	-	3	-
Ī	Titanium dioxide	-	2B	-

### **Reproductive toxicity**

**Conclusion/Summary** : Mixture. Not fully tested.

**Teratogenicity** 

**Conclusion/Summary** : Mixture.Not fully tested.

**Specific target organ toxicity (single exposure)** 

Not available.

**Specific target organ toxicity (repeated exposure)** 

Not available.

**Aspiration hazard** 

Not available.

Information on likely routes of

exposure

Not available.

Potential acute health effects

**Eve contact** : Causes serious eye irritation.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact** : Causes skin irritation.

**Ingestion** : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following: pain or irritation,

watering, redness

**Inhalation** : Adverse symptoms may include the following: reduced fetal weight,

increase in fetal deaths, skeletal malformations

**Skin contact**: Adverse symptoms may include the following: irritation, redness,

reduced fetal weight, increase in fetal deaths, skeletal malformations

**Ingestion** : Adverse symptoms may include the following: reduced fetal weight,

increase in fetal deaths, skeletal malformations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure



## WS7568 WB-S BARK RFU

Version Number 1.0 Page 14 of 22 Revision Date 06/10/2020 Print Date 06/11/2020

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

**Potential chronic health effects** 

**Conclusion/Summary** : Mixture.Not fully tested.

General:No known significant effects or critical hazards.Carcinogenicity:No known significant effects or critical hazards.Mutagenicity:No known significant effects or critical hazards.Teratogenicity:No known significant effects or critical hazards.Developmental effects:No known significant effects or critical hazards.

Fertility effects : Suspected of damaging fertility.

**Numerical measures of toxicity** 

### **Acute toxicity estimates**

Route	ATE value
Oral	179,804.4 mg/kg

# Section 12. Ecological information

### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Octamethylcyclotetrasiloxane			
	Acute LC50 > 1,000 Mg/l Fresh Fish - Fish		96 h
	water		
Remarks - Acute - Fish:	Acute		
Remarks - Acute - Aquatic	No applicable toxicity data		
invertebrates.:			
	Acute NOEC 0.001 - 0.029 Mg/l Aquatic plants - Algae 9		96 h
Remarks - Acute - Aquatic	Chronic		
plants:			
	Chronic NOEC 0.0000044 Mg/l	Fish - Fish	93 d
	Fresh water		



# WS7568 WB-S BARK RFU

Version Number 1.0 Revision Date 06/10/2020 Page 15 of 22 Print Date 06/11/2020

Remarks - Chronic - Fish:	Chronic			
	Chronic NOEC 0.0079 Mg/l Fresh	Aquatic invertebrates.	21 d	
	water	Daphnia		
Remarks - Chronic -	Chronic			
Aquatic invertebrates.:				
Carbon black				
Remarks - Acute - Fish:	No applicable toxicity data	1		
	Acute EC50 37.563 Mg/l Fresh	Aquatic invertebrates.	48 h	
	water	Daphnia		
Remarks - Acute - Aquatic	Acute			
invertebrates.:				
Remarks - Acute - Aquatic	No applicable toxicity data			
plants:				
Remarks - Chronic - Fish:	No applicable toxicity data			
Remarks - Chronic -	No applicable toxicity data			
Aquatic invertebrates.:				
Triethanolamine				
	Acute LC50 11.8 Mg/l Fresh water	Fish - Fish	96 h	
Remarks - Acute - Fish:	Acute			
	Acute EC50 609.98 Mg/l Fresh	Aquatic invertebrates.	48 h	
	water	Crustaceans		
Remarks - Acute - Aquatic	Acute			
invertebrates.:				
Remarks - Acute - Aquatic	No applicable toxicity data			
plants:	,			
Remarks - Chronic - Fish:	No applicable toxicity data			
	Chronic NOEC 0.016 Mg/l Fresh	Aquatic invertebrates.	21 d	
	water	Daphnia		
Remarks - Chronic -	Chronic			
Aquatic invertebrates.:				
Diethylene glycol				
	Acute LC50 75.2 Mg/l Fresh water	Fish - Fish	96 h	
Remarks - Acute - Fish:	Acute		·	
Remarks - Acute - Aquatic	No applicable toxicity data		_	
invertebrates.:				
Remarks - Acute - Aquatic				
plants:	• • • • • • • • • • • • • • • • • • • •			
Remarks - Chronic - Fish:	No applicable toxicity data			
Remarks - Chronic -				
Aquatic invertebrates.:				
Urea				
	Acute LC50 0.000023 Mg/l Fresh	Fish - Fish	96 h	
	water			
Remarks - Acute - Fish:	Acute			
	45/00			



# WS7568 WB-S BARK RFU

Version Number 1.0 Revision Date 06/10/2020 Page 16 of 22 Print Date 06/11/2020

	A out o EC50 6 572 1 Mg/l Eroch	A questi e inventable et es	10 h	
	Acute EC50 6,573.1 Mg/l Fresh	Aquatic invertebrates. Crustaceans	48 h	
Daniela Arrata Arrata	water	Crustaceans		
Remarks - Acute - Aquatic	Acute			
invertebrates.:	A	A sussetti a tiu susuut alla matta	40.1	
	Acute EC50 3,910 Mg/l Fresh	Aquatic invertebrates.	48 h	
7	water	Daphnia		
Remarks - Acute - Aquatic	Acute			
invertebrates.:				
Remarks - Acute - Aquatic	No applicable toxicity data			
plants:	CI : NOEG 2 000 M (I.E. 1	E' 1 E' 1	20.1	
	Chronic NOEC 2,000 Mg/l Fresh	Fish - Fish	30 d	
	water			
Remarks - Chronic - Fish:	Chronic			
Remarks - Chronic -	No applicable toxicity data			
Aquatic invertebrates.:				
Titanium dioxide				
	Acute LC50 > 1,000 Mg/l Marine	Fish - Fish	96 h	
	water			
Remarks - Acute - Fish:	Acute			
	Acute LC50 3 Mg/l Fresh water	Aquatic invertebrates.	48 h	
		Crustaceans		
Remarks - Acute - Aquatic	Acute			
invertebrates.:				
	Acute LC50 6.5 Mg/l Fresh water	Aquatic invertebrates.	48 h	
		Daphnia		
Remarks - Acute - Aquatic	Acute			
invertebrates.:				
Remarks - Acute - Aquatic	No applicable toxicity data			
plants:				
Remarks - Chronic - Fish:	No applicable toxicity data			
Remarks - Chronic -	No applicable toxicity data			
Aquatic invertebrates.:				
1,2-Propanediol				
	Acute LC50 710 Mg/l Fresh water	Fish - Fish	96 h	
Remarks - Acute - Fish:	Acute			
	Acute EC50 > 110 Mg/l Fresh	Aquatic invertebrates.	48 h	
	water	Daphnia		
Remarks - Acute - Aquatic	, <u>1</u>			
invertebrates.:				
	Acute LC50 1,020 Mg/l Fresh Aquatic invertebrates.		48 h	
	water			
Remarks - Acute - Aquatic				
invertebrates.:				
Remarks - Acute - Aquatic				
Transition from figuration	1 ppireacte tollierty data			



### WS7568 WB-S BARK RFU

Version Number 1.0 Revision Date 06/10/2020 Page 17 of 22 Print Date 06/11/2020

plants:	
Remarks - Chronic - Fish:	No applicable toxicity data
Remarks - Chronic -	No applicable toxicity data
Aquatic invertebrates.:	

**Conclusion/Summary** : Not available.

Persistence and degradability

**Conclusion/Summary** : Not available.

### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Octamethylcyclotetrasiloxane	6.488	13,400.00	high
Triethanolamine	-1	3.90	low
Diethylene glycol	-1.98	100.00	low
Urea	-1.73	-	low
1,2-Propanediol	-1.070.085	-	low

### Mobility in soil

Soil/water partition coefficient

(KOC)

Other adverse effects

Not available.

No known significant effects or critical hazards.

# Section 13. Disposal considerations

### Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.



### WS7568 WB-S BARK RFU

Version Number 1.0 Revision Date 06/10/2020 Page 18 of 22 Print Date 06/11/2020

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

# Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water : Not regulated for transportation.

International Air ICAO/IATA

Consult mode specific transport rules

International Water

IMO/IMDG

: Consult mode specific transport rules

# Section 15. Regulatory information

U.S. Federal regulations : United States - TSCA 12(b) - Chemical export notification: None

of the components are listed.

United States - TSCA 4(a) - Final Test Rules: Listed

Octamethylcyclotetrasiloxane

United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed

United States - TSCA 5(a)2 - Final significant new use rules: Not

listed

United States - TSCA 5(a)2 - Proposed significant new use rules:

Not listed

United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not

determined

United States - TSCA 8(a) - Preliminary assessment report

(PAIR): Listed Octamethylcyclotetrasiloxane

United States - TSCA 8(c) - Significant adverse reaction (SAR):

Not listed



### WS7568 WB-S BARK RFU

Version Number 1.0 Revision Date 06/10/2020 Page 19 of 22 Print Date 06/11/2020

United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed Acrylonitrile

United States - EPA Clean water act (CWA) section 311 -

Hazardous substances: Listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Flammable substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Toxic substances: Not listed

**United States - Department of commerce - Precursor chemical:** 

Listed **Triethanolamine** 

Clean Air Act Section 112(b)

Hazardous Air Pollutants (HAPs)

Clean Air Act Section 602 Class I

**Substances** 

Clean Air Act Section 602 Class II

**Substances** 

**DEA List I Chemicals (Precursor** 

Chemicals)

**DEA List II Chemicals (Essential** 

**Chemicals**)

Listed

Not listed

Not listed

Not listed

Not listed

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312

**Classification** : SKIN IRRITATION - Category 2

EYE IRRITATION - Category 2A

TOXIC TO REPRODUCTION - Fertility - Category 2

### **Composition/information on ingredients**

Name	<b>%</b>	Classification
1,2-Propanediol	>= 5 - <= 10	SKIN IRRITATION - Category 2
		EYE IRRITATION - Category 2B
		- '
Titanium dioxide	>= 5 - <= 10	CARCINOGENICITY - Category 2
Octamethylcyclotetrasiloxan	> 0 - <= 0.3	FLAMMABLE LIQUIDS - Category 3
e		ACUTE TOXICITY - oral - Category 4
		ACUTE TOXICITY - dermal - Category 4
		EYE IRRITATION - Category 2B

19/22



## WS7568 WB-S BARK RFU

Version Number 1.0 Revision Date 06/10/2020 Page 20 of 22 Print Date 06/11/2020

		TOXIC TO REPRODUCTION - Fertility - Category 2
Carbon black	> 0 - <= 0.3	CARCINOGENICITY - Category 2
Triethanolamine	>= 1 - <= 3	SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A
Diethylene glycol	>= 3 - <= 5	EYE IRRITATION - Category 2B
Urea	>= 3 - <= 5	SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A

Not applicable.

**State regulations** 

Massachusetts: None of the components are listed.New York: None of the components are listed.New Jersey: The following components are listed:

Carbon black Triethanolamine Titanium dioxide 1,2-Propanediol Calcium carbonate

**Pennsylvania** : The following components are listed:

Triethanolamine

Diethylene glycol

Titanium dioxide

1,2-Propanediol

Calcium carbonate

Carbon black

### California Prop. 65

**WARNING:** This product can expose you to chemicals including Titanium dioxide, Carbon black, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable
		dosage level



### WS7568 WB-S BARK RFU

 Version Number 1.0
 Page 21 of 22

 Revision Date 06/10/2020
 Print Date 06/11/2020

Titanium dioxide	-	-
Carbon black	-	-

United States inventory (TSCA 8b) : All components are active or exempted.

Canada inventory : Not determined.

### **International regulations**

#### **Inventory list**

Not determined. Australia Canada Not determined. Not determined. China **Europe inventory** Not determined. Japan Not determined. **New Zealand** Not determined. **Philippines** Not determined. Republic of Korea Not determined. Taiwan Not determined. **Turkey** Not determined.

United States : All components are active or exempted.

# Section 16. Other information

### **Hazardous Material Information System (U.S.A.)**

Health	*	2
Flammability		0
Physical hazards		0
		•

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual. History

**Date of printing** : 06/11/2020 **Date of issue/Date of revision** : 06/10/2020



### WS7568 WB-S BARK RFU

 Version Number 1.0
 Page 22 of 22

 Revision Date 06/10/2020
 Print Date 06/11/2020

**Date of previous issue** : 00/00/0000

Version : 1.0

**Key to abbreviations** : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of

Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From

Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine

pollution)

UN = United Nations

**References** : Not available.

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.