

MATERIAL SAFETY DATA SHEET

# FM136 RED NO LEAD

Version Number 1.1 Revision Date 08/26/2002 Page 1 of 7 Print Date 11/5/2011

# 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	FM136 RED NO LEAD
Product code	:	FO20000147
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
1,2-Benzenedicarboxylic acid, butyl	85-68-7	5 - 10
phenylmethylester		
Di(2-ethylhexyl)phthalate	117-81-7	0.1 - 1
Calcium carbonate	1317-65-3	5 - 10

# 3. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET

# FM136 RED NO LEAD

sion Number 1.1 ision Date 08/26/2002	Page 2 Print Date 11/5/2
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases of doubt, seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available.
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>No data available.</li> <li>No data available.</li> <li>Not applicable.</li> <li>Carbon dioxide blanket, dry powder, foam, Water spray.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



### MATERIAL SAFETY DATA SHEET

# FM136 RED NO LEAD

Version Number 1.1 Revision Date 08/26/2002		Page 3 of 7 Print Date 11/5/2011
Handling	:	Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.
8. EXPOS	SUF	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	Under normal handling conditions a respirator may not be required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	10 mg/m3	Time Weighted Average	Total dust.	ACGIH
		(TWA):		
Calcium carbonate	5 mg/m3	PEL:	Respirable dust.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Di(2-ethylhexyl)phthal	5 mg/m3	Time Weighted Average	Vapor.	ACGIH
ate		(TWA):		
Di(2-ethylhexyl)phthal	5 mg/m3	PEL:	Vapor.	OSHA Z1
ate				

## 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- : Liquid
  : Viscous, Liquid
  : RED
  : Very faint
  : Not applicable
  : Not applicable
  : Immiscible
- Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH
- Not established
  Not determined
  Not applicable.
  Not determined
  Not determined
  Not applicable.



MATERIAL SAFETY DATA SHEET

# FM136 RED NO LEAD

Version Number 1.1 Revision Date 08/26/2002 Page 4 of 7 Print Date 11/5/2011

	10. STABILITY AND REACTIVITY
Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	<ul> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).</li> </ul>

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
85-68-7	1,2-Benzenedicarboxylic acid, butyl phenylmethylester	Irritant	Eyes, Skin.
		Systemic effects	Liver, reproductive system.
117-81-7	Di(2-ethylhexyl)phthalate	Systemic effects	Eyes, Respiratory system, Liver, central nervous system, Skin, digestive system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

### LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
85-68-7	1,2-Benzenedicarboxylic acid, butyl phenylmethylester	Oral LD50 Dermal LD50	2,330 mg/kg > 10 gm/kg	rat rabbit
117-81-7	Di(2-ethylhexyl)phthalate	Oral LD50 Dermal LD50	30 gm/kg 25 gm/kg	rat rabbit

Carcinogenicity:



MATERIAL SAFETY DATA SHEET

# FM136 RED NO LEAD

Version Number 1.1 Revision Date 08/26/2002 Page 5 of 7 Print Date 11/5/2011

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
117-81-7	Di(2-ethylhexyl)phthalate	no	no	2

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

#### Additional Health Hazard Information:

Di(2-ethylhexyl)phthalate 117-81-7 There is sufficient evidence for the carcinogenicity of di (2-ethylhexyl) phthalate in experimental animals. Administered in the feed this chemical caused an increase incidence of liver cancer in male and female rats and mice. The relevance of this finding to humans is uncertain.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: No data available.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT / CA TDG Classification	: Not regulated for transportation.



# MATERIAL SAFETY DATA SHEET

# FM136 RED NO LEAD

	08/26/2002							ate 11/5/2
ICAO/IATA	Δ	: Not re	egulated for	transpo	rtation.			
IMO / IMD	G	: Not re	egulated for	transpo	rtation.			
		15. REG	ULATORY	INFO	RMATION			
US Regulat	ons:							
OSH	IA Status	: Classi	fied as haza	rdous b	ased on compo	onents.		
TSC	A Status	: All co exemp	-	f this pr	oduct are listed	d on the	TSCA inve	entory or ar
US. EPA CI	ERCLA Hazard	lous Substances	(40 CFR 30	)2)				
Chen	nical Name	CAS-No.	% in Pr	oduct	RQ for comp	onent	RQ for Mixture/F	Product
oxyli	enzenedicarb c acid, butyl ylmethylester	85-68-7	6.4295		100 lbs		1,555 LB	
Cali 65	fornia Propositi		NING! Thi ornia to caus		ct contains a cl r.	hemical	known in t	the State of
65	-		ornia to caus			hemical	known in t	the State of
65	III Section 313 Chemical N	Califo 3 Toxic Chemica ame	ornia to caus als:	cance	r. -No.	Weigh		the State of
65	III Section 313 Chemical N	Califo 3 Toxic Chemica	ornia to caus als:	e cance	r. -No.			the State of
65 SARA Title	III Section 313 Chemical N DI(2-ETHY (DEHP)	Califo 3 Toxic Chemica ame	ornia to caus als:	cance	r. -No.	Weigh		the State of
65 SARA Title Canadian R	III Section 313 Chemical N DI(2-ETHY (DEHP) egulations:	Califo 3 Toxic Chemica ame	ornia to caus als:	cance	r. -No.	Weigh		the State of
65 SARA Title Canadian R WH	III Section 313 Chemical N DI(2-ETHY (DEHP) egulations: MIS Classificat	Califo 3 Toxic Chemica ame THEXYL)PHT	ornia to caus als:	cance	r. -No.	Weigh		the State of
65 SARA Title Canadian R WH	III Section 313 Chemical N DI(2-ETHY (DEHP) egulations: MIS Classificat	Califo 3 Toxic Chemica 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	ornia to caus als:	cance	r. -No.	Weigh		the State of
65 SARA Title Canadian R WH	III Section 313 Chemical N DI(2-ETHY (DEHP) egulations: MIS Classificat MIS Ingredient CAS-No. 117-81-7 85-68-7	Califo 3 Toxic Chemica 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	ornia to caus	cance	r. -No.	Weigh		the State of
65 SARA Title Canadian R WH WHI	III Section 313 Chemical N DI(2-ETHY (DEHP) egulations: MIS Classificat MIS Ingredient CAS-No. 117-81-7 85-68-7	Califo 3 Toxic Chemica ame LHEXYL)PHT tion : D2A Disclosure List	ornia to caus	cance	r. -No.	Weigh		the State of



### MATERIAL SAFETY DATA SHEET

# FM136 RED NO LEAD

Version Number 1.1 Revision Date 08/26/2002 Page 7 of 7 Print Date 11/5/2011

China IECS	: Not determined.
Europe EINECS	: Not determined.
Japan ENCS	: Not determined.
Korea KECI	: Not determined.
Philippines PICCS	: Not determined.

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.