MATERIAL SAFETY DATA SHEET OP BURGUNDY

Version Number 1.3 Revision Date 06/17/2008 Page 1 of 6 Print Date 1/4/2012

1. PRODUCT AND COMPANY IDENTIFICATION POLYONE CORPORATION

8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone:Emergency telephone:	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	OP BURGUNDY
Product code	:	FO20000186
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Iron oxide	1309-37-1	0.1 - 1

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion		
Acute exposure			
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.		
Ingestion	: May be harmful if swallowed.		
Eyes	: May cause eye/skin irritation.		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		
Medical Conditions Aggravated by Exposure:	: None known.		



MATERIAL SAFETY DATA SHEET **OP BURGUNDY**

Version Number 1.3 Revision Date 06/17/2008 Page 2 of 6 Print Date 1/4/2012

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 No data available No data available Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	5. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing



MATERIAL SAFETY DATA SHEET **OP BURGUNDY**

appropriate exhaust ventilation at machinery. Exposure limit(s) Exposure limit Exposure type Lis Iron oxide 5 mg/m3 Time Weighted Average (TWA): Respirable fraction. ACC 10 mg/m3 PEL: Fume. OSHA 5 mg/m3 Time Weighted Average (TWA): as Fe MX C	on Number 1.3 sion Date 06/17/2008			Prin	Page 3 t Date 1/4/2
and contamination. Store in a cool dry place. 8. EXPOSURE CONTROLS/PERSONAL PROTECTION Respiratory protection : No personal respiratory protective equipment normally required. Eye/Face Protection : Safety glasses with side-shields Hand protection : Protective gloves Skin and body protection : Long sleeved clothing Additional Protective : Safety shoes Measures : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Ion mg/m3 Time Weighted Average Respirable fraction. ACC (TWA): 10 mg/m3 Time Weighted Average As Fe MX C (TWA): 10 mg/m3 Short Term Exposure Limit as Fe		Р	eriodically clean hoods, ducts,	and other surfaces to m	
Respiratory protection : No personal respiratory protective equipment normally required. Eye/Face Protection : Safety glasses with side-shields Hand protection : Protective gloves Skin and body protection : Long sleeved clothing Additional Protective : Safety shoes Measures : General Hygiene : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Iron oxide 5 mg/m3 10 mg/m3 PEL: Fume. OSH/ 5 mg/m3 Time Weighted Average (TWA): 10 mg/m3 Short Term Exposure Limit as Fe	Storage				e absorption
Eye/Face Protection : Safety glasses with side-shields Hand protection : Protective gloves Skin and body protection : Long sleeved clothing Additional Protective : Safety shoes Measures : Safety shoes General Hygiene : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : 10 mg/m3 10 mg/m3 Time Weighted Average (TWA): : 10 mg/m3 Short Term Exposure Limit as Fe	8. 1	EXPOSURE	CONTROLS/PERSONAL I	PROTECTION	
Hand protection : Protective gloves Skin and body protection : Long sleeved clothing Additional Protective : Safety shoes Measures : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Iron oxide 5 mg/m3 10 mg/m3 PEL: Fume. OSH4 5 mg/m3 Time Weighted Average (TWA): 10 mg/m3 Short Term Exposure Limit 10 mg/m3 Short Term Exposure Limit	Respiratory protection	: N	lo personal respiratory protecti	ve equipment normally	required.
Skin and body protection : Long sleeved clothing Additional Protective : Safety shoes Measures : General Hygiene : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) Iron oxide 5 mg/m3 10 mg/m3 PEL: Fume. OSH4 10 mg/m3 Short Term Exposure Limit 10 mg/m3 Short Term Exposure Limit	Eye/Face Protection	: S	afety glasses with side-shields		
Additional Protective Measures : Safety shoes General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Io mg/m3 Time Weighted Average (TWA): : Exposure type 10 mg/m3 : Fume. OSHA (TWA): 10 mg/m3 Short Term Exposure Limit as Fe	Hand protection	: P	rotective gloves		
Measures General Hygiene : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation. Accord (TWA): 10 mg/m3 PEL: 5 mg/m3 Time Weighted Average (TWA): 10 mg/m3 Short Term Exposure Limit as Fe 10 mg/m3 Short Term Exposure Limit as Fe	Skin and body protection	: L	ong sleeved clothing		
Considerations practice. Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Components Value Exposure limit(s) : : : <td></td> <td colspan="4">: Safety shoes</td>		: Safety shoes			
appropriate exhaust ventilation at machinery. Exposure limit(s) Exposure time Exposure type Lis Iron oxide 5 mg/m3 Time Weighted Average Respirable fraction. ACC Iron oxide 5 mg/m3 Time Weighted Average Respirable fraction. ACC Iron oxide 5 mg/m3 Time Weighted Average Respirable fraction. ACC Iron oxide 10 mg/m3 PEL: Fume. OSHA Iron oxide 10 mg/m3 Short Term Exposure Limit as Fe MX C					
ComponentsValueExposure timeExposure typeLisIron oxide5 mg/m3Time Weighted Average (TWA):Respirable fraction.ACC10 mg/m3PEL:Fume.OSHA5 mg/m3Time Weighted Average (TWA):as FeMX C10 mg/m3Short Term Exposure Limitas FeMX C					
Iron oxide 5 mg/m3 Time Weighted Average (TWA): Respirable fraction. ACC 10 mg/m3 PEL: Fume. OSHA 5 mg/m3 Time Weighted Average (TWA): as Fe MX C 10 mg/m3 Short Term Exposure Limit as Fe MX C	Exposure limit(s)				
Iron oxide 5 mg/m3 Time Weighted Average (TWA): Respirable fraction. ACC 10 mg/m3 PEL: Fume. OSHA 5 mg/m3 Time Weighted Average (TWA): as Fe MX C 10 mg/m3 Short Term Exposure Limit as Fe MX C	Components	Value	Exposure time	Exposure type	List:
5 mg/m3 Time Weighted Average (TWA): as Fe MX C 10 mg/m3 Short Term Exposure Limit as Fe MX C	Iron oxide	5 mg/m3			ACGIH
(TWA): 10 mg/m3 Short Term Exposure Limit as Fe MX C			PEL:	Fume.	OSHA Z1
U I		5 mg/m3	(TWA):	as Fe	MX OEL
		10 mg/m3	1	as Fe	MX OEL
9. PHYSICAL AND CHEMICAL PROPERTIES		0 DHVG	AL AND CHEMICAL DDO	PERTIES	

Form Appearance Color Odour Melting point/range Boiling Point: Water solubility

3/6

10. STABILITY AND REACTIVITY

Evaporation rate

Specific Gravity

Vapour pressure

Vapour density

Bulk density

pН

Not established

Not determined

Not applicable

Not determined

: Not determined

: Not applicable

:

:

:

:

: liquid

RED

Very faint

: Immiscible

: Not applicable

Not applicable

:

:

:

:

Viscous, liquid

PolyOne

MATERIAL SAFETY DATA SHEET OP BURGUNDY

Version Number 1.3 Revision Date 06/17/2008 Page 4 of 6 Print Date 1/4/2012

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	-	Chemical Name	Effect	Target Organ	
1309-37-1	309-37-1 Iron oxide		Systemic effects	Respiratory system.	
				T	
		12. ECOLOGIC	AL INFORMATION	N	
Persistence and degra	dability	: Not readily bi	odegradable.		
Environmental Toxic	ity	: Environmental toxicity has not been established for this mixture as a whole.			
Bioaccumulation Pote	ential	: No data availa	able		
Additional advice		: No data available			
		13. DISPOSAL	CONSIDERATIONS	5	
Product		: Where possib generator of v classification,	le recycling is preferre vaste material has the r	d to disposal or incineration. The sponsibility for proper waste posal in accordance with	
Contaminated packaging				e. The generator of waste oper waste classification,	

PolyOne.

MATERIAL SAFETY DATA SHEET **OP BURGUNDY**

Version Number 1.3 Revision Date 06/17/2008

Page 5 of 6 Print Date 1/4/2012

	14. TRANSPORT INFORMATION	
U.S. DOT Classification	: Refer to specific regulation.	
ICAO/IATA (air)	: Refer to specific regulation.	
IMO / IMDG (maritime)	: Refer to specific regulation.	
	15. REGULATORY INFORMATION	
US Regulations:		
OSHA Status	: Classified as hazardous based on components.	
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.	
US. EPA CERCLA Hazardous	Substances (40 CFR 302)	
Not applicable		
California Proposition 65	: Not applicable	
SARA Title III Section 302 Ext	remely Hazardous Substance	
Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation		
SARA Title III Section 313 Tox	tic Chemicals:	
Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation		
Canadian Regulations:		
National Pollutant Release Inventory (NPRI)		
Not applicable		
WHMIS Classification	: Not controlled.	
DSL	: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.	

PolyOne

MATERIAL SAFETY DATA SHEET **OP BURGUNDY**

Version Number 1.3 Revision Date 06/17/2008 Page 6 of 6 Print Date 1/4/2012

National Inventories:

Australia AICS	: Not determined
China IECS	: Not determined
Europe EINECS	: Not determined
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.