

MATERIAL SAFETY DATA SHEET

DB3384 Black

Version Number 1.0 Revision Date 07/09/2002 Page 1 of 6 Print Date 11/5/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	DB3384 Black
Product code	:	FO20000787
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Carbon black	1333-86-4	0.1 - 1

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

DB3384 Black

sion Date 07/09/2002	Print Date 11/5/
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases
	doubt, seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If en irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available.
Flammable Limits	
Upper explosion limit	: No data available.
Lower explosion limit Autoignition temperature	No data available.Not applicable.
Suitable extinguishing media	: Carbon dioxide blanket, dry powder, foam, Water spray.
Special Fire Fighting	: Fullface self-contained breathing apparatus (SCBA) used in positive
Procedures	pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion	: May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under
Hazards	fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize

MATERIAL SAFETY DATA SHEET



			Print I	Page Date 11/5/		
	a	ccumulation of these materials	S.			
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.					
8. I	EXPOSURE	CONTROLS / PERSONAL	PROTECTION			
Respiratory protection	: U	nder normal handling condition	ons a respirator may not b	be required.		
Eye/Face Protection	: S	afety glasses with side-shields	3.			
Hand protection	: P:	rotective gloves.				
Skin and body protection	: L	ong sleeved clothing.				
Additional Protective Measures	: S	afety shoes.				
General Hygiene Considerations		andle in accordance with good ash hands before breaks and		afety practio		
Engineering measures		eat only in areas with approproprion of the second se		Provide		
Exposure limit(s)						
Components	Value	Exposure time	Exposure type	List:		
Components Calcium carbonate	Value 10 mg/m3	Exposure time Time Weighted Average (TWA):	Exposure type Total dust.	List: ACGIH		
		Time Weighted Average		ACGIH		
Calcium carbonate	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH OSHA Z		
Calcium carbonate Calcium carbonate Carbon black	10 mg/m3 5 mg/m3 15 mg/m3 3.5 mg/m3	Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA):	Total dust. Respirable dust.	ACGIH OSHA Z OSHA Z ACGIH		
Calcium carbonate Calcium carbonate	10 mg/m3 5 mg/m3 15 mg/m3	Time Weighted Average (TWA): PEL: PEL: Time Weighted Average	Total dust. Respirable dust. Total dust. Total dust. as carbon	ACGIH OSHA Z OSHA Z ACGIH		
Calcium carbonate Calcium carbonate Carbon black	10 mg/m3 5 mg/m3 15 mg/m3 3.5 mg/m3 3.5 mg/m3	Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA):	Total dust. Respirable dust. Total dust. Total dust. as carbon black Total dust. as carbon black	ACGIH OSHA Z OSHA Z ACGIH		
Calcium carbonate Calcium carbonate Carbon black Carbon black	10 mg/m3 5 mg/m3 15 mg/m3 3.5 mg/m3 3.5 mg/m3 9. PHYSIC	Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO	Total dust. Respirable dust. Total dust. Total dust. as carbon black Total dust. as carbon black DPERTIES	ACGIH OSHA Z OSHA Z ACGIH OSHA Z		
Calcium carbonate Calcium carbonate Carbon black Carbon black Form	10 mg/m3 5 mg/m3 15 mg/m3 3.5 mg/m3 3.5 mg/m3 9. PHYSIC : Liqui	Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO	Total dust. Respirable dust. Total dust. Total dust. as carbon black Total dust. as carbon black DPERTIES Dration rate : Not	ACGIH OSHA Z OSHA Z ACGIH OSHA Z established		
Calcium carbonate Calcium carbonate Carbon black Carbon black Form Appearance	10 mg/m3 5 mg/m3 15 mg/m3 3.5 mg/m3 3.5 mg/m3 9. PHYSIC : Liqui : Visco	Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO	Total dust. Respirable dust. Total dust. Total dust. as carbon black Total dust. as carbon black DPERTIES Total or rate : Not fic Gravity : Not	ACGIH OSHA Z OSHA Z ACGIH OSHA Z established determined		
Calcium carbonate Calcium carbonate Carbon black Carbon black Form	10 mg/m3 5 mg/m3 15 mg/m3 3.5 mg/m3 3.5 mg/m3 9. PHYSIC : Liqui : Visco : BLA	Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO id Evapo pus, Liquid Specif CK Bulk of	Total dust. Respirable dust. Total dust. Total dust. as carbon black Total dust. as carbon black DPERTIES oration rate : Not c Gravity : Not lensity : Not	ACGIH OSHA Z OSHA Z ACGIH OSHA Z established determined applicable.		
Calcium carbonate Calcium carbonate Carbon black Carbon black Form Appearance Color	10 mg/m3 5 mg/m3 15 mg/m3 3.5 mg/m3 3.5 mg/m3 9. PHYSIC : Liqui : Visco : BLA : Very	Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO id Evapo ous, Liquid Specif CK Bulk of faint Vapor	Total dust. Respirable dust. Total dust. as carbon black Total dust. as carbon black Total dust. as carbon black DPERTIES Total orate : Not fic Gravity : Not lensity : Not pressure : Not	ACGIH OSHA Z OSHA Z ACGIH OSHA Z established determined applicable. determined		
Calcium carbonate Calcium carbonate Carbon black Carbon black Form Appearance Color Odor	10 mg/m3 5 mg/m3 15 mg/m3 3.5 mg/m3 3.5 mg/m3 9. PHYSIC : Liqui : Visco : BLA : Very : Not a : Not a	Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO CAL AND CHEMICAL PRO DUS, Liquid Specific CK Bulk of faint Vapor applicable Vapor applicable pH	Total dust. Respirable dust. Total dust. as carbon black Total dust. as carbon black Total dust. as carbon black DPERTIES Total orate : Not fic Gravity : Not lensity : Not orgensure : Not orge	ACGIH OSHA Z OSHA Z ACGIH OSHA Z established determined applicable. determined determined		
Calcium carbonate Calcium carbonate Carbon black Carbon black Carbon black Form Appearance Color Odor Melting point/range	10 mg/m3 5 mg/m3 15 mg/m3 3.5 mg/m3 3.5 mg/m3 9. PHYSIC : Liqui : Visco : BLA : Very : Not a	Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO CAL AND CHEMICAL PRO DUS, Liquid Specific CK Bulk of faint Vapor applicable Vapor applicable pH	Total dust. Respirable dust. Total dust. as carbon black Total dust. as carbon black Total dust. as carbon black DPERTIES Total orate : Not fic Gravity : Not lensity : Not orgensure : Not orge	List: ACGIH OSHA Z OSHA Z ACGIH OSHA Z OSHA Z established determined applicable. determined applicable.		
Calcium carbonate Calcium carbonate Carbon black Carbon black Carbon black Form Appearance Color Odor Melting point/range Boiling Point:	10 mg/m3 5 mg/m3 15 mg/m3 3.5 mg/m3 3.5 mg/m3 9. PHYSIC : Liqui : Visco : BLA : Very : Not a : Not a : Immi	Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO CAL AND CHEMICAL PRO DUS, Liquid Specific CK Bulk of faint Vapor applicable Vapor applicable pH	Total dust. Respirable dust. Total dust. Total dust. as carbon black Total dust. as carbon black DPERTIES oration rate : Not Fic Gravity : Not opressure : Not · Pressure : Not · Not : Not	ACGIH OSHA Z OSHA Z ACGIH OSHA Z established determined applicable. determined determined		

DB3384 Black

MATERIAL SAFETY DATA SHEET



Version Number 1.0 Page 4 of 6 Revision Date 07/09/2002 Print Date 11/5/2011 Hazardous Polymerization : Will not occur. : Keep away from oxidizing agents and open flame. To avoid thermal Conditions to avoid decomposition, do not overheat. Incompatible Materials : Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen Hazardous decomposition : products (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	> 15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1333-86-4	Carbon black	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:



MATERIAL SAFETY DATA SHEET

DB3384 Black

Version Number 1.0	Page 5 of 6
Revision Date 07/09/2002	Print Date 11/5/2011

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: No data available.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT / CA TDG Classification	: Not regulated for transportation.
ICAO/IATA	: Not regulated for transportation.
IMO / IMDG	: Not regulated for transportation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.



MATERIAL SAFETY DATA SHEET

ersion Number 1.0		Page 6 of
evision Date 07/09/2002		Print Date 11/5/201
TSCA Status	:	All components of this product are listed on the TSCA inventory or are exempt.
US. EPA CERCLA Hazardous	Sub	stances (40 CFR 302)
Not applicable		
California Droposition		WADNING This product contains a shemical known in the State of
California Proposition 65	:	WARNING! This product contains a chemical known in the State of California to cause cancer.
Canadian Regulations:		
WHMIS Classification	:	D2A
DSL	:	Listed.
National Inventories:		
Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Not determined.
Philippines PICCS	:	Listed.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.