

### MATERIAL SAFETY DATA SHEET

# STAN-TONE HCC-21283 HI-LITE ORANGE

Version Number 1.1 Page 1 of 7
Revision Date 08/15/2003 Print Date 11/12/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION

2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY : Product Stewardship, (314) 771-1800

TELEPHONE

Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure

number or accident).

Product name : STAN-TONE HCC-21283 HI-LITE ORANGE

Product code : FO20000823 Chemical Name : Mixture CAS-No. : Mixture

Product Use : Industrial Applications

### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

| Components             | CAS-No.    | Weight % |
|------------------------|------------|----------|
| Ethyl benzene          | 100-41-4   | 0.1 - 1  |
| 1,2,4-Trimethylbenzene | 95-63-6    | 5 - 10   |
| Mica                   | 12001-26-2 | 10 - 30  |

## 3. HAZARDS IDENTIFICATION

### **EMERGENCY OVERVIEW**

Combustible. Vapors may be irritating to eyes and respiratory tract. This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Inhalation, Skin contact, Ingestion

Acute exposure

Inhalation : Inhalation of airborne droplets may cause irritation of the respiratory

tract.

Ingestion : May be harmful if swallowed. Eyes : May cause eye/skin irritation.

Skin : Experience shows no unusual dermatitis hazard from routine handling.

**Chronic exposure** : Refer to Section 11 for Toxicological Information.



#### MATERIAL SAFETY DATA SHEET

# STAN-TONE HCC-21283 HI-LITE ORANGE

 Version Number 1.1
 Page 2 of 7

 Revision Date 08/15/2003
 Print Date 11/12/2011

**Medical Conditions** 

Aggravated by Exposure:

: None known.

4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of fumes from

overheating or combustion. When symptoms persist or in all cases of

doubt seek medical advice.

Ingestion : Do not induce vomiting without medical advice. Seek medical

attention if necessary.

Eyes : Rinse immediately with plenty of water for at least 15 minutes. If eye

irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists seek

medical attention.

**5. FIRE-FIGHTING MEASURES** 

Flash point : Between 100  $^{\circ}$ F and 200  $^{\circ}$ F

Flammable Limits

Upper explosion limit : No data available.

Lower explosion limit : No data available.

Autoignition temperature : No data available.

Suitable extinguishing media : Carbon dioxide blanket, dry powder, foam, water spray.

Special Fire Fighting

Procedures

: Fullface self-contained breathing apparatus (SCBA) used in positive  $\,$ 

pressure mode should be worn to prevent inhalation of airborne

contaminants.

Unusual Fire/Explosion

Hazards

May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under

fire conditions.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear appropriate personal protection during cleanup, such as

impervious gloves, boots and coveralls.

Environmental precautions : Should not be released into the environment. The product should not

be allowed to enter drains, water courses or the soil.

Methods for cleaning up : Contain and collect spillage with non-combustible absorbent material,

(e.g. sand, earth, diatomaceus earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Package all material in appropriate container for disposal.

Refer to Section 13 of this MSDS for proper disposal methods.

7. HANDLING AND STORAGE



### MATERIAL SAFETY DATA SHEET

# STAN-TONE HCC-21283 HI-LITE ORANGE

Version Number 1.1 Page 3 of 7
Revision Date 08/15/2003 Print Date 11/12/2011

Handling : Combustible liquid. Keep away from flames, hot surfaces, and sources

of ignition. Use only in an area with appropriate ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to

minimize accumulation of these materials.

Storage : Store below 140 deg F (60 deg C). Keep containers dry and tightly

closed to avoid moisture absorption and contamination.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection : Under normal handling conditions a respirator may not be required.

Airborne contaminant levels should be maintained below the

occupational exposure guidelines.

Eye/Face Protection : Safety glasses with side-shields.

Hand protection : Protective gloves.

Skin and body protection : Long sleeved clothing.

Additional Protective

Measures

Safety shoes.

General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Ensure adequate

ventilation, especially in confined areas.

Engineering measures : Provide general and/or local exhaust ventilation to control airborne

contaminant levels below the exposure guidelines.

## Exposure limit(s)

| Components            | Value      | Exposure time             | Exposure type        | List:   |
|-----------------------|------------|---------------------------|----------------------|---------|
| Ethyl benzene         | 100 ppm    | Time Weighted Average     | Vapor and aerosol.   | ACGIH   |
|                       | 434 mg/m3  | (TWA):                    |                      |         |
|                       | 125 ppm    | Short Term Exposure Limit | Vapor and aerosol.   | ACGIH   |
|                       | 543 mg/m3  | (STEL):                   |                      |         |
|                       | 100 ppm    | PEL:                      | Vapor and aerosol.   | OSHA Z1 |
|                       | 435 mg/m3  |                           |                      |         |
| Mica                  | 20 mppcf   | PEL:                      | Total dust.          | OSHA    |
|                       | 3 mg/m3    | Time Weighted Average     | Respirable fraction. | ACGIH   |
|                       |            | (TWA):                    |                      |         |
| 1,2,4-Trimethylbenzen | 25 ppm 123 | Time Weighted Average     | Vapor.               | ACGIH   |
| e                     | mg/m3      | (TWA):                    |                      |         |

# 9. PHYSICAL AND CHEMICAL PROPERTIES



#### MATERIAL SAFETY DATA SHEET

# STAN-TONE HCC-21283 HI-LITE ORANGE

Version Number 1.1 Page 4 of 7
Revision Date 08/15/2003 Print Date 11/12/2011

Form : Liquid Evaporation rate : Not established Appearance : Viscous, Liquid Specific Gravity Not determined Color : ORANGE Bulk density Not applicable. Odor : Very faint Vapor pressure Not determined : Not determined Melting point/range : Not applicable Vapor density Boiling Point: : No data available. : Not determined pН

Water solubility : Immiscible

## 10. STABILITY AND REACTIVITY

Stability : Stable.

Hazardous Polymerization : Will not occur.

Conditions to avoid : Keep away from oxidizing agents and open flame.

Incompatible Materials : Incompatible with strong acids and oxidizing agents. Avoid contact

with acetal homopolymers and acetal copolymers during processing.

Hazardous decomposition

products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

# 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

## **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

| CAS-No.    | Chemical Name          | Effect           | Target Organ                    |
|------------|------------------------|------------------|---------------------------------|
| 100-41-4   | Ethyl benzene          | Irritant         | Eyes, Skin, Respiratory system. |
|            |                        | Systemic effects | Eyes, Skin, Respiratory system, |
|            |                        |                  | central nervous system.         |
| 95-63-6    | 1,2,4-Trimethylbenzene | Systemic effects | central nervous system.         |
|            |                        | Irritant         | Eyes, Skin.                     |
| 12001-26-2 | Mica                   | Systemic effects | Respiratory system.             |

### LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

| CAS-No.  | Chemical Name          | Route       | Value       | Species |
|----------|------------------------|-------------|-------------|---------|
| 100-41-4 | Ethyl benzene          | Oral LD50   | 3,500 mg/kg | rat     |
|          |                        | Dermal LD50 | 17800 ul/kg | rabbit  |
| 95-63-6  | 1,2,4-Trimethylbenzene | Oral LD50   | 5,000 mg/kg | rat     |



#### MATERIAL SAFETY DATA SHEET

# STAN-TONE HCC-21283 HI-LITE ORANGE

Version Number 1.1 Page 5 of 7
Revision Date 08/15/2003 Print Date 11/12/2011

## Carcinogenicity:

This product contains the following components which, in their pure form, have the following carcinogenicity data:

| CAS-No.  | Chemical Name | OSHA | IARC | NTP |
|----------|---------------|------|------|-----|
| 100-41-4 | Ethyl benzene | no   | 2B   | no  |

### IARC Carcinogen Classifications:

- 1 The component is carcinogenic to humans.
- 2A The component is probably carcinogenic to humans.
- 2B The component is possibly carcinogenic to humans.

## NTP Carcinogen Classifications:

- 1 The component is known to be a human carcinogen.
- 2 The component is reasonably anticipated to be a human carcinogen.

| 12. | ECOL | OGICAL | INFORMATION  |
|-----|------|--------|--------------|
| 14. | ECOL | OUICAL | HIT OKMALION |

Persistence and degradability : Not readily biodegradable.

Environmental Toxicity : Environmental toxicity has not been established for this mixture as a

whole.

Bioaccumulation Potential : No data available.

Additional advice : No data available.

### 13. DISPOSAL CONSIDERATIONS

Product : Where possible, recycling is preferred to disposal or incineration. The

generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste material

has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial

and local regulations.

## 14. TRANSPORT INFORMATION

U.S. DOT Classification : Refer to specific regulation.

ICAO/IATA : Refer to specific regulation.

IMO / IMDG : Refer to specific regulation.

#### 15. REGULATORY INFORMATION



## MATERIAL SAFETY DATA SHEET

# STAN-TONE HCC-21283 HI-LITE ORANGE

 Version Number 1.1
 Page 6 of 7

 Revision Date 08/15/2003
 Print Date 11/12/2011

US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on or exempt from the TSCA

Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

| Chemical Name       | CAS-No.   | % in Product | RQ for component | RQ for          |
|---------------------|-----------|--------------|------------------|-----------------|
|                     |           |              |                  | Mixture/Product |
| Xylenes (o-, m-, p- | 1330-20-7 | 0.7160       | 100 lbs          | 13,966 LB       |
| isomers)            |           |              |                  |                 |

California Proposition : This product does not contain a substance listed by California Prop 65.

65

SARA Title III Section 302 Extremely Hazardous Substance

Not applicable

SARA Title III Section 313 Toxic Chemicals:

| Chemical Name          | CAS-No. | Weight % |
|------------------------|---------|----------|
| 1,2,4-TRIMETHYLBENZENE | 95-63-6 | 7.63     |

# Canadian Regulations:

National Pollutant Release Inventory (NPRI)

| Chemical Name                | CAS-No.   | Weight % | NPRI ID# |
|------------------------------|-----------|----------|----------|
| Chromium hydroxide (Cr(OH)3) | 1308-14-1 | 0.51     | 68       |
| Ethyl benzene                | 100-41-4  | 0.11     | 111      |
| Xylenes (o-, m-, p- isomers) | 1330-20-7 | 0.71     | 240      |
| Cumene                       | 98-82-8   | 0.35     | 73       |
| 1,2,4-Trimethylbenzene       | 95-63-6   | 7.63     | 233      |

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

| CAS-No.    |
|------------|
| 100-41-4   |
| 12001-26-2 |
| 1330-20-7  |



## MATERIAL SAFETY DATA SHEET

# STAN-TONE HCC-21283 HI-LITE ORANGE

 Version Number 1.1
 Page 7 of 7

 Revision Date 08/15/2003
 Print Date 11/12/2011

95-63-6

DSL : All components of this product are on the Canadian Domestic

Substances List (DSL) or are exempt.

National Inventories:

Australia AICS : Not determined.

China IECS : Listed.

Europe EINECS : Not determined.

Japan ENCS : Not determined.

Korea KECI : Not determined.

Philippines PICCS : Not determined.

## 16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.