

MATERIAL SAFETY DATA SHEET

WB-10472-A WHITE SATURANT

 Version Number 1.2
 Page 1 of 7

 Revision Date 02/10/2004
 Print Date 11/13/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION

2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY : Product Stewardship (314) 771-1800

TELEPHONE

Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure

number or accident).

Product name : WB-10472-A WHITE SATURANT

Product code : FO20000836 Chemical Name : Mixture CAS-No. : Mixture

Product Use : Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous	7631-86-9	1 - 5
Ethylene glycol	107-21-1	1 - 5
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Eyes, Skin contact, Inhalation, Ingestion

Acute exposure

Inhalation : Excessive inhalation of product vapors, especially during heating or

processing, may be irritating to respiratory system.

Ingestion : May be harmful if swallowed.

Eyes : Mild eye irritation

Skin : Prolonged or repeated skin contact can cause de-fatting and drying of

the skin which may result in skin irritation and dermatitis (rash).

Chronic exposure : Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET

WB-10472-A WHITE SATURANT

 Version Number 1.2
 Page 2 of 7

 Revision Date 02/10/2004
 Print Date 11/13/2011

Medical Conditions Aggravated by Exposure:

: None known.

4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of vapors or fumes

from overheating or combustion. When symptoms persist or in all

cases of doubt seek medical advice.

Ingestion : Drink 1 or 2 glasses of water. Induce vomiting immediately and call a

physician. Never give anything by mouth to an unconscious person.

Eyes : Immediately flush eye(s) with plenty of water. Seek medical attention

if necessary.

Skin : Wash off immediately with soap and plenty of water. If skin irritation

persists seek medical attention.

5. FIRE-FIGHTING MEASURES

Flash point : Greater than 200 °F (93 °C)

Flammable Limits

Upper explosion limit : No data available
Lower explosion limit : No data available
Autoignition temperature : No data available

Suitable extinguishing media : carbon dioxide (CO2), dry chemical, water spray, alcohol-resistant

foamnone.

Special Fire Fighting

Procedures

: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne

contaminants.

Unusual Fire/Explosion

Hazards

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen

(NOx), other hazardous materials, and smoke are all possible.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear appropriate personal protection during cleanup, such as

impervious gloves, boots and coveralls. Material can create slippery

conditions.

Environmental precautions : The product should not be allowed to enter drains, water courses or the

soil. Should not be released into the environment.

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder,

universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper

disposal methods.



MATERIAL SAFETY DATA SHEET

WB-10472-A WHITE SATURANT

 Version Number 1.2
 Page 3 of 7

 Revision Date 02/10/2004
 Print Date 11/13/2011

7. HANDLING AND STORAGE

Handling : Heat only in areas with appropriate exhaust ventilation.

Storage : Keep containers dry and tightly closed to avoid moisture absorption

and contamination. Store in a cool dry place. Product is hygroscopic.

Protect from moisture. Keep drums tigthly closed to prevent

contamination.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection : Under normal handling conditions a respirator may not be required.

Eye/Face Protection : Safety glasses with side-shields.

Hand protection : Protective gloves.

Skin and body protection : Long sleeved shirts and long pants are adequate for normal handling.

Where operations present a splash or spill potential, employees should wear chemically resistant clothing, boots, apron, gloves, and eye/face

protection.

Additional Protective

Measures

: Safety shoes.

General Hygiene

Considerations

Handle in accordance with good industrial hygiene and safety practice.

Wash hands before breaks and at the end of workday.

Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide

appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Silica, amorphous	20 mppcf	PEL:	Total dust.	OSHA
	20 mppcf	PEL:	Total dust.	Z3
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Ethylene glycol	100	Ceiling Limit Value:	Aerosol.	ACGIH
	mg/m3			

9. PHYSICAL AND CHEMICAL PROPERTIES

Form : liquid Evaporation rate : Negligible Appearance : Viscous Specific Gravity: : > 1

Color : WHITE Bulk density : Not applicable
Odor : mild Vapor pressure : <0.04 mm Hg @ 20



MATERIAL SAFETY DATA SHEET

WB-10472-A WHITE SATURANT

Version Number 1.2 Page 4 of 7
Revision Date 02/10/2004 Print Date 11/13/2011

°C

Melting point/range : No data available Vapour density : Heavier than air. Boiling Point: : Not established pH : No data available

Water solubility : slightly soluble

10. STABILITY AND REACTIVITY

Stability : Stable.

Hazardous Polymerization : Will not occur.

Conditions to avoid : Heating the product above 212 °F (100 °C) in the presence of air may

result in the formation of aldehydes. Product reacts exothermically

with isocyanates.

Incompatible Materials : strong acids and strong bases

Hazardous decomposition

products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen

(NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
107-21-1	Ethylene glycol	Systemic effects	Eyes, Skin, Respiratory system, central nervous system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
107-21-1	Ethylene glycol	Oral LD50	4,700 mg/kg	rat
		Dermal LD50	9530 ul/kg	rabbit

Additional Health Hazard Information:

Ethylene glycol 107-21-1 The metabolites may cause reproductive as well as developmental toxicity or birth defects.

12. ECOLOGICAL INFORMATION

Persistence and degradability : No data available

Environmental Toxicity : No data available



MATERIAL SAFETY DATA SHEET

WB-10472-A WHITE SATURANT

 Version Number 1.2
 Page 5 of 7

 Revision Date 02/10/2004
 Print Date 11/13/2011

Bioaccumulation Potential : Does not bioaccumulate.

Additional advice : No data available

13. DISPOSAL CONSIDERATIONS

Product : Where possible recycling is preferred to disposal or incineration. The

generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste material

has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial

and local regulations.

14. TRANSPORT INFORMATION

U.S. DOT Classification : Refer to specific regulation.

ICAO/IATA (air) : Refer to specific regulation.

IMO / IMDG (maritime) : Refer to specific regulation.

15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on or exempt from the TSCA

Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	% in Product	RQ for component	RQ for
				Mixture/Product
Ammonium hydroxide ((NH4)(OH))	1336-21-6	0.6685	1,000 lbs	149,589 LB

California Proposition : This product does not contain a substance listed by California Prop 65.

65

SARA Title III Section 302 Extremely Hazardous Substance



MATERIAL SAFETY DATA SHEET

WB-10472-A WHITE SATURANT

 Version Number 1.2
 Page 6 of 7

 Revision Date 02/10/2004
 Print Date 11/13/2011

Not applicable

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
ETHYLENE GLYCOL	107-21-1	2.91

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
Ethylene glycol	107-21-1	2.91	114

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

Ī	CAS-No.
Ī	7631-86-9
ſ	107-21-1

DSL : All components of this product are on the Canadian Domestic

Substances List (DSL) or are exempt.

National Inventories:

Australia AICS : Not determined

China IECS : Not determined

Europe EINECS : Not determined

Japan ENCS : Not determined

Korea KECI : Not determined

Philippines PICCS : Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.



POLYONE CORPORATION		
MATERIAL SAFETY DATA SHEET		
WB-10472-A WHITE SATURANT		
Version Number 1.2 Revision Date 02/10/2004	Print Date	Page 7 of 7 11/13/2011
Revision Date 02/10/2004	Fillit Date	11/13/2011