MATERIAL SAFETY DATA SHEET **STAN-TONE HCC-27612 YELLOW**

Version Number 1.2 Revision Date 03/15/2005

Page 1 of 8 Print Date 11/17/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone:Emergency telephone:number		Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	STAN-TONE HCC-27612 YELLOW
Product code	:	FO20000967
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Lead sulfate	7446-14-2	0.1 - 1
Lead chromate	7758-97-6	5 - 10
Chrome yellow (Lead chromate pigment)	1344-37-2	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion		
Acute exposure			
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.		
Ingestion	: May be harmful if swallowed.		
Eyes	: May cause eye/skin irritation.		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		

PolyOne

MATERIAL SAFETY DATA SHEET **STAN-TONE HCC-27612 YELLOW**

Version Number 1.2 Revision Date 03/15/2005 Page 2 of 8 Print Date 11/17/2011

Medical Conditions : None known. Aggravated by Exposure:				
	4. FIRST AID MEASURES			
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.			
Ingestion	: Do not induce vomiting without medical advice. Seek medical attention if necessary.			
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.			
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.			
	5. FIRE-FIGHTING MEASURES			
Flash point	: No data available			
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 No data available No data available Not applicable Carbon dioxide blanket, water spray, dry powder, foam. 			
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. 			
	6. ACCIDENTAL RELEASE MEASURES			
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.			
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.			
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.			
	7. HANDLING AND STORAGE			
Handling	: Heat only in areas with appropriate exhaust ventilation. Prolonged			

MATERIAL SAFETY DATA SHEET STAN-TONE HCC-27612 YELLOW

Version Number 1.2 Revision Date 03/15/2005 Page 3 of 8 Print Date 11/17/2011

heating may result in product degradation. Keep containers dry and tightly closed to avoid moisture absorption Storage : and contamination. Store in a cool dry place. 8. EXPOSURE CONTROLS / PERSONAL PROTECTION Respiratory protection : Under normal handling conditions a respirator may not be required. Eye/Face Protection Safety glasses with side-shields. : Hand protection Protective gloves. : Skin and body protection : Long sleeved clothing. Additional Protective Safety shoes. : Measures General Hygiene Handle in accordance with good industrial hygiene and safety practice. : Considerations Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s)

PolyOne

MATERIAL SAFETY DATA SHEET **STAN-TONE HCC-27612 YELLOW**

Version Number 1.2 Revision Date 03/15/2005 Page 4 of 8 Print Date 11/17/2011

Components	Value	Exposure time	Exposure type	List:
Chrome yellow (Lead	0.05	Time Weighted Average		OSHA
chromate pigment)	mg/m3	(TWA):		
	0.03	OSHA Action level:		OSHA
	mg/m3			
	0.01	Time Weighted Average	as Cr	ACGIH
	mg/m3	(TWA):		
	0.05	Time Weighted Average	as Pb	ACGIH
	mg/m3	(TWA):		
	1 mg/m3	PEL:	as Cr	OSHA Z1
Lead chromate	0.05	Time Weighted Average	Dust. as Pb	OSHA
	mg/m3	(TWA):		
	0.03	OSHA Action level:	Dust. as Pb	OSHA
	mg/m3			
	0.012	Time Weighted Average	as Cr	ACGIH
	mg/m3	(TWA):		
	0.05	Time Weighted Average	as Pb	ACGIH
	mg/m3	(TWA):		
	0.1 mg/m3	Ceiling Limit Value:		OSHA Z2
	1 mg/m3	PEL:	as Cr	OSHA Z1
Lead sulfate	0.05	Time Weighted Average	as Pb	OSHA
	mg/m3	(TWA):		
	0.03	OSHA Action level:	as Pb	OSHA
	mg/m3			
	0.05	Time Weighted Average	as Pb	ACGIH
	mg/m3	(TWA):		

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odor Melting point/range Boiling Point: Water solubility liquid
liquid, Viscous liquid dispersion
YELLOW
Very faint
Not applicable
Not applicable
Immiscible Evaporation rate Specific Gravity:

Bulk density

pН

Vapor pressure

Vapour density

: Not established

: Not determined

: Not applicable

: Not determined

: Heavier than air.

: Not determined

10. STABILITY AND REACTIVITY

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen

MATERIAL SAFETY DATA SHEET **STAN-TONE HCC-27612 YELLOW**

Version Number 1.2 Revision Date 03/15/2005

Page 5 of 8 Print Date 11/17/2011

products

(NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7446-14-2	Lead sulfate	Corrosive	Skin.
7758-97-6	Lead chromate	Systemic effects	central nervous system (CNS), reproductive system.
1344-37-2	Chrome yellow (Lead chromate pigment)	Systemic effects	central nervous system (CNS), reproductive system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
7758-97-6	Lead chromate	Oral LD50	> 12 gm/kg	mouse

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
7446-14-2	Lead sulfate	no	2A	no
7758-97-6	Lead chromate	no	no	1
1344-37-2	Chrome yellow (Lead	no	1	no
	chromate pigment)			

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Lead sulfate 7446-14-2 Systemic effects include neurotoxic, teratogenic, fetotoxic and reproductive with abdominal pain, anemia, pallor, decreased hand grip strength with characteristic "wrist drop".

Additional Health Hazard Information:

Lead chromate 7758-97-6 Systemic effects include neurotoxic, teratogenic, fetotoxic and reproductive with abdominal pain, anemia, pallor, decreased hand grip strength with characteristic "wrist drop".

PolyOne.

MATERIAL SAFETY DATA SHEET **STAN-TONE HCC-27612 YELLOW**

Version Number 1.2 Revision Date 03/15/2005 Page 6 of 8 Print Date 11/17/2011

Additional Health Hazard Information:

Chrome yellow (Lead chromate pigment) 1344-37-2 Systemic effects include neurotoxic, teratogenic, fetotoxic and reproductive with abdominal pain, anemia, pallor, decreased hand grip strength with characteristic "wrist drop".

12. ECOLOGICAL INFORMATION		
: Not readily biodegradable.		
: Environmental toxicity has not been established for this mixture as a whole.		
: No data available		
: No data available		
13. DISPOSAL CONSIDERATIONS		
: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.		
: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.		
14. TRANSPORT INFORMATION		
: Refer to specific regulation.		
: Refer to specific regulation.		
: Refer to specific regulation.		
15. REGULATORY INFORMATION		
: Classified as hazardous based on components.		
TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.		
Substances (40 CFR 302)		
AS-No. RQ for component RQ for		

PolyOne.

Page 7 of 8

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET STAN-TONE HCC-27612 YELLOW

Version Number 1.2

Rev

ision Date 03/15/2005			Prin	t Date 11/1//2011
				_
Lead sulfate 7446-14	-2 010 lbs	2,000 LB		
	WARNING! This proc			
	California to cause can			
	chemical known to the		to cause bi	rth defects or
	other reproductive harr	n.		
SARA Title III Section 302 Extremel	y Hazardous Substance			
Not applicable				
SARA Title III Section 313 Toxic Ch	omiaala			
SARA The III Section 515 Toxic Ch	ennears.			
Chemical Name		CAS-No.	Weight	0/.
CHROMIUM VI COMPOUN	JDSLEAD	1344-37-2	41.39	/0
COMPOUNDS, INORGANI		13++-37-2	+1.37	
COMPOUNDS				
CHROMIUM VI COMPOUN		7758-97-6	9.49	
COMPOUNDS, INORGANI		1150-71-0	7.47	
COMPOUNDS	CLEIND			
LEAD COMPOUNDS, INOI	RGANIC	7446-14-2	0.49	
		,	0.17]
Canadian Regulations:				
National Pollutant Release Inv	entory (NPRI)			
Chemical Name	, , ,	CAS-No.	Weight %	NPRI ID#
Chrome yellow (Lead chromate	pigment)		41.39	235
Chrome yellow (Lead chromate			41.39	236
Lead chromate		7758-97-6	9.49	235
Lead chromate			9.49	236
Lead sulfate			0.49	236
WHMIS Classification :	D2A			
WHMIS Ingredient Disclosure	e List			
CAS-No.				
1344-37-2				
7758-97-6				
DSL :	All components of this	product are on the	Canadian	Domestic
	Substances List (DSL)	or are exempt.		
National Inventories:				
Australia AICS :	Listed			
	7/8			
	110			

PolyOne

MATERIAL SAFETY DATA SHEET **STAN-TONE HCC-27612 YELLOW**

Version Number 1.2 Revision Date 03/15/2005 Page 8 of 8 Print Date 11/17/2011

China IECS	: Listed
Europe EINECS	: Listed
Japan ENCS	: Not determined
Korea KECI	: Listed
Philippines PICCS	: Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.