## MATERIAL SAFETY DATA SHEET DM433GR GREEN

Version Number 1.0 Revision Date 03/21/2007

Page 1 of 6 Print Date 11/27/2011

## 1. PRODUCT AND COMPANY IDENTIFICATION

### POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone number	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	DM433GR GREEN
Product code	:	FO20001032
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

## 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Bisphenol A - Epichlorohydrin polymer	25068-38-6	1 - 5
Calcium oxide	1305-78-8	1 - 5

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

**POLYONE CORPORATION** 

PolyOne.

# MATERIAL SAFETY DATA SHEET **DM433GR GREEN**

Version Number 1.0 Revision Date 03/21/2007 Page 2 of 6 Print Date 11/27/2011

Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.		
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.		
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If exirct irritation persists, seek medical attention.		
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.		
	5. FIRE-FIGHTING MEASURES		
Flash point	: no data available		
Elemental Limite			
Flammable Limits Upper explosion limit	: no data available		
Lower explosion limit	: no data available		
Autoignition temperature	: Not applicable		
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, Dry powder, Foam.		
Suitable extinguishing media	. Carbon dioxide branket, water spray, Dry powder, Foam.		
Special Fire Fighting	: Fullface self-contained breathing apparatus (SCBA) used in positive		
Procedures	pressure mode should be worn to prevent inhalation of airborne		
	contaminants.		
Unusual Fire/Explosion	: May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under		
Hazards fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide			
of nitrogen (NOx), other hazardous materials, and smoke are all			
	possible.		
	6. ACCIDENTAL RELEASE MEASURES		
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.		
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.		
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.		
	7. HANDLING AND STORAGE		
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing		



## MATERIAL SAFETY DATA SHEET DM433GR GREEN

sion Number 1.0 rision Date 03/21/2007			Print [	Page 3 Date 11/27/2	
	Р	ume condensates may contain eriodically clean hoods, ducts ccumulation of these material	s, and other surfaces to m		
Storage		Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.			
8. E	XPOSURE	CONTROLS / PERSONAL	PROTECTION		
Respiratory protection	: N	o personal respiratory protec	tive equipment normally	required.	
Eye/Face Protection	: S	afety glasses with side-shield	s		
Hand protection	: P	rotective gloves			
Skin and body protection	: L	ong sleeved clothing			
Additional Protective Measures	: S	afety shoes			
General Hygiene Considerations		landle in accordance with goo Vash hands before breaks and		safety practice.	
Engineering measures		leat only in areas with approp ppropriate exhaust ventilation		Provide	
Exposure limit(s)					
Components	Value	Exposure time	Exposure type	List:	
Calcium oxide	2 mg/m3	Time Weighted Average (TWA):	Dust.	ACGIH	
	5 mg/m3	PEL:	Dust.	OSHA Z1	
	2 mg/m3	Time Weighted Average (TWA):		MX OEL	
	9. PHYSIC	CAL AND CHEMICAL PR	OPERTIES		
Form Appearance Color	: liqui : Visc : GRE	ous, liquid Speci	fic Gravity: : Not	t established t determined t applicable	

Color Odour Melting point/range Boiling Point: Water solubility

: Very faint : not applicable : not applicable : Immiscible

# Bulk density Vapour pressure Vapour density pН

Not applicable : : Not determined : Not determined : Not applicable

## **10. STABILITY AND REACTIVITY**

Stability

: Stable.

# MATERIAL SAFETY DATA SHEET **DM433GR GREEN**

Version Number 1.0 Page 4 of 6 Print Date 11/27/2011 Revision Date 03/21/2007 Hazardous Polymerization : Will not occur. Conditions to avoid Keep away from oxidizing agents and open flame. To avoid thermal : decomposition, do not overheat. Incompatible Materials : Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing. Hazardous decomposition : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen products (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F). **11. TOXICOLOGICAL INFORMATION** 

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
25068-38-6	Bisphenol A -	Irritant	Skin.
	Epichlorohydrin polymer		
		sensitizer	Skin.
1305-78-8	Calcium oxide	Irritant	Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
		Corrosive	Skin.

### LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
25068-38-6	Bisphenol A -	Oral LD50	11,400 mg/kg	rat
	Epichlorohydrin polymer	Dermal LD50	> 6,000 mg/kg	rabbit

## **12. ECOLOGICAL INFORMATION**

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	:	no data available
Additional advice	:	no data available

## **13. DISPOSAL CONSIDERATIONS**



# MATERIAL SAFETY DATA SHEET **DM433GR GREEN**

Version Number 1.0 Revision Date 03/21/2007	Page 5 of 6 Print Date 11/27/2011
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	
	: Refer to specific regulation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	s Substances (40 CFR 302)
not applicable	
California Proposition 65	: Not applicable
SARA Title III Section 302 E	xtremely Hazardous Substance
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulation
SARA Title III Section 313 T	oxic Chemicals:
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulation

PolyOne

# MATERIAL SAFETY DATA SHEET **DM433GR GREEN**

POLYONE CORPORATION

Version Number 1.0 Revision Date 03/21/2007				Ρ	rint Date	Page 6 of 6 11/27/2011
Canadian Regulations:						
National Pollutant Releas	se I	nventory (NPRI)				
Chemical Name		• • •	CAS-No.	Weight %	NPRI	ID#
Phthalocyanine green			1328-53-6	0.10 - 1.00	71	
WHMIS Classification : D2B WHMIS Ingredient Disclosure List CAS-No. 1305-78-8 DSL : All components of this product are on the Canadian Domestic						
National Inventories:		Substances List	(DSL) or are exe	mpt.		
Australia AICS	:	Not determined				
China IECS	:	Not determined				
Europe EINECS	:	Not determined				
Japan ENCS	:	Not determined				
Korea KECI	:	Not determined				
Philippines PICCS	:	Not determined				
		16. OTHER IN	NFORMATION			

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.