

POLYONE CORPORATION**MATERIAL SAFETY DATA SHEET****CASM14267701 Higher Viscosity**Version Number 1.2
Revision Date 05/17/2007Page 1 of 7
Print Date 11/28/2011**1. PRODUCT AND COMPANY IDENTIFICATION****POLYONE CORPORATION**
8155 Cobb Center Drive, Kennesaw, GA 30152Telephone : Product Stewardship (770) 590-3500 x.3563
Emergency telephone : **CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).**Product name : CASM14267701 Higher Viscosity
Product code : FO20001328
Chemical Name : Mixture
CAS-No. : Mixture
Product Use : Industrial Applications**2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS**

Components	CAS-No.	Weight %
Antimony trioxide	1309-64-4	0.1 - 1
Titanium dioxide	13463-67-7	0.1 - 1

3. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS**Routes of Exposure:** : Inhalation, Skin contact, Ingestion**Acute exposure**Inhalation : Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion : May be harmful if swallowed.
Eyes : May cause eye/skin irritation.
Skin : Experience shows no unusual dermatitis hazard from routine handling.**Chronic exposure** : Refer to Section 11 for Toxicological Information.**Medical Conditions** : None known.**Aggravated by Exposure:**

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

CASM14267701 Higher Viscosity

Version Number 1.2
Revision Date 05/17/2007

Page 2 of 7
Print Date 11/28/2011

4. FIRST AID MEASURES

- Inhalation : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
- Ingestion : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
- Eyes : Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
- Skin : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

5. FIRE-FIGHTING MEASURES

- Flash point : No data available
- Flammable Limits
Upper explosion limit : No data available
Lower explosion limit : No data available
- Autoignition temperature : Not applicable
- Suitable extinguishing media : Carbon dioxide blanket, Water spray, Dry powder, Foam.
- Special Fire Fighting Procedures : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
- Unusual Fire/Explosion Hazards : May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), other hazardous materials, and smoke are all possible.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
- Environmental precautions : The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
- Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

7. HANDLING AND STORAGE

- Handling : Heat only in areas with appropriate exhaust ventilation. Processing

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

CASM14267701 Higher Viscosity

Version Number 1.2
Revision Date 05/17/2007

Page 3 of 7
Print Date 11/28/2011

fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.

Storage : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- Respiratory protection : No personal respiratory protective equipment normally required.
- Eye/Face Protection : Safety glasses with side-shields
- Hand protection : Protective gloves
- Skin and body protection : Long sleeved clothing
- Additional Protective Measures : Safety shoes
- General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
- Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Antimony trioxide	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form : liquid
- Evaporation rate : Not established
- Appearance : Viscous, liquid
- Specific Gravity : Not determined
- Color : GREY
- Bulk density : Not applicable
- Odour : Very faint
- Vapour pressure : Not determined
- Melting point/range : Not applicable
- Vapour density : Not determined

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

CASM14267701 Higher Viscosity

Version Number 1.2
Revision Date 05/17/2007

Page 5 of 7
Print Date 11/28/2011

- 1 - The component is carcinogenic to humans.
- 2A - The component is probably carcinogenic to humans.
- 2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

- 1 - The component is known to be a human carcinogen.
- 2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Antimony trioxide 1309-64-4 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

12. ECOLOGICAL INFORMATION

- Persistence and degradability : Not readily biodegradable.
- Environmental Toxicity : Environmental toxicity has not been established for this mixture as a whole.
- Bioaccumulation Potential : No data available
- Additional advice : No data available

13. DISPOSAL CONSIDERATIONS

- Product : Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
- Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

14. TRANSPORT INFORMATION

- U.S. DOT Classification : Refer to specific regulation.
- ICAO/IATA (air) : Refer to specific regulation.
- IMO / IMDG (maritime) : Refer to specific regulation.

15. REGULATORY INFORMATION

US Regulations:

- OSHA Status : Classified as hazardous based on components.

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

CASM14267701 Higher Viscosity

Version Number 1.2
Revision Date 05/17/2007

Page 6 of 7
Print Date 11/28/2011

TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

California Proposition 65 : WARNING! This product contains a chemical known to the State of California to cause cancer.

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
Antimony trioxide	1309-64-4	0.10 - 1.00	17

WHMIS Classification : D2A

DSL : DSL status has not been determined. Quantity use in Canada may be restricted by regulations.

National Inventories:

Australia AICS : Not determined

China IECS : Not determined

Europe EINECS : Not determined

Japan ENCS : Not determined

Korea KECI : Not determined

Philippines PICCS : Not determined



POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

CASM14267701 Higher Viscosity

Version Number 1.2
Revision Date 05/17/2007

Page 7 of 7
Print Date 11/28/2011

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.