# MATERIAL SAFETY DATA SHEET WB-10476-A WHITE SATURANT

Version Number 1.1 Revision Date 02/10/2004 Page 1 of 7 Print Date 11/13/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	WB-10476-A WHITE SATURANT
Product code	:	FO20001380
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous	7631-86-9	1 - 5
Ethylene glycol	107-21-1	1 - 5
Titanium dioxide	13463-67-7	10 - 30

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. In addition, heating or processing this material may result in product degradation or byproduct formation creating additional hazards. See Sections 8 and 11 for additional details.

### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Skin contact, Inhalation, Ingestion	
Acute exposure		
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.	
Ingestion	: No known effects.	
Eyes	: Vapour during processing may be irritating to the respiratory tract and to the eyes.	
Skin	: May cause eye or skin irritation with susceptible persons.	
Chronic exposure	: Refer to Section 11 for Toxicological Information.	

PolyOne.

# MATERIAL SAFETY DATA SHEET WB-10476-A WHITE SATURANT

Version Number 1.1 Revision Date 02/10/2004 Page 2 of 7 Print Date 11/13/2011

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of vapors or fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Obtain medical attention. Never give anything by mouth to an unconscious person.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Greater than 400 °F (204.4 °C)
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>No data available</li> <li>No data available</li> <li>No data available</li> <li>carbon dioxide (CO2), water, foam, dry chemical.</li> </ul>
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Cool closed containers exposed to fire with water spray Do not allow run-off from fire fighting to enter drains or water courses
Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Ensure response personnel are properly protected (see section 8 for respiratory or other protection guidelines.) Use caution as floors may be slippery.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Sweep up and shovel into suitable containers for disposal.
	7. HANDLING AND STORAGE



# MATERIAL SAFETY DATA SHEET WB-10476-A WHITE SATURANT

ion Number 1.1 sion Date 02/10/2004			Print Da	Page 3 ate 11/13/2
Handling	Pi	se only in area provided with a rolonged heating may result in ettle during storage. Careful me necessary before use.	product degradation. Ma	aterial may
Storage	սլ	ontainers which are opened mu pright to prevent leakage. Keep eezing and temperature extrem	p in a dry, cool place. Ke	
8. I	EXPOSURE	CONTROLS / PERSONAL I	PROTECTION	
Respiratory protection	ar	respirator is normally not requ reas of good general ventilation rocessing equipment during rou	and adequate local exha	
Eye/Face Protection		afety glasses with side-shields. perations that present a splash p		nield during
Hand protection	: Ir	npervious gloves such as rubbe	er or PVC	
Skin and body protection	W W	ong sleeved shirts and long par /here operations present a splas ear chemically resistant clothir rotection.	h or spill potential, empl	oyees shoul
Additional Protective Measures	: Sa	afety shoes.		
General Hygiene Considerations	Н	Ash hands before breaks and in andle in accordance with good ractices.		
Engineering measures	al	dequate ventilation and/or appr so be necessary to minimize e apors.		
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Silica, amorphous	20 mppcf	PEL:	Total dust.	OSHA
	20 mppcf	PEL:	Total dust.	Z3
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Ethylene glycol	100 mg/m3	Ceiling Limit Value:	Aerosol.	ACGIH
	9. PHYSIC	CAL AND CHEMICAL PRO	PERTIES	

## MATERIAL SAFETY DATA SHEET WB-10476-A WHITE SATURANT

Version Number 1.1 Revision Date 02/10/2004 Page 4 of 7 Print Date *11/13/2011* 

Form	: liquid	Evaporation rate	: Slower than Butyl Acetate
Appearance	: liquid	Specific Gravity:	: Not determined
Color	: WHITE	Bulk density	: Not applicable
Odor	: Slight	Vapor pressure	: Not established
Melting point/range	: Not applicable	Vapour density	: Heavier than air.
Boiling Point:	: No data available	pH	: Not determined
Water solubility	: Completely miscible	-	
	10. STABILITY ANI	D REACTIVITY	
Stability	: Stable.		
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Extremes of tempe	rature and direct sunlight.	Keep from freezing.
Incompatible Materials	: Acids, metal salts,	and solvents	
Hazardous decomposition	· Carbon dioxide (C	O2), carbon monoxide (CC	)) ovides of nitrogen

### 11. TOXICOLOGICAL INFORMATION

(NOx), other hazardous materials, and smoke are all possible.

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

products

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
107-21-1	Ethylene glycol	Systemic effects	Eyes, Skin, Respiratory system,
			central nervous system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
107-21-1	Ethylene glycol	Oral LD50	4,700 mg/kg	rat
		Dermal LD50	9530 ul/kg	rabbit

### Additional Health Hazard Information:

Ethylene glycol 107-21-1 The metabolites may cause reproductive as well as developmental toxicity or birth defects.

#### **12. ECOLOGICAL INFORMATION**

Persistence and degradability

: No data available

PolyOne.

# MATERIAL SAFETY DATA SHEET WB-10476-A WHITE SATURANT

Version Number 1.1 Revision Date 02/10/2004 Page 5 of 7 Print Date 11/13/2011

A 11'	NT 1			
Additional advice	: No da	ata available		
	13. DIS	POSAL CONSIDI	ERATIONS	
Product	gener classi	ator of waste mater fication, transporta	g is preferred to dispo- rial has the responsibil tion and disposal in ac provincial and local re	cordance with
Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				
	14. TR	ANSPORT INFO	RMATION	
U.S. DOT Classification	: Refer	to specific regulation	ion.	
ICAO/IATA (air)	: Refer	to specific regulation	ion.	
IMO / IMDG (maritime)	: Refer	to specific regulation	ion.	
	15. REG	ULATORY INFO	ORMATION	
US Regulations:				
OSHA Status	: Class	ified as hazardous	based on components.	
TSCA Status	: All c Inven		product are listed on or	exempt from the TSCA
US. EPA CERCLA Hazard	ous Substances	(40 CFR 302)		
Chemical Name	CAS-No.	% in Product	RQ for component	RQ for Mixture/Product
Ammonium hydroxide ((NH4)(OH))	1336-21-6	0.6405	1,000 lbs	156,128 LB

Po<u>lvOne</u>

# MATERIAL SAFETY DATA SHEET WB-10476-A WHITE SATURANT

Version Number 1.1 Revision Date 02/10/2004 Page 6 of 7 Print Date 11/13/2011

SARA Title III Section 302 Extremely Hazardous Substance

Not applicable

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
ETHYLENE GLYCOL	107-21-1	2.78

Canadian Regulations:

National Pollutant Release Inventory (NPRI)			
Chemical Name	CAS-No.	Weight %	NPRI ID#
Ethylene glycol	107-21-1	2.78	114

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

ĺ	CAS-No.
	7631-86-9
	107-21-1

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	: Not determined
China IECS	: Not determined
Europe EINECS	: Not determined
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined

:

### **16. OTHER INFORMATION**



# MATERIAL SAFETY DATA SHEET WB-10476-A WHITE SATURANT

Version Number 1.1 Revision Date 02/10/2004 Page 7 of 7 Print Date *11/13/2011* 

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.