

MATERIAL SAFETY DATA SHEET

PX-G-026 HOT DIP PLASTISOL

Version Number 1.0 Page 1 of 7
Revision Date 08/22/2002 Print Date 11/5/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION

2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY : Product Stewardship, (314) 771-1800

TELEPHONE

Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure

number or accident).

Product name : PX-G-026 HOT DIP PLASTISOL

Product code : FO20001461 Chemical Name : Mixture CAS-No. : Mixture

Product Use : Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Di(2-ethylhexyl)phthalate	117-81-7	0.1 - 1
Petroleum distillates, hydrotreated light	64742-53-6	1 - 5
naphthenic		

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Inhalation, Skin contact, Ingestion

Acute exposure

Inhalation : Inhalation of airborne droplets may cause irritation of the respiratory

tract.

Ingestion : May be harmful if swallowed. Eyes : May cause eye/skin irritation.

Skin : Experience shows no unusual dermatitis hazard from routine handling.

Chronic exposure : Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET

PX-G-026 HOT DIP PLASTISOL

 Version Number 1.0
 Page 2 of 7

 Revision Date 08/22/2002
 Print Date 11/5/2011

Medical Conditions Aggravated by Exposure:

: None known.

4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of fumes from

overheating or combustion. When symptoms persist, or in all cases of

doubt, seek medical advice.

Ingestion : Do not induce vomiting without medical advice. When symptoms

persist, or in all cases of doubt, seek medical advice.

Eyes : Rinse immediately with plenty of water for at least 15 minutes. If eye

irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists seek

medical attention.

5. FIRE-FIGHTING MEASURES

Flash point : No data available.

Flammable Limits

Upper explosion limit : No data available.

Lower explosion limit : No data available.

Autoignition temperature : Not applicable.

Suitable extinguishing media : Carbon dioxide blanket, dry powder, foam, Water spray.

Special Fire Fighting

Procedures

Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne

contaminants.

Unusual Fire/Explosion

Hazards

May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under

fire conditions.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear appropriate personal protection during cleanup, such as

impervious gloves, boots and coveralls.

Environmental precautions : Should not be released into the environment. The product should not

be allowed to enter drains, water courses or the soil.

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder,

universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper

disposal methods.

7. HANDLING AND STORAGE

Handling : Heat only in areas with appropriate exhaust ventilation. Processing



MATERIAL SAFETY DATA SHEET

PX-G-026 HOT DIP PLASTISOL

 Version Number 1.0
 Page 3 of 7

 Revision Date 08/22/2002
 Print Date 11/5/2011

fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize

accumulation of these materials.

Storage : Keep containers dry and tightly closed to avoid moisture absorption

and contamination. Store in a cool dry place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection : Under normal handling conditions a respirator may not be required.

Eye/Face Protection : Safety glasses with side-shields.

Hand protection : Protective gloves.

Skin and body protection : Long sleeved clothing.

Additional Protective

Measures

: Safety shoes.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

Wash hands before breaks and at the end of workday.

Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide

appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Di(2-ethylhexyl)phthal	5 mg/m3	Time Weighted Average	Vapor.	ACGIH
ate		(TWA):		
Di(2-ethylhexyl)phthal	5 mg/m3	PEL:	Vapor.	OSHA Z1
ate				
Petroleum distillates,	500 ppm	PEL:	Vapor.	OSHA Z1
hydrotreated light	2,000			
naphthenic	mg/m3			

9. PHYSICAL AND CHEMICAL PROPERTIES

Not established Form : Liquid Evaporation rate Viscous, Liquid Specific Gravity Not determined Appearance NOT APPLICABLE Color Bulk density Not applicable. Very faint Vapor pressure Not determined Odor Melting point/range : Not applicable Vapor density Not determined **Boiling Point:** Not applicable рH : Not applicable.

Water solubility : Immiscible

10. STABILITY AND REACTIVITY



MATERIAL SAFETY DATA SHEET

PX-G-026 HOT DIP PLASTISOL

 Version Number 1.0
 Page 4 of 7

 Revision Date 08/22/2002
 Print Date 11/5/2011

Stability : Stable.

Hazardous Polymerization : Will not occur.

Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal

decomposition, do not overheat.

Incompatible Materials : Incompatible with strong acids and oxidizing agents. Avoid contact

with acetal homopolymers and acetal copolymers during processing.

Hazardous decomposition

products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and

smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 $^{\circ}$ C (350 $^{\circ}$ F), after 10 minutes at 204 $^{\circ}$ C (400 $^{\circ}$ F),

and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
117-81-7	Di(2-ethylhexyl)phthalate	Systemic effects	Eyes, Respiratory system,
			Liver, central nervous system,
			Skin, digestive system.
64742-53-6	Petroleum distillates,	Irritant	Eyes, Skin.
	hydrotreated light		
	naphthenic		

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
117-81-7	Di(2-ethylhexyl)phthalate	Oral LD50	30 gm/kg	rat
		Dermal LD50	25 gm/kg	rabbit

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
117-81-7	Di(2-ethylhexyl)phthalate	no	no	2

IARC Carcinogen Classifications:

- 1 The component is carcinogenic to humans.
- 2A The component is probably carcinogenic to humans.
- 2B The component is possibly carcinogenic to humans.



MATERIAL SAFETY DATA SHEET

PX-G-026 HOT DIP PLASTISOL

 Version Number 1.0
 Page 5 of 7

 Revision Date 08/22/2002
 Print Date 11/5/2011

NTP Carcinogen Classifications:

- 1 The component is known to be a human carcinogen.
- 2 The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Di(2-ethylhexyl)phthalate 117-81-7 There is sufficient evidence for the carcinogenicity of di (2-ethylhexyl) phthalate in experimental animals. Administered in the feed this chemical caused an increase incidence of liver cancer in male and female rats and mice. The relevance of this finding to humans is uncertain.

12. ECOLOGICAL INFORMATION

Persistence and degradability : Not readily biodegradable.

Environmental Toxicity : Environmental toxicity has not been established for this mixture as a

whole.

Bioaccumulation Potential : No data available.

Additional advice : No data available.

13. DISPOSAL CONSIDERATIONS

Product : Where possible, recycling is preferred to disposal or incineration. The

generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste material

has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial

and local regulations.

14. TRANSPORT INFORMATION

U.S. DOT / CA TDG

Classification

Not regulated for transportation.

ICAO/IATA : Not regulated for transportation.

IMO / IMDG : Not regulated for transportation.

15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.



MATERIAL SAFETY DATA SHEET

PX-G-026 HOT DIP PLASTISOL

 Version Number 1.0
 Page 6 of 7

 Revision Date 08/22/2002
 Print Date 11/5/2011

TSCA Status : All components of this product are listed on the TSCA inventory or are

exempt.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	% in Product	RQ for component	RQ for
			_	Mixture/Product
Di(2-ethylhexyl)ph	117-81-7	0.1733	100 lbs	57,703 LB
thalate				

California Proposition

65

: WARNING! This product contains a chemical known in the State of

California to cause cancer.

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
DI(2-ETHYLHEXYL)PHTHALATE	117-81-7	00.17
(DEHP)		

Canadian Regulations:

WHMIS Classification : D2A

DSL : Listed.

National Inventories:

Australia AICS : Not determined.

China IECS : Not determined.

Europe EINECS : Not determined.

Japan ENCS : Not determined.

Korea KECI : Listed.

Philippines PICCS : Not determined.

16. OTHER INFORMATION



MATERIAL SAFETY DATA SHEET

PX-G-026 HOT DIP PLASTISOL

ersion Number 1.0 Revision Date 08/22/2002	Page 7 of 7 Print Date 11/5/2011
The information provided in this Safety Data Sheet is correct to the best of belief at the date of its publication. The information given is designed only processing, storage, transportation, disposal and release and is not to be conspecification. The information relates only to the specific material designate material used in combination with any other materials or in any process, under the combination of the specific materials or in any process, under the combination of the specific materials or in any process, under the combination of the combination of the specific materials or in any process, under the combination of the combination of the specific materials or in any process, under the combination of	of our knowledge, information and y as a guidance for safe handling, use, onsidered a warranty or quality ated and may not be valid for such