# MATERIAL SAFETY DATA SHEET V495 ORANGE

Version Number 1.2 Revision Date 08/03/2009 Page 1 of 8 Print Date 1/8/2012

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone:Emergency telephone:	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	V495 ORANGE
Product code	:	FO20002025
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent		
Titanium dioxide	13463-67-7	0.1 - 1		
Lead chromate	7758-97-6	1 - 5		

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Particulates, like other inert materials can be mechanically irritating.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



# MATERIAL SAFETY DATA SHEET **V495 ORANGE**

Version Number 1.2 Revision Date 08/03/2009 Page 2 of 8 Print Date 1/8/2012

		4. FIRST AID MEASURES			
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.			
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.			
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.			
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.				
		5. FIRE-FIGHTING MEASURES			
Flash point	:	not applicable			
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures	::	not applicable not applicable Not relevant Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.			
Unusual Fire/Explosion Hazards	:	May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.			
	6. A	CCIDENTAL RELEASE MEASURES			
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.			
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.			
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.			
		7. HANDLING AND STORAGE			
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. Processing fume			



# MATERIAL SAFETY DATA SHEET **V495 ORANGE**

ersion Number 1.2 Revision Date 08/03/2009		Page 3 of 8 Print Date 1/8/2012
		condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXI	POSUI	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required. If dusty conditions occur wear appropriate respiratory protection.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

PolyOne

# MATERIAL SAFETY DATA SHEET **V495 ORANGE**

Version Number 1.2 Revision Date 08/03/2009 Page 4 of 8 Print Date 1/8/2012

Components	Value	Exposure time	Exposure type	List:
Lead chromate	0.012	Time Weighted Average	as Cr	ACGIH
	mg/m3	(TWA):		
	0.05	Time Weighted Average	as Pb	ACGIH
	mg/m3	(TWA):		
	0.005	Time Weighted Average		OSHA
	mg/m3	(TWA):		
	0.0025	OSHA Action level:		OSHA
	mg/m3			
	0.001	Recommended exposure	as Cr(VI)	NIOSH
	mg/m3	limit (REL):		
	0.1 mg/m3	Ceiling Limit Value:		OSHA Z2
	0.1 mg/m3	Ceiling Limit Value:	as CrO3	OSHA Z1A
	0.01	Time Weighted Average		MX OEL
	mg/m3	(TWA):		
	1 mg/m3	PEL:	as Cr	OSHA Z1
	1 mg/m3	Time Weighted Average (TWA):		OSHA Z1A
	0.05	Time Weighted Average		OSHA
	mg/m3	(TWA):		OSIIA
	0.03	OSHA Action level:		OSHA
	mg/m3	OSHA Action level.		OSIIA
	0.05	Time Weighted Average	as Pb	OSHA Z1A
	mg/m3	(TWA):	<i>as</i> 1 <i>b</i>	OSHA LIA
	0.15	Time Weighted Average	Dust and fume. as Pb	MX OEL
	mg/m3	(TWA):		
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility
- solid
  powder, granular
  ORANGE
  very faint
  Not determined
  not applicable
  insoluble
- Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH
- Not applicable
  Not determined
  Not determined
  not applicable
  not applicable
  not applicable

#### **10. STABILITY AND REACTIVITY**

Stability

: Stable

**POLYONE CORPORATION** 



# MATERIAL SAFETY DATA SHEET **V495 ORANGE**

Version Number 1.2 Revision Date 08/03/2009 Page 5 of 8 Print Date 1/8/2012

Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	To avoid thermal decomposition, do not overheat. Keep away from oxidizing agents and open flame.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

#### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
7758-97-6	Lead chromate	Systemic effects	central nervous system (CNS), reproductive system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
7758-97-6	Lead chromate	Oral LD50	> 12 gm/kg	mouse

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no
7758-97-6	Lead chromate	yes	1	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

PolyOne

### MATERIAL SAFETY DATA SHEET V495 ORANGE

Version Number 1.2 Revision Date 08/03/2009 Page 6 of 8 Print Date 1/8/2012

2 - The component is reasonably anticipated to be a human carcinogen.

<u>Additional Health Hazard Information:</u> Lead chromate 7758-97-6 Systemic effects include neurotoxic, teratogenic, fetotoxic and reproductive with abdominal pain, anemia, pallor, decreased hand grip strength with characteristic "wrist drop".

	12. ECOLOGICAL INFORMATION				
Persistence and degradability	: Not readily biodegradable.				
Environmental Toxicity	: Adverse ecological impact is not known or expected under normal use.				
Bioaccumulation Potential	: no data available				
Additional advice	: no data available				
	13. DISPOSAL CONSIDERATIONS				
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				
	14. TRANSPORT INFORMATION				
U.S. DOT Classification	: Not regulated for transportation.				
ICAO/IATA	: Not regulated for transportation.				
IMO / IMDG (maritime)	: Not regulated for transportation.				
	15. REGULATORY INFORMATION				
US Regulations:					
OSHA Status	: Classified as hazardous based on components.				
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.				
US. EPA CERCLA Hazardous	Substances (40 CFR 302)				
not applicable					
	6/8				

PolyOne.

# MATERIAL SAFETY DATA SHEET **V495 ORANGE**

435 ONANOL							
ersion Number 1.2 evision Date 08/03/2009					F	P Print Date	age 7 of 8 1/8/2012
California Proposition : 65	WARNING! TI California to cat chemical known other reproducti	use cance to the St	r., WARNI	NG! Th	nis produ	ict contains	s a
SARA Title III Section 302 Extrem	-						
Unless specific chemicals are ident	ified under this se	ction, this	s product is	Not Ap	plicable	under this	regulation
SARA Title III Section 313 Toxic Unless specific chemicals are ident		ction, this	s product is	Not Ap	plicable	under this	regulation
Chemical Name			CAS-No.			percent	•
CHROMIUM VI COMPOUND	SCHROMIUM		7758-97-6	j j	1.00 -		
COMPOUNDSLEAD COMPO	UNDSLEAD						
COMPOUNDS, INORGANIC							
Canadian Regulations: National Pollutant Release I	nventory (NPRI)						
Chemical Name		CAS-N	lo.	Weight		NPRI ID	#
Lead chromate		7758-9	7-6	1.00 - 5			
WHMIS Classification : WHMIS Ingredient Disclos CAS-No. 7758-97-6							
DSL :	All components Substances List				anadian	Domestic	
National Inventories:							
Australia AICS :	Not determined						
China IECS :	Not determined						
Europe EINECS :	Not determined						

P	bh	one.

# MATERIAL SAFETY DATA SHEET V495 ORANGE

Version Number 1.2 Revision Date 08/03/2009 Page 8 of 8 Print Date 1/8/2012

Japan ENCS : Not determined

Korea KECI : Not determined

Philippines PICCS : Not determined

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.