

#### MATERIAL SAFETY DATA SHEET

# **M2949B WHITE**

Version Number 1.0 Revision Date 10/10/2002 Page 1 of 6 Print Date 11/6/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	M2949B WHITE
Product code	:	FO20002120
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Quartz	14808-60-7	0.1 - 1
Petroleum distillates, hydrotreated light naphthenic	64742-53-6	5 - 10
Calcium carbonate	1317-65-3	30 - 60

# **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

MATERIAL SAFETY DATA SHEET





ion Number 1.0 sion Date 10/10/2002		Page 2 Print Date 11/6/2
Medical Conditions Aggravated by Exposure:	: None known.	
	4. FIRST AID MEASURES	
Inhalation	: Move to fresh air in case of accid overheating or combustion. Whe doubt, seek medical advice.	ental inhalation of fumes from en symptoms persist, or in all cases o
Ingestion	: Do not induce vomiting without r persist, or in all cases of doubt, se	
Eyes	: Rinse immediately with plenty of irritation persists, seek medical at	f water for at least 15 minutes. If ey ttention.
Skin	: Wash off with soap and plenty of medical attention.	water. If skin irritation persists see
	5. FIRE-FIGHTING MEASURE	CS
Flash point	: No data available.	
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>No data available.</li> <li>No data available.</li> <li>Not applicable.</li> <li>Carbon dioxide blanket, dry power</li> </ul>	der, foam, Water spray.
Special Fire Fighting Procedures	: Fullface self-contained breathing pressure mode should be worn to contaminants.	apparatus (SCBA) used in positive prevent inhalation of airborne
Unusual Fire/Explosion Hazards	: May emit Hydrogen Chloride (He fire conditions.	Cl) or Carbon Monoxide (CO) unde
	5. ACCIDENTAL RELEASE MEAS	URES
Personal precautions	: Wear appropriate personal protect impervious gloves, boots and cov	
Environmental precautions	: Should not be released into the er be allowed to enter drains, water	nvironment. The product should not courses or the soil.
Methods for cleaning up	universal binder, sawdust). Packa	erial (e.g. sand, silica gel, acid binder age all material in appropriate Section 13 of this MSDS for proper
	7. HANDLING AND STORAG	R

#### MATERIAL SAFETY DATA SHEET



#### M2949B WHITE Page 3 of 6 Version Number 1.0 Revision Date 10/10/2002 Print Date 11/6/2011 Handling : Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials. Storage Keep containers dry and tightly closed to avoid moisture absorption : and contamination. Store in a cool dry place. 8. EXPOSURE CONTROLS / PERSONAL PROTECTION : Under normal handling conditions a respirator may not be required. Respiratory protection Eye/Face Protection Safety glasses with side-shields. : Hand protection Protective gloves. : Skin and body protection Long sleeved clothing. : Additional Protective Safety shoes. ÷ Measures General Hygiene Handle in accordance with good industrial hygiene and safety practice. : Considerations Wash hands before breaks and at the end of workday. Heat only in areas with appropriate exhaust ventilation. Provide Engineering measures : appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate 10 mg/n		Time Weighted Average	Total dust.	ACGIH
		(TWA):		
Calcium carbonate	5 mg/m3	PEL:	Respirable dust.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Petroleum distillates,	500 ppm	PEL:	Vapor.	OSHA Z1
hydrotreated light	2,000			
naphthenic	mg/m3			
Quartz	0.05	Time Weighted Average	Respirable dust.	ACGIH
	mg/m3	(TWA):		
Quartz	0.1 mg/m3	PEL:	Respirable dust.	OSHA
	0.3 mg/m3	PEL:	Total dust.	OSHA

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odor Melting point/range : Liquid
: Viscous, Liquid
: WHITE
: Very faint
: Not applicable

Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density Not establishedNot determinedNot applicable.

- : Not determined
- : Not determined



#### MATERIAL SAFETY DATA SHEET

# M2949B WHITE

Version Number 1.0 Revision Date 10/10/2002		Page 4 of Print Date <i>11/6/201</i>
Boiling Point: Water solubility	: Not applicable p : Immiscible	pH : Not applicable.
	10. STABILITY AND REA	ACTIVITY
Stability	: Stable.	
Hazardous Polymerization	: Will not occur.	
Conditions to avoid	: Keep away from oxidizing decomposition, do not over	ng agents and open flame. To avoid thermal verheat.
Incompatible Materials		g acids and oxidizing agents. Avoid contact rs and acetal copolymers during processing.
Hazardous decomposition products	(NOx), hydrogen chloride smoke are all possible. Pr degradation. As a general	carbon monoxide (CO), oxides of nitrogen le (HCl), other hazardous materials, and Prolonged heating may result in product al rule of thumb, degradation begins to occur (350 °F), after 10 minutes at 204 °C (400 °F), 232 °C (450 °F).

#### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
14808-60-7	Quartz	Systemic effects	Eyes, Respiratory system.
64742-53-6	Petroleum distillates, hydrotreated light naphthenic	Irritant	Eyes, Skin.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
14808-60-7	Quartz	no	1	1

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.



#### MATERIAL SAFETY DATA SHEET

# **M2949B WHITE**

Version Number 1.0 Revision Date 10/10/2002 Page 5 of 6 Print Date 11/6/2011

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

## Additional Health Hazard Information:

**Quartz** 14808-60-7 This material in its free releasable form may cause respiratory tract irritation, and possibly silicosis which is a scarring of the lungs.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: No data available.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible, recycling is preferred to disposal or incineration. Th generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA	: Refer to specific regulation.
IMO / IMDG	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on the TSCA inventory or are exempt.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)

#### MATERIAL SAFETY DATA SHEET



# M2949B WHITE

Version Number 1.0		Page 6 of 6
Revision Date 10/10/2002		Print Date 11/6/2011
Not applicable		
California Proposition 65	:	WARNING! This product contains a chemical known in the State of California to cause cancer.
Canadian Regulations:		
WHMIS Classification	:	D2A
DSL	:	Listed.
National Inventories:		
Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Listed.
Philippines PICCS	:	Not determined.

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.