

MATERIAL SAFETY DATA SHEET

XCD40049 EXP. 10110PC WITH R706

Version Number 1.0 Revision Date 10/17/2002 Page 1 of 6 Print Date 11/6/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	XCD40049 EXP. 10110PC WITH R706
Product code	:	FO20002219
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous	7631-86-9	5 - 10
Titanium dioxide	13463-67-7	60 - 100

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET

XCD40049 EXP. 10110PC WITH R706

Medical Conditions	: None known.
Aggravated by Exposure:	. Ivole klowii.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases doubt, seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. Seek medical attention if necessary.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available.
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 No data available. No data available. Not applicable. Carbon dioxide blanket, dry powder, foam, Water spray. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binde universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Prolonged



MATERIAL SAFETY DATA SHEET

XCD40049 EXP. 10110PC WITH R706

Storage 8. E	: K	eating may result in prod	uct de	gradation.	
C				-	
8. E		eep containers dry and ti nd contamination. Store		re absorption	
	XPOSURE	CONTROLS / PERSO	NAL I	PROTECTION	
Respiratory protection	: U	nder normal handling co	nditio	ns a respirator may not	be required.
Eye/Face Protection	: S	afety glasses with side-sh	nields.		
Hand protection	: P	rotective gloves.			
Skin and body protection	: L	: Long sleeved clothing.			
Additional Protective Measures	: S	afety shoes.			
General Hygiene Considerations		andle in accordance with ash hands before breaks			safety practic
Engineering measures		eat only in areas with ap propriate exhaust ventile			. Provide
Exposure limit(s)					
Components	Value	Exposure time		Exposure type	List:
Silica, amorphous	20 mppcf	PEL:		Total dust.	OSHA
Silica, amorphous	20 mppcf	PEL:		Total dust.	Z3
Titanium dioxide	10 mg/m3	Time Weighted Avera (TWA):	nge	Dust.	ACGIH
Titanium dioxide	15 mg/m3	PEL:		Total dust.	OSHA Z
	9. PHYSIC	CAL AND CHEMICAL	, PRO	PERTIES	
Form	: Liqui	id F	Evapor	ation rate : No	ot established
Appearance					ot determined
		ersion			
Color	: WHI		Bulk de		ot applicable.
Odor					ot determined
Melting point/range			-	2	avier than air
Boiling Point:		applicable p iscible	Н	: No	ot determined
Water solubility	: Imm	Iscible			
	10. S	TABILITY AND REA	CTIV	ITY	
Stability	: S	table.			
Hazardous Polymerization	1 : W	/ill not occur.			



MATERIAL SAFETY DATA SHEET

XCD40049 EXP. 10110PC WITH R706

Version Number 1.0		Page 4 of 6
Revision Date 10/17/2002		Print Date 11/6/2011
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: No data available.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product Contaminated packaging	 Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA	: Refer to specific regulation.



MATERIAL SAFETY DATA SHEET

XCD40049 EXP. 10110PC WITH R706

Version Number 1.0 Revision Date 10/17/2002 Page 5 of 6 Print Date 11/6/2011

IMO / IMDG	:	Refer to specific regulation.
	15	5. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on the TSCA inventory or are exempt.
US. EPA CERCLA Hazardou	s Sub	stances (40 CFR 302)
Not applicable		
California Proposition 65	:	This product does not contain a substance listed by California Prop 65.
Canadian Regulations:		
WHMIS Classification	ı :	D2B
WHMIS Ingredient Dis	sclosu	ire List
CAS-No. 7631-86-9		
DSL	:	Listed.
National Inventories:		
Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Listed.
Japan ENCS	:	Not determined.
Korea KECI	:	Listed.
Philippines PICCS	:	Listed.
		16. OTHER INFORMATION



MATERIAL SAFETY DATA SHEET

XCD40049 EXP. 10110PC WITH R706

Version Number 1.0 Revision Date 10/17/2002 Page 6 of 6 Print Date 11/6/2011

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.