

#### MATERIAL SAFETY DATA SHEET

### DB3636 WHITE

Version Number 1.0 Revision Date 10/21/2002 Page 1 of 6 Print Date 11/6/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	DB3636 WHITE
Product code	:	FO20002269
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous	7631-86-9	1 - 5
Titanium dioxide	13463-67-7	1 - 5

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Skin contact, Ingestion		
Acute exposure			
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.		
Ingestion	: May be harmful if swallowed.		
Eyes	: May cause eye/skin irritation.		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		





#### DB3636 WHITE Version Number 1.0 Page 2 of 6 Revision Date 10/21/2002 Print Date 11/6/2011 **Medical Conditions** : None known. Aggravated by Exposure: 4. FIRST AID MEASURES Move to fresh air in case of accidental inhalation of fumes from Inhalation : overheating or combustion. When symptoms persist, or in all cases of doubt, seek medical advice. : Do not induce vomiting without medical advice. When symptoms Ingestion persist, or in all cases of doubt, seek medical advice. Eyes : Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention. Skin : Wash off with soap and plenty of water. If skin irritation persists seek medical attention. **5. FIRE-FIGHTING MEASURES** Flash point No data available. · Flammable Limits No data available. Upper explosion limit : Lower explosion limit No data available. : Autoignition temperature Not applicable. : Suitable extinguishing media : Carbon dioxide blanket, dry powder, foam, Water spray. Special Fire Fighting : Fullface self-contained breathing apparatus (SCBA) used in positive Procedures pressure mode should be worn to prevent inhalation of airborne contaminants. Unusual Fire/Explosion May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under : Hazards fire conditions. 6. ACCIDENTAL RELEASE MEASURES Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. Environmental precautions Should not be released into the environment. The product should not • be allowed to enter drains, water courses or the soil. Methods for cleaning up Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, : universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods. 7. HANDLING AND STORAGE Handling : Heat only in areas with appropriate exhaust ventilation. Processing





DB3636 WHITE		
ersion Number 1.0 evision Date 10/21/2002		Page 3 of 6 Print Date 11/6/2011
		fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.
8. EXI	POSUI	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	Under normal handling conditions a respirator may not be required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

Components	Value	Exposure time	Exposure type	List:
Silica, amorphous	20 mppcf	PEL:	Total dust.	OSHA
Silica, amorphous	20 mppcf	PEL:	Total dust.	Z3
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):	Dust.	ACGIH
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- : Liquid
  : Viscous, Liquid
  : WHITE
  : Very faint
  : Not applicable
  : Not applicable
  : Immiscible
- Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH
- Not establishedNot determined
- : Not applicable.
- : Not determined
- : Not determined
- : Not applicable.

#### **10. STABILITY AND REACTIVITY**

Stability

: Stable.



#### MATERIAL SAFETY DATA SHEET

## DB3636 WHITE

Version Number 1.0 Revision Date 10/21/2002		Page 4 of 6 Print Date 11/6/2011
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: No data available.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.



#### MATERIAL SAFETY DATA SHEET

# DB3636 WHITE

Version Number 1.0 Revision Date 10/21/2002 Page 5 of 6 Print Date 11/6/2011

	1	4. TRANSPORT INFORMATION
U.S. DOT Classification	:	Refer to specific regulation.
ICAO/IATA	:	Refer to specific regulation.
IMO / IMDG	:	Refer to specific regulation.
	15	. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on the TSCA inventory or are exempt.
US. EPA CERCLA Hazardou	us Sub	stances (40 CFR 302)
Not applicable		
California Proposition 65 SARA Title III Section 302 E Not applicable		California to cause cancer.
65 SARA Title III Section 302 E		California to cause cancer.
65 SARA Title III Section 302 E Not applicable	Extrem	California to cause cancer.
65 SARA Title III Section 302 E Not applicable Canadian Regulations:	Extrem n :	California to cause cancer. ely Hazardous Substance D2B
65 SARA Title III Section 302 E Not applicable Canadian Regulations: WHMIS Classificatio	Extrem n :	California to cause cancer. ely Hazardous Substance D2B
65 SARA Title III Section 302 E Not applicable Canadian Regulations: WHMIS Classification WHMIS Ingredient Di CAS-No.	Extrem n :	California to cause cancer. ely Hazardous Substance D2B
65 SARA Title III Section 302 E Not applicable Canadian Regulations: WHMIS Classificatio WHMIS Ingredient Di CAS-No. 7631-86-9	Extrem n : isclosu	California to cause cancer. ely Hazardous Substance D2B re List
65 SARA Title III Section 302 E Not applicable Canadian Regulations: WHMIS Classificatio WHMIS Ingredient Di CAS-No. 7631-86-9 DSL	Extrem n : isclosu	California to cause cancer. ely Hazardous Substance D2B re List
65 SARA Title III Section 302 E Not applicable Canadian Regulations: WHMIS Classification WHMIS Ingredient Di CAS-No. 7631-86-9 DSL National Inventories:	Extrem n : isclosu	California to cause cancer. ely Hazardous Substance D2B re List Listed.



#### MATERIAL SAFETY DATA SHEET

## DB3636 WHITE

Version Number 1.0 Revision Date 10/21/2002 Page 6 of 6 Print Date 11/6/2011

Japan ENCS	:	Not determined.

Korea KECI : Listed.

Philippines PICCS : Listed.

### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.