PolvOne

MATERIAL SAFETY DATA SHEET 95550SSVFF MATTE BLACK

Version Number 1.3 Revision Date 03/26/2010 Page 1 of 8 Print Date 1/11/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone:Emergency telephone:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	95550SSVFF MATTE BLACK
Product code :	FO20002327
Chemical Name :	Mixture
CAS-No. :	Mixture
Product Use :	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent
1,2-Benzenedicarboxylic acid, butyl	85-68-7	30 - 60
phenylmethylester		
Carbon black	1333-86-4	1 - 5
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion Eyes	May be harmful if swallowed.May cause eye and skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne.

MATERIAL SAFETY DATA SHEET 95550SSVFF MATTE BLACK

Version Number 1.3 Revision Date 03/26/2010 Page 2 of 8 Print Date 1/11/2012

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: no data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 no data available no data available Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are
	all possible. 6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as
L.	impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS

PolyOne.

Page 3 of 8 Print Date 1/11/2012

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET 95550SSVFF MATTE BLACK

Version Number 1.3 Revision Date 03/26/2010

		7. HANDLING AND STORAGE
Handling	:	Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.
8. EX	POSU	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

PolyOne

MATERIAL SAFETY DATA SHEET 95550SSVFF MATTE BLACK

Version Number 1.3 Revision Date 03/26/2010 Page 4 of 8 Print Date 1/11/2012

Components	Value	Exposure time	Exposure type	List:
Carbon black	3.5 mg/m3	Time Weighted Average (TWA):		ACGIH
	3.5 mg/m3	Recommended exposure limit (REL):		NIOSH
	0.1 mg/m3	Recommended exposure limit (REL):		NIOSH
	3.5 mg/m3	PEL:		OSHA Z1
	3.5 mg/m3	Time Weighted Average (TWA):		OSHA Z1A
	3.5 mg/m3	Time Weighted Average (TWA):		MX OEL
	7 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Silica, amorphous, fumed, crystal-free	0.8 mg/m3	Time Weighted Average (TWA):		Z3
	10 mg/m3	Time Weighted Average (TWA):	Inhalable particulate.	MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility
- liquid
 viscous, liquid
 BLACK
 very faint
 not applicable
 not applicable
 immiscible

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH Not established
Not determined
Not applicable
Not determined
Not determined
Not applicable

10. STABILITY AND REACTIVITY

Stability	:	Stable
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

MATERIAL SAFETY DATA SHEET 95550SSVFF MATTE BLACK

Version Number 1.3 Revision Date 03/26/2010

Page 5 of 8 Print Date 1/11/2012

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
85-68-7	1,2-Benzenedicarboxylic acid, butyl phenylmethylester	Irritant	Eyes, Skin.
		Systemic effects	Liver, reproductive system.
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
112945-52-5	Silica, amorphous, fumed, crystal-free	Irritant	Eyes, Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
85-68-7	1,2-Benzenedicarboxylic	Oral LD50	2,330 mg/kg	rat
	acid, butyl	Dermal LD50	>10 gm/kg	rabbit
	phenylmethylester	Dermal LD50	6,700 mg/kg	rat
		Dermal LD50	6,700 mg/kg	mouse
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit
112945-52-5	Silica, amorphous, fumed,	Oral LD50	3,160 mg/kg	rat
	crystal-free			

Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). The IARC 2B listing only pertains to airborne, unbound carbon black particles of respirable size. Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Environmental toxicity has

: Environmental toxicity has not been established for this mixture as a whole.

PolyOne.

MATERIAL SAFETY DATA SHEET 95550SSVFF MATTE BLACK

Version Number 1.3 Revision Date 03/26/2010 Page 6 of 8 Print Date 1/11/2012

Additional advice	: no data avail	aon	
	13. DISPOSAI	CONSIDERA	TIONS
Product	generator of classification	waste material h	preferred to disposal or incineration. Th as the responsibility for proper waste and disposal in accordance with incial and local regulations.
Contaminated packaging	material has transportatio	the responsibility	possible. The generator of waste y for proper waste classification, accordance with applicable federal, ulations.
	14. TRANSPO	ORT INFORMA	TION
U.S. DOT Classification Proper Shipping Name: Technical Name: Hazard Class / Division UN Number Packing Group	Environmentally 9 UN3082 III	hazardous subst	ances, liquid, n.o.s.
Label Required	9		
Hazardous Substa Butyl benzyl phthalate		RQ for ure/Product	
ICAO/IATA	Refer to specific	regulation.	
IMO/IMDG (maritime)	Refer to specific	regulation.	
	15. REGULAT	ORY INFORM	ATION
US Regulations:			
OSHA Status	: Classified as	hazardous based	l on components.
TSCA Status	: All compon TSCA Inven		act are listed on or exempt from the
US. EPA CERCLA Hazardo	us Substances (40 CI	FR 302)	
Chemical Name	CAS-No. RO	Q for component	RQ for

PolyOne.

MATERIAL SAFETY DATA SHEET 95550SSVFF MATTE BLACK

Version Number 1.3 Revision Date 03/26/2010 Page 7 of 8 Print Date 1/11/2012

Calif Calif 65 ARA Title aless speci Chemical ARA Title aless speci anadian Ra <u>Natic</u> Chemical	Name III Section 313 ific chemicals a egulations: onal Pollutant R	Extremel re identifi Toxic Ch re identifi	California ly Hazardo ied under ti nemicals: ied under ti	to cause birth ous Substance <u>his section, thi</u> CAS-No.	defects or o s product is % in P	a chemical kno other reproducti s Not Applicable roduct RQ f comp	ve harm. e under this re or oonent	gula
Calif 65 RA Title less speci Chemical RA Title less speci nadian Ro Natic Chemical	fornia Propositi III Section 302 ific chemicals a Name III Section 313 ific chemicals a egulations: onal Pollutant R	Extremel re identifi Toxic Ch re identifi	California ly Hazardo ied under ti nemicals: ied under ti	to cause birth ous Substance <u>his section, thi</u> CAS-No.	defects or o s product is % in P	Not Applicable roduct RQ f	ve harm. e under this re or oonent	gula
65 RA Title less speci Chemical RA Title less speci nadian Ro Natic Chemical	III Section 302 ific chemicals a Name III Section 313 ific chemicals a egulations: onal Pollutant R	Extremel re identifi Toxic Ch re identifi	California ly Hazardo ied under ti nemicals: ied under ti	to cause birth ous Substance <u>his section, thi</u> CAS-No.	defects or o s product is % in P	Not Applicable roduct RQ f	ve harm. e under this re or oonent	gula
65 RA Title less speci Chemical RA Title less speci nadian Ro Natic Chemical	III Section 302 ific chemicals a Name III Section 313 ific chemicals a egulations: onal Pollutant R	Extremel re identifi Toxic Ch re identifi	California ly Hazardo ied under ti nemicals: ied under ti	to cause birth ous Substance <u>his section, thi</u> CAS-No.	defects or o s product is % in P	Not Applicable roduct RQ f	ve harm. e under this re or oonent	gula
65 RA Title less speci Chemical RA Title less speci nadian Ro Natic Chemical	III Section 302 ific chemicals a Name III Section 313 ific chemicals a egulations: onal Pollutant R	Extremel re identifi Toxic Ch re identifi	California ly Hazardo ied under ti nemicals: ied under ti	to cause birth ous Substance <u>his section, thi</u> CAS-No.	defects or o s product is % in P	Not Applicable roduct RQ f	ve harm. e under this re or oonent	gula
Iess speci Chemical RA Title Iess speci nadian Re Natic Chemical	ific chemicals a Name III Section 313 ific chemicals a egulations: onal Pollutant R	re identifi Toxic Ch re identifi	ied under the memicals:	his section, thi CAS-No.	% in P	Product RQ f	or ponent	-
Iess speci Chemical RA Title Iess speci nadian Re Natic Chemical	ific chemicals a Name III Section 313 ific chemicals a egulations: onal Pollutant R	re identifi Toxic Ch re identifi	ied under the memicals:	his section, thi CAS-No.	% in P	Product RQ f	or ponent	-
RA Title less speci nadian Re Natic Chemical	Name III Section 313 ific chemicals a egulations: onal Pollutant R	Toxic Cł re identifi	nemicals: ied under ti	CAS-No.	% in P	Product RQ f	or ponent	-
less speci nadian Ro <u>Natic</u> Chemical	ific chemicals a egulations: onal Pollutant R	re identifi	ied under t			comp	oonent	gulat
nadian Ro Natio Chemical	ific chemicals a egulations: onal Pollutant R	re identifi	ied under t		s product is	S Not Applicable	e under this re	gulat
nadian Ro Natio Chemical	ific chemicals a egulations: onal Pollutant R	re identifi	ied under t		s product is	s Not Applicable	e under this re	gulat
lless speci nadian Ro <u>Natic</u> Chemical	ific chemicals a egulations: onal Pollutant R	re identifi	ied under t		s product is	s Not Applicable	e under this re	gula
nadian Re <u>Natic</u> Chemical 1,2-Benze	egulations: onal Pollutant R				s product is	s Not Applicable	e under this re	gula
Natio Chemical	onal Pollutant R	elease Inv	ventory (N	PRI)				
Chemical		elease Inv	ventory (N	PRI)				
Chemical 1,2-Benze								
				CAS-N	lo.	Weight	NPRI ID#]
phenylme	enedicarboxylic	acid, but	yl	85-68-	7	percent 30.00 - 60.00		-
	thylester							
WH	MIS Classificat	ion :	D2A					
WHN	MIS Ingredient	Disclosur	e List					
** 111		Disclosur	e List					
	CAS-No. 1333-86-4							
	85-68-7							
DSL		:		is has not been by regulations.		d. Quantity use	in Canada ma	ıy be
tional Inv	ventories:							
Aust	ralia AICS	:	Not detern	nined				
Chin	a IECS	:	Not detern	nined				

PolyOne.

MATERIAL SAFETY DATA SHEET 95550SSVFF MATTE BLACK

Version Number 1.3 Revision Date 03/26/2010 Page 8 of 8 Print Date 1/11/2012

:	Not determined
:	Not determined
:	Not determined
:	Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.