## MATERIAL SAFETY DATA SHEET C DM1520 ORANGE

Version Number 1.5 Revision Date 03/26/2007

Page 1 of 7 Print Date 11/27/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone:Emergency telephone:number	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	C DM1520 ORANGE
Product code :	FO20002668
Chemical Name :	Mixture
CAS-No. :	Mixture
Product Use :	Industrial Applications

### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Lead chromate	7758-97-6	1 - 5

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne.

# MATERIAL SAFETY DATA SHEET C DM1520 ORANGE

Version Number 1.5 Revision Date 03/26/2007 Page 2 of 7 Print Date 11/27/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: no data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>no data available</li> <li>no data available</li> <li>Not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide: of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> <li>6. ACCIDENTAL RELEASE MEASURES</li> </ul>
Personal precautions	<ul> <li>Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.</li> </ul>
Environmental precautions	<ul> <li>The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.</li> </ul>
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing



# MATERIAL SAFETY DATA SHEET C DM1520 ORANGE

Version Number 1.5	Page 3 of 7
Revision Date 03/26/2007	Print Date 11/27/2011
	fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
Storage :	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.
8. EXPOSU	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection :	No personal respiratory protective equipment normally required.
Eye/Face Protection :	Safety glasses with side-shields
Hand protection :	Protective gloves
Skin and body protection :	Long sleeved clothing
Additional Protective : Measures	Safety shoes
General Hygiene : Considerations	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures :	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Lead chromate	0.012	Time Weighted Average	as Cr	ACGIH
	mg/m3	(TWA):		
	0.05	Time Weighted Average	as Pb	ACGIH
	mg/m3	(TWA):		
	0.005	Time Weighted Average		OSHA
	mg/m3	(TWA):		
	0.0025	OSHA Action level:		OSHA
	mg/m3			
	0.1 mg/m3	Ceiling Limit Value:		OSHA Z2
	0.01	Time Weighted Average		MX OEL
	mg/m3	(TWA):		
	1 mg/m3	PEL:	as Cr	OSHA Z1
	0.05	Time Weighted Average		OSHA
	mg/m3	(TWA):		
	0.03	OSHA Action level:		OSHA
	mg/m3			
	0.15	Time Weighted Average	Dust and fume. as Pb	MX OEL
	mg/m3	(TWA):		

## 9. PHYSICAL AND CHEMICAL PROPERTIES

## **MATERIAL SAFETY DATA SHEET** C DM152O ORANGE

Version Number 1.5 Revision Date 03/26/2007

Page 4 of 7 Print Date 11/27/2011

	10. STABILITY AND REACTIVITY
Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	<ul> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).</li> </ul>

### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7758-97-6	Lead chromate	Systemic effects	central nervous system (CNS), reproductive system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
7758-97-6	Lead chromate	Oral LD50	> 12 gm/kg	mouse

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

PolyOne

# MATERIAL SAFETY DATA SHEET C DM1520 ORANGE

Version Number 1.5

Revision Date 03/26/2007

Page 5 of 7 Print Date 11/27/2011

CAS-No.	Chemical Name	OSHA	IARC	NTP
7758-97-6	Lead chromate	yes	1	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

#### Additional Health Hazard Information:

Lead chromate 7758-97-6 Systemic effects include neurotoxic, teratogenic, fetotoxic and reproductive with abdominal pain, anemia, pallor, decreased hand grip strength with characteristic "wrist drop".

### **12. ECOLOGICAL INFORMATION**

Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: no data available
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION

PolyOne.

# MATERIAL SAFETY DATA SHEET C DM1520 ORANGE

ersion Number 1.5 evision Date 03/26/2007					Pri	F nt Date 1	Page 6 of 7 1/27/201
US Regulations:							
OSHA Status :	Classified as haz	ardous b	ased on con	nponent	S.		
TSCA Status :	All components of this product are listed on or exempt from the TSCA Inventory.						
US. EPA CERCLA Hazardous Sub	stances (40 CFR 3	302)					
Not applicable							
California Proposition : 65	WARNING! This product contains a chemical known to the State of California to cause cancer., WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.						
SARA Title III Section 302 Extrem	ely Hazardous Su	bstance					
Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation							
Oness specific chemicars are ident	incu under uns sec	zuon, uns	s product is	Not Ap	pheable	under uns	regulation
SARA Title III Section 313 Toxic	Chemicals:						
TT-1	· C . 1 1		1		. 1 1. 1.	1.1.1	1.1.1
Unless specific chemicals are identified under this section, this prod							
Chemical Name CHROMIUM VI COMPOUNDS			CAS-No. 7758-97-6		Weight % 1.00 - 5.00		
COMPOUNDSLEAD COMPOUNDS		IIC	//38-9/-0		1.00 - 5.00		
COMI OCIUSELIU COMI OC							
Canadian Regulations:							
National Pollutant Release I	nventory (NPRI)						
Chemical Name		CAS-N	0.	Weight	: %	NPRI IE	<b>)</b> #
Lead chromate		7758-9	7-6	1.00 - 5		235	
				1.00 - 5		236	
Miscellaneous Zinc Compounds		0-31-7		0.10 - 1	1.00	241	
WHMIS Classification :	D2A						
WHMIS Ingredient Disclosure List							
CAS-No. 7758-97-6							

PolyOne

## MATERIAL SAFETY DATA SHEET C DM1520 ORANGE

Version Number 1.5 Revision Date 03/26/2007		Print Date	Page 7 of 7 11/27/2011				
DSL :	All of the components of this product are list aventories or are exempt. However, at least roduct is on the Canadian Non-Domestic Su quantity use in Canada is restricted by regula	one component bstances List (	of this				
National Inventories:							
Australia AICS	ot determined						
China IECS :	lot determined						
Europe EINECS :	lot determined						
Japan ENCS :	lot determined						
Korea KECI :	lot determined						
Philippines PICCS :	lot determined						
16. OTHER INFORMATION							

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.