

MATERIAL SAFETY DATA SHEET

## STAN-TONE HCC-27818 BLUE

Version Number 1.0 Revision Date 11/19/2002 Page 1 of 7 Print Date 11/6/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	STAN-TONE HCC-27818 BLUE
Product code	:	FO20002676
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Di(2-ethylhexyl)phthalate	117-81-7	30 - 60

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. In addition, heating or processing this material may result in product degradation or byproduct formation creating additional hazards. See Sections 8 and 11 for additional details.

#### POTENTIAL HEALTH EFFECTS

: Inhalation, Skin contact, Ingestion
: Irritating to respiratory system.
: No known effects.
: Particulates, like other inert materials can be mechanically irritating.
: Experience shows no unusual dermatitis hazard from routine handling.
: Refer to Section 11 for Toxicological Information.
: None known.



#### MATERIAL SAFETY DATA SHEET

# STAN-TONE HCC-27818 BLUE

ion Number 1.0 sion Date 11/19/2002	Page 2 Print Date 11/6/2
Inhalation	: Move to fresh air. When symptoms persist or in all cases of doubt seel medical advice.
Ingestion	: Not an anticipated hazard.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits	No. 11. 11.
Upper explosion limit	: Not applicable
Lower explosion limit Autoignition temperature	<ul><li>Not applicable</li><li>No data available.</li></ul>
Suitable extinguishing media	: Use water spray, alcohol-resistant foam, dry chemical or carbon
Suitable extinguishing media	dioxide
Special Fire Fighting	: Fullface self-contained breathing apparatus (SCBA) used in positive
Procedures	pressure mode should be worn to prevent inhalation of airborne
	contaminants.
Unusual Fire/Explosion Hazards	: None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Avoid breathing dust. Avoid dust formation. Ensure adequate ventilation. Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Do not create a powder cloud by using a brush or compressed air. Shovel into suitable container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Provide for appropriate exhaust ventilation and dust collection at machinery. Avoid formation of dust and aerosols.
Storage	: Store in a cool dry place. Keep away from open flames, hot surfaces and sources of ignition.



MATERIAL SAFETY DATA SHEET

# STAN-TONE HCC-27818 BLUE

Version Number 1.0 Revision Date 11/19/2002 Page 3 of 7 Print Date 11/6/2011

	XPOSURE	CONTROLS / PERSONAL	PROTECTION	
Respiratory protection	n r	When workers are facing concernust use appropriate certified respirators must be properly traipplicable regulations such as O	spirators. Employees under Employees under Employers must f	using Follow
Eye/Face Protection	: S	afety glasses with side-shields.		
Hand protection	: P	Protective gloves.		
Skin and body protection	: L	long sleeved clothing.		
Additional Protective Measures	: S	afety shoes		
General Hygiene Considerations		Handle in accordance with good Vash hands before breaks and in		
Engineering measures	a	Adequate ventilation and/or app lso be necessary to minimize e apors.		
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Components Di(2-ethylhexyl)phthal ate	Value 5 mg/m3	Exposure time Time Weighted Average (TWA):	Exposure type Vapor.	List: ACGIH
Di(2-ethylhexyl)phthal		Time Weighted Average		ACGIH
Di(2-ethylhexyl)phthal ate Di(2-ethylhexyl)phthal	5 mg/m3	Time Weighted Average (TWA):	Vapor.	ACGIH
Di(2-ethylhexyl)phthal ate Di(2-ethylhexyl)phthal ate Di(2-ethylhexyl)phthal	5 mg/m3 5 mg/m3	Time Weighted Average (TWA): PEL: Time Weighted Average	Vapor. Vapor.	ACGIH OSHA Z1 MX OEL
Di(2-ethylhexyl)phthal ate Di(2-ethylhexyl)phthal ate Di(2-ethylhexyl)phthal	5 mg/m3 5 mg/m3 5 mg/m3 10 mg/m3	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit	Vapor. Vapor. Vapor. Vapor.	ACGIH OSHA Z1 MX OEL
Di(2-ethylhexyl)phthal ate Di(2-ethylhexyl)phthal ate Di(2-ethylhexyl)phthal ate	5 mg/m3 5 mg/m3 5 mg/m3 10 mg/m3 9. PHYSIC	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO	Vapor. Vapor. Vapor. Vapor. PERTIES	ACGIH OSHA Z1 MX OEL MX OEL
Di(2-ethylhexyl)phthal ate Di(2-ethylhexyl)phthal ate Di(2-ethylhexyl)phthal ate	5 mg/m3 5 mg/m3 5 mg/m3 10 mg/m3 9. PHYSIC : Solid	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO	Vapor. Vapor. Vapor. Vapor. PERTIES ration rate : No	ACGIH OSHA Z1 MX OEL MX OEL t applicable.
Di(2-ethylhexyl)phthal ate Di(2-ethylhexyl)phthal ate Di(2-ethylhexyl)phthal ate	5 mg/m3 5 mg/m3 5 mg/m3 10 mg/m3 9. PHYSIC : Solic : pow	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapor der, flakes Specifi	Vapor. Vapor. Vapor. Vapor. PERTIES ration rate : No c Gravity : No	ACGIH OSHA Z1 MX OEL MX OEL t applicable. t determined
Di(2-ethylhexyl)phthal ate Di(2-ethylhexyl)phthal ate Di(2-ethylhexyl)phthal ate Form Appearance Color	5 mg/m3 5 mg/m3 5 mg/m3 10 mg/m3 9. PHYSIC : Solic : pow : BLU	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapor der, flakes Specifi JE Bulk d	Vapor. Vapor. Vapor. Vapor. PERTIES ration rate : No c Gravity : No ensity : No	ACGIH OSHA Z1 MX OEL MX OEL t applicable. t determined t determined
Di(2-ethylhexyl)phthal ate Di(2-ethylhexyl)phthal ate Di(2-ethylhexyl)phthal ate Form Appearance Color Odor	5 mg/m3 5 mg/m3 5 mg/m3 10 mg/m3 9. PHYSIC : Solic : pow : BLU : Very	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapor der, flakes Specifi JE Bulk d y faint Vapor	Vapor. Vapor. Vapor. Vapor. PERTIES ation rate : No c Gravity : No ensity : No pressure : No	ACGIH OSHA Z1 MX OEL MX OEL t applicable. t determined t determined t applicable.
Di(2-ethylhexyl)phthal ate Di(2-ethylhexyl)phthal ate Di(2-ethylhexyl)phthal ate Form Appearance Color Odor Melting point/range	5 mg/m3 5 mg/m3 5 mg/m3 10 mg/m3 9. PHYSIO : Solid : pow : BLU : Very : Not	Time Weighted Average (TWA):   PEL:   Time Weighted Average (TWA):   Short Term Exposure Limit (STEL):   CAL AND CHEMICAL PRO   d Evapor   der, flakes Specifi   JE Bulk d   / faint Vapor   applicable Vapor	Vapor. Vapor. Vapor. Vapor. PERTIES ration rate : No c Gravity : No ensity : No pressure : No density : No	ACGIH OSHA Z1 MX OEL MX OEL MX OEL t applicable. t determined t determined t applicable. t applicable
Di(2-ethylhexyl)phthal ate Di(2-ethylhexyl)phthal ate Di(2-ethylhexyl)phthal ate Form Appearance Color Odor	5 mg/m3 5 mg/m3 5 mg/m3 10 mg/m3 9. PHYSIO : Solid : pow : BLU : Very : Not : Not	Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapor der, flakes Specifi JE Bulk d y faint Vapor	Vapor. Vapor. Vapor. Vapor. PERTIES ration rate : No c Gravity : No ensity : No pressure : No density : No	ACGIH OSHA Z1 MX OEL MX OEL t applicable. t determined t determined t applicable.
Di(2-ethylhexyl)phthal ate Di(2-ethylhexyl)phthal ate Di(2-ethylhexyl)phthal ate Form Appearance Color Odor Melting point/range Boiling Point:	5 mg/m3 5 mg/m3 5 mg/m3 10 mg/m3 9. PHYSI : Solid : pow : BLU : Very : Not : Not : Neg	Time Weighted Average (TWA):   PEL:   Time Weighted Average (TWA):   Short Term Exposure Limit (STEL):   CAL AND CHEMICAL PRO   d Evapor   der, flakes Specifi   JE Bulk d   / faint Vapor   applicable Vapor   applicable. pH	Vapor. Vapor. Vapor. Vapor. PERTIES ation rate : No c Gravity : No ensity : No pressure : No density : No : No	ACGIH OSHA Z1 MX OEL MX OEL MX OEL t applicable. t determined t determined t applicable. t applicable
Di(2-ethylhexyl)phthal ate Di(2-ethylhexyl)phthal ate Di(2-ethylhexyl)phthal ate Form Appearance Color Odor Melting point/range Boiling Point:	5 mg/m3 5 mg/m3 5 mg/m3 10 mg/m3 9. PHYSIO : Solid : pow : BLU : Very : Not : Not : Negi 10. §	Time Weighted Average (TWA):   PEL:   Time Weighted Average (TWA):   Short Term Exposure Limit (STEL):   CAL AND CHEMICAL PRO   d Evapor   der, flakes Specifi   JE Bulk d   y faint Vapor   applicable pH   ligible Vapor	Vapor. Vapor. Vapor. Vapor. PERTIES ation rate : No c Gravity : No ensity : No pressure : No density : No : No	ACGIH OSHA Z1 MX OEL MX OEL MX OEL t applicable. t determined t determined t applicable. t applicable



#### MATERIAL SAFETY DATA SHEET

# STAN-TONE HCC-27818 BLUE

Version Number 1.0 Revision Date 11/19/2002 Page 4 of 7 Print Date 11/6/2011

Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible Materials	:	strong acids and oxidizing agents
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible.

#### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
117-81-7	Di(2-ethylhexyl)phthalate	Systemic effects	Eyes, Respiratory system, Liver, central nervous system, Skin, digestive system.

#### LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
117-81-7	Di(2-ethylhexyl)phthalate	Oral LD50	30 gm/kg	rat
		Dermal LD50	25 gm/kg	rabbit

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
117-81-7	Di(2-ethylhexyl)phthalate	no	no	2

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

#### Additional Health Hazard Information:



MATERIAL SAFETY DATA SHEET

## STAN-TONE HCC-27818 BLUE

Version Number 1.0 Revision Date 11/19/2002 Page 5 of 7 Print Date 11/6/2011

Di(2-ethylhexyl)phthalate 117-81-7 There is sufficient evidence for the carcinogenicity of di (2-ethylhexyl) phthalate in experimental animals. Administered in the feed this chemical caused an increase incidence of liver cancer in male and female rats and mice. The relevance of this finding to humans is uncertain.

Environmental Toxicity				
	: No data available.			
Bioaccumulation Potential	: No data available.			
Additional advice	: No data	available.		
	13. DISPO	SAL CONSIDE	RATIONS	
Product	generato classifica	r of waste mater ation, transportat	g is preferred to dispo- ial has the responsibili ion and disposal in ac provincial and local re	cordance with
Contaminated packaging	has the r and disp	esponsibility for	nen possible. The gen proper waste classific ce with applicable fed	
	14. TRAN	SPORT INFOR	RMATION	
J.S. DOT Classification	: Refer to	specific regulati	on.	
CAO/IATA	: Refer to	specific regulati	on.	
MO / IMDG	: Refer to	specific regulati	on.	
	15. REGUL	ATORY INFO	RMATION	
JS Regulations:				
OSHA Status	: Classifie	ed as hazardous b	ased on components.	
TSCA Status	: All com Inventor		roduct are listed on or	exempt from the TSC.
JS. EPA CERCLA Hazardous	Substances (4	0 CFR 302)		
Chemical Name C.	AS-No.	% in Product	RQ for component	RQ for Mixture/Product



MATERIAL SAFETY DATA SHEET

### STAN-TONE HCC-27818 BLUE

Version Number 1.0 Page 6 of 7 Print Date 11/6/2011 Revision Date 11/19/2002 Di(2-ethylhexyl)ph 117-81-7 54.1998 100 lbs 185 LB thalate California Proposition : WARNING! This product contains a chemical known to the State of 65 California to cause cancer. SARA Title III Section 313 Toxic Chemicals: Chemical Name CAS-No. Weight % DI(2-ETHYLHEXYL)PHTHALATE 117-81-7 54.19 (DEHP) Canadian Regulations: WHMIS Classification : D2A WHMIS Ingredient Disclosure List CAS-No. 117-81-7 DSL All components of this product are on the Canadian Domestic : Substances List (DSL) or are exempt. National Inventories: Australia AICS Listed. : China IECS Not determined. **Europe EINECS** Listed. : Japan ENCS Not determined. · Korea KECI Listed. : **Philippines PICCS** Not determined. : **16. OTHER INFORMATION** The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief

at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.



MATERIAL SAFETY DATA SHEET

# STAN-TONE HCC-27818 BLUE

Version Number 1.0 Revision Date 11/19/2002 Page 7 of 7 Print Date 11/6/2011