

### MATERIAL SAFETY DATA SHEET

## **19095MET BLACK METALLIC**

Version Number 1.0 Revision Date 12/18/2002 Page 1 of 7 Print Date 11/7/2011

## 1. PRODUCT AND COMPANY IDENTIFICATION

### POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	19095MET BLACK METALLIC
Product code	:	FO20002725
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Carbon black	1333-86-4	1 - 5
Diatomaceous earth	61790-53-2	1 - 5
Aluminum	7429-90-5	5 - 10

## **3. HAZARDS IDENTIFICATION**

### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

## POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET

# 19095MET BLACK METALLIC

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available.
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>No data available.</li> <li>No data available.</li> <li>Not applicable.</li> <li>Carbon dioxide blanket, dry powder, foam, Water spray.</li> </ul>
Special Fire Fighting Procedures	<ul> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> </ul>
Unusual Fire/Explosion Hazards	: May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binde universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing



### MATERIAL SAFETY DATA SHEET

## **19095MET BLACK METALLIC**

Version Number 1.0 Revision Date 12/18/2002	Page 3 of 7 Print Date 11/7/2011
Storage :	fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials. Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.
8. EXPOSU	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection :	Under normal handling conditions a respirator may not be required.
Eye/Face Protection :	Safety glasses with side-shields.
Hand protection :	Protective gloves.
Skin and body protection :	Long sleeved clothing.
Additional Protective : Measures	Safety shoes.
General Hygiene : Considerations	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures :	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

## Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Aluminum	10 mg/m3	Time Weighted Average (TWA):	Dust.	ACGIH
	5 mg/m3	Time Weighted Average (TWA):	Welding fume. as Al	ACGIH
Aluminum	15 mg/m3	PEL:	Total dust. as Al	OSHA Z1
	5 mg/m3	PEL:	Respirable dust. as Al	OSHA Z1
Carbon black	3.5 mg/m3	Time Weighted Average	Total dust. as carbon	ACGIH
		(TWA):	black	
Carbon black	3.5 mg/m3	PEL:	Total dust. as carbon black	OSHA Z1
Diatomaceous earth	10 mg/m3	Time Weighted Average (TWA):	Inhalable dust.	ACGIH
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	ACGIH
Diatomaceous earth	20 mppcf	PEL:	Total dust.	Z3

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance : Liquid : Viscous, Liquid

Evaporation rate : Not established Specific Gravity : Not determined



### MATERIAL SAFETY DATA SHEET

## **19095MET BLACK METALLIC**

Version Number 1.0 Revision Date 12/18/2002 Page 4 of 7 Print Date 11/7/2011

Color Odor Melting point/range Boiling Point: Water solubility	: V : 1 : 1	BLACK Very faint Not applicable Not applicable mmiscible	Bulk density Vapor pressure Vapor density pH	: :	Not applicable. Not determined Not determined Not applicable.
	1	10. STABILITY AND RE	ACTIVITY		
Stability	:	Stable.			
Hazardous Polymerization	:	Will not occur.			
Conditions to avoid	:	Keep away from oxidized decomposition, do not o	00	me.	To avoid thermal
Incompatible Materials	:	Incompatible with stron with acetal homopolym	• •	-	
Hazardous decomposition products	:	Carbon dioxide (CO2), (NOx), hydrogen chlori smoke are all possible.	de (HCl), other hazardo	ous r	naterials, and

### **11. TOXICOLOGICAL INFORMATION**

and within 5 minutes at 232 °C (450 °F).

degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F),

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
61790-53-2	Diatomaceous earth	Irritant	Eyes, Respiratory system.
7429-90-5	Aluminum	Irritant	Skin, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system.

#### LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

#### Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:



MATERIAL SAFETY DATA SHEET

## **19095MET BLACK METALLIC**

Version Number 1.0 Revision Date 12/18/2002 Page 5 of 7 Print Date 11/7/2011

CAS-No.	Chemical Name	OSHA	IARC	NTP
1333-86-4	Carbon black	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

### Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

#### **12. ECOLOGICAL INFORMATION**

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	:	No data available.
Additional advice	:	No data available.
	1	3. DISPOSAL CONSIDERATIONS
Product	:	Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	:	Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	1	4. TRANSPORT INFORMATION



## MATERIAL SAFETY DATA SHEET

# 19095MET BLACK METALLIC

ersion Number 1.0 Nevision Date 12/18/2002			Page 6 c Print Date 11/7/20	
U.S. DOT Classification	: Refer to specifi	c regulation.		
ICAO/IATA	: Refer to specifi	c regulation.		
IMO / IMDG	: Refer to specifi	c regulation.		
	15. REGULATOR	RY INFORMATIC	DN	
US Regulations:				
OSHA Status	: Classified as ha	zardous based on co	omponents.	
TSCA Status	: All component Inventory.	s of this product are	listed on or exempt from the TSCA	
US. EPA CERCLA Hazardou	s Substances (40 CFR	302)		
Not applicable				
SARA Title III Section 302 E Not applicable SARA Title III Section 313 To		ubstance		
		C 4 G M	XXX : 1 - 0/	
Chemical Nam ALUMINUM	e (FUME OR DUST)	CAS-No. 7429-90-5	Weight % 08.39	
Canadian Regulations:				
WHMIS Classification	n : D2A			
WHMIS Ingredient Dis	sclosure List			
CAS-No. 7429-90-5 1333-86-4				
DSL	-	ts of this product are to (DSL) or are exem	e on the Canadian Domestic pt.	
National Inventories:				
Australia AICS	: Listed.			



### MATERIAL SAFETY DATA SHEET

## **19095MET BLACK METALLIC**

Version Number 1.0 Revision Date 12/18/2002 Page 7 of 7 Print Date 11/7/2011

China IECS	: Not determined.
Europe EINECS	: Not determined.
Japan ENCS	: Not determined.
Korea KECI	: Listed.
Philippines PICCS	: Not determined.

### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.