## MATERIAL SAFETY DATA SHEET **D3308 DARK GREEN**

Version Number 1.2 Revision Date 06/19/2007

Page 1 of 6 Print Date 11/29/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	D3308 DARK GREEN
Product code	:	FO20004031
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Calcium carbonate	1317-65-3	5 - 10

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Skin contact, Ingestion		
Acute exposure			
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.		
Ingestion	: May be harmful if swallowed.		
Eyes	: May cause eye/skin irritation.		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		
Medical Conditions Aggravated by Exposure:	: None known.		

PolyOne.

# MATERIAL SAFETY DATA SHEET **D3308 DARK GREEN**

Version Number 1.2 Revision Date 06/19/2007 Page 2 of 6 Print Date 11/29/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases or doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>No data available</li> <li>No data available</li> <li>Not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> <li>ACCIDENTAL RELEASE MEASURES</li> </ul>
	b. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or th soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing

PolyOne.

# MATERIAL SAFETY DATA SHEET **D3308 DARK GREEN**

sion Date 06/19/2007			Print D	Page 3 ate 11/29/
	Р	ume condensates may contain eriodically clean hoods, ducts ccumulation of these material	, and other surfaces to mi	
Storage		eep containers dry and tightly nd contamination. Store in a		absorption
8. H	XPOSURE	CONTROLS / PERSONAL	PROTECTION	
Respiratory protection	: N	o personal respiratory protect	ive equipment normally r	equired.
Eye/Face Protection	: S	afety glasses with side-shield	S	
Hand protection	: P	rotective gloves		
Skin and body protection	: L	ong sleeved clothing		
Additional Protective Measures	: S	afety shoes		
General Hygiene Considerations		andle in accordance with goo Vash hands before breaks and		afety practic
Engineering measures		leat only in areas with approp ppropriate exhaust ventilation		Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	<b>.</b>
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	List:
		I LL.		
	15 mg/m3	PEL:	Total dust.	OSHA Z
	10 mg/m3	PEL: Time Weighted Average (TWA):	Total dust.	OSHA Z OSHA Z MX OEL
	-	PEL: Time Weighted Average	Total dust.	OSHA Z OSHA Z MX OEL
	10 mg/m3 20 mg/m3	PEL: Time Weighted Average (TWA): Short Term Exposure Limit		OSHA Z OSHA Z MX OEL
Form	10 mg/m3 20 mg/m3 9. PHYSIC	PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO	OPERTIES	OSHA Z OSHA Z MX OEL
Form	10 mg/m3 20 mg/m3 9. PHYSIC : liquio	PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRODUCTION d Evapo	OPERTIES Dration rate : Not	OSHA ZI OSHA ZI MX OEL MX OEL established
Appearance	10 mg/m3 20 mg/m3 9. PHYSIC : liquid : Visco	PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapo ous, liquid Speci	OPERTIES Dration rate : Not fic Gravity : Not	OSHA ZI OSHA ZI MX OEL MX OEL established determined
Appearance Color	10 mg/m3 20 mg/m3 9. PHYSIC : liquid : Visco : GRE	PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PR d Evapo ous, liquid Speci EN Bulk	OPERTIES Diration rate : Not fic Gravity : Not density : Not	OSHA Z OSHA Z MX OEL MX OEL established determined applicable
Appearance Color Odour	10 mg/m3 20 mg/m3 9. PHYSIC : liquid : Viscc : GRE : Very	PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapo ous, liquid Speci EN Bulk faint Vapo	OPERTIES Diration rate : Not fic Gravity : Not density : Not ur pressure : Not	OSHA Z OSHA Z MX OEL MX OEL MX OEL established determined applicable determined
Appearance Color Odour Melting point/range	10 mg/m3 20 mg/m3 9. PHYSIC : liquid : Visco : GRE : Very : Not a	PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PR d Evapo ous, liquid Speci EN Bulk faint Vapo applicable Vapo	OPERTIES Diration rate : Not fic Gravity : Not density : Not ur pressure : Not ur density : Not	OSHA Z OSHA Z MX OEL MX OEL MX OEL established determined applicable determined determined
Appearance Color Odour	10 mg/m3 20 mg/m3 9. PHYSIC : liquid : Visco : GRE : Very : Not a : Not a	PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapo ous, liquid Speci EN Bulk faint Vapo	OPERTIES Diration rate : Not fic Gravity : Not density : Not ur pressure : Not ur density : Not	OSHA ZI OSHA ZI MX OEL MX OEL established determined applicable determined

Stability

: Stable.

# MATERIAL SAFETY DATA SHEET **D3308 DARK GREEN**

Version Number 1.2 Revision Date 06/19/2007 Page 4 of 6 Print Date 11/29/2011

Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

### **12. ECOLOGICAL INFORMATION**

Fersistence and degradability       Not readily biodegradable.         Environmental Toxicity       : Environmental toxicity has not been established for this mixture as whole.         Bioaccumulation Potential       : No data available         Additional advice       : No data available		]
Environmental Toxicity : Environmental toxicity has not been established for this mixture as whole.		
Environmental Toxicity : Environmental toxicity has not been established for this mixture as		
reisistence and degradability . Not readily biodegradable.	a	
Persistence and degradability : Not readily biodegradable.		

Product: Where possible recycling is preferred to disposal or incineration. The<br/>generator of waste material has the responsibility for proper waste<br/>classification, transportation and disposal in accordance with<br/>applicable federal, state/provincial and local regulations.Contaminated packaging: Recycling is preferred when possible. The generator of waste material<br/>has the responsibility for proper waste classification, transportation<br/>and disposal in accordance with applicable federal, state/provincial<br/>and disposal in accordance with applicable federal, state/provincial<br/>and local regulations.

PolyOne.

## MATERIAL SAFETY DATA SHEET D3308 DARK GREEN

Version Number 1.2 Revision Date 06/19/2007 Page 5 of 6 Print Date 11/29/2011

		4. TRANSPORT INFO		1	
U.S. DOT Classification	:	Refer to specific regula	tion.		
ICAO/IATA (air)	:	Refer to specific regula	tion.		
IMO / IMDG (maritime)	:	Refer to specific regula	tion.		
	15	. REGULATORY INF	ORMATI	ON	
US Regulations:					
OSHA Status	:	Classified as hazardous	based on	components.	
TSCA Status	:	All components of this Inventory.	product ar	e listed on or exer	mpt from the TSC.
US. EPA CERCLA Hazardou	s Sub	stances (40 CFR 302)			
Not applicable					
California Proposition 65		Not applicable			
SARA Title III Section 302 E	xtrem	ely Hazardous Substance	e		
Unless specific chemicals are	identi	fied under this section, t	his product	is Not Applicabl	e under this regul
SARA Title III Section 313 To	oxic (	Chemicals:			
Unless specific chemicals are	identi	fied under this section, t	his product	is Not Applicabl	e under this regul
Canadian Regulations:					
National Pollutant Rele	ease I	ventory (NPRI)			
Chemical Name		CAS	-No.	Weight %	NPRI ID#
		1328	-53-6	0.10 - 1.00	71
Phthalocyanine green					I

<u>PolyOne</u>

# MATERIAL SAFETY DATA SHEET **D3308 DARK GREEN**

JUSU DANK OKEEN	
/ersion Number 1.2 Revision Date 06/19/2007	Page 6 of 6 Print Date 11/29/201
DSL	: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:	
Australia AICS	: Not determined
China IECS	: Not determined
Europe EINECS	: Not determined
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined
	16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.