

MATERIAL SAFETY DATA SHEET

PX-19301-C CLEAR PLASTISOL

Version Number 1.0 Revision Date 03/18/2003 Page 1 of 6 Print Date 11/10/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PX-19301-C CLEAR PLASTISOL
Product code	:	FO20004224
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

There are no known hazardous components above regulatory thresholds in this product.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

PX-19301-C CLEAR PLASTISOL

Version Number 1.0 Revision Date 03/18/2003 Page 2 of 6 Print Date 11/10/2011

	4. FIRST AID MEASURES	
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.	of
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.	
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If e irritation persists, seek medical attention.	;ye
Skin	: Wash off with soap and plenty of water. If skin irritation persists se medical attention.	ek
	5. FIRE-FIGHTING MEASURES	
Flash point	: No data available.	
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 No data available. No data available. Not applicable. Carbon dioxide blanket, dry powder, foam, Water spray. 	
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.	e
Unusual Fire/Explosion Hazards	: May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) und fire conditions.	er
	5. ACCIDENTAL RELEASE MEASURES	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.	ot
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid bind universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.	
	7. HANDLING AND STORAGE	
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize	



MATERIAL SAFETY DATA SHEET

PX-19301-C CLEAR PLASTISOL

		Print Date	Page 3 11/10/2
	accumulation of the	se materials.	
Storage		and tightly closed to avoid moisture abso Store in a cool dry place.	rption
8. EXF	OSURE CONTROLS / P	ERSONAL PROTECTION	
Respiratory protection	: Under normal hand	ling conditions a respirator may not be req	uired.
Eye/Face Protection	: Safety glasses with	side-shields.	
Hand protection	: Protective gloves.		
Skin and body protection	: Long sleeved clothi	ng.	
Additional Protective Measures	: Safety shoes.		
General Hygiene Considerations		ce with good industrial hygiene and safety preaks and at the end of workday.	practice
Engineering measures		vith appropriate exhaust ventilation. Proviventilation at machinery.	ide
		tory thresholds in this product.	
9	PHYSICAL AND CHEM	IICAL PROPERTIES	
			mined cable. mined mined
9 Form Appearance Color Odor Melting point/range Boiling Point:	 PHYSICAL AND CHEM Liquid Viscous, Liquid TRANSPARENT Very faint Not applicable Not applicable 	IICAL PROPERTIES Evaporation rate : Not estab Specific Gravity : Not deterned Bulk density : Not applie Vapor pressure : Not deterned Vapor density : Not deterned pH : Not applie	mined cable. mined mined
9 Form Appearance Color Odor Melting point/range Boiling Point:	 PHYSICAL AND CHEM Liquid Viscous, Liquid TRANSPARENT Very faint Not applicable Not applicable Immiscible 	IICAL PROPERTIES Evaporation rate : Not estab Specific Gravity : Not deterned Bulk density : Not applie Vapor pressure : Not deterned Vapor density : Not deterned pH : Not applie	mined cable. mined mined
9. Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	 PHYSICAL AND CHEM Liquid Viscous, Liquid TRANSPARENT Very faint Not applicable Not applicable Immiscible 10. STABILITY AND	IICAL PROPERTIES Evaporation rate : Not estab Specific Gravity : Not deterned Bulk density : Not applie Vapor pressure : Not deterned Vapor density : Not deterned pH : Not applie	mined cable. mined mined
9 Form Appearance Color Odor Melting point/range Boiling Point: Water solubility Stability	PHYSICAL AND CHEM : Liquid : Viscous, Liquid : TRANSPARENT : Very faint : Not applicable : Not applicable : Immiscible 10. STABILITY AND : Stable. : Will not occur.	IICAL PROPERTIES Evaporation rate : Not estab Specific Gravity : Not deter Bulk density : Not applie Vapor pressure : Not deter Vapor density : Not deter pH : Not applie OREACTIVITY : Not avoid t	mined cable. mined mined cable.
9 Form Appearance Color Odor Melting point/range Boiling Point: Water solubility Stability Hazardous Polymerization	 PHYSICAL AND CHEM Liquid Viscous, Liquid TRANSPARENT Very faint Not applicable Not applicable Immiscible 10. STABILITY AND Stable. Will not occur. Keep away from ox decomposition, do not see the second sec	IICAL PROPERTIES Evaporation rate : Not estab Specific Gravity : Not deter Bulk density : Not applie Vapor pressure : Not deter Vapor density : Not deter pH : Not applie OREACTIVITY : Not avoid t	mined cable. mined mined cable.

Version Number 1.0 Revision Date 03/18/2003



Page 4 of 6 Print Date 11/10/2011

MATERIAL SAFETY DATA SHEET

PX-19301-C CLEAR PLASTISOL

products	(NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).				
11. TOXICOLOGICAL INFORMATION					
There are no known hazardous	components above regulatory thresholds in this product.				
	12. ECOLOGICAL INFORMATION				
Persistence and degradability	: Not readily biodegradable.				
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.				
Bioaccumulation Potential	: No data available.				
Additional advice	: No data available.				
	13. DISPOSAL CONSIDERATIONS				
Product	: Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				
	14. TRANSPORT INFORMATION				
U.S. DOT Classification	: Refer to specific regulation.				
ΙCAO/ΙΑΤΑ	: Refer to specific regulation.				
IMO / IMDG	: Refer to specific regulation.				
	15. REGULATORY INFORMATION				
US Regulations:					
OSHA Status	: There are no known hazardous components above regulatory thresholds in this product.				
	: All components of this product are listed on or exempt from the TSCA				



MATERIAL SAFETY DATA SHEET

PX-19301-C CLEAR PLASTISOL

Version Number 1.0 Revision Date 03/18/2003 Page 5 of 6 Print Date 11/10/2011

		Inventory.				
US. EPA CERCLA Hazardous S	US. EPA CERCLA Hazardous Substances (40 CFR 302)					
Not applicable						
California Proposition 65	:	WARNING! This product contains a chemical known to the State of California to cause cancer.				
SARA Title III Section 302 Extr	em	ely Hazardous Substance				
Not applicable						
SARA Title III Section 313 Tox	SARA Title III Section 313 Toxic Chemicals:					
	N	ot applicable				
Considian Pagulations:						
Canadian Regulations:						
WHMIS Classification	:	Not controlled.				
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.				
National Inventories:						
Australia AICS	:	Listed.				
China IECS	:	Not determined.				
Europe EINECS	:	Not determined.				
Japan ENCS	:	Not determined.				
Korea KECI	:	Not determined.				
Philippines PICCS	:	Listed.				
		16 OTHER INCORMATION				

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.



MATERIAL SAFETY DATA SHEET

PX-19301-C CLEAR PLASTISOL

Version Number 1.0 Revision Date 03/18/2003 Page 6 of 6 Print Date 11/10/2011