# MATERIAL SAFETY DATA SHEET **PX-21445-B WHITE PLASTISOL**

Version Number 1.0 Revision Date 06/09/2003 Page 1 of 6 Print Date 11/11/2011

## 1. PRODUCT AND COMPANY IDENTIFICATION

## POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PX-21445-B WHITE PLASTISOL
Product code	:	FO20005204
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Quartz	14808-60-7	0.1 - 1
Calcium carbonate	471-34-1	10 - 30

### **3. HAZARDS IDENTIFICATION**

### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

## POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

<u>PolyOne</u>

# MATERIAL SAFETY DATA SHEET PX-21445-B WHITE PLASTISOL

Version Number 1.0 Revision Date 06/09/2003 Page 2 of 6 Print Date 11/11/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available.
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>No data available.</li> <li>No data available.</li> <li>Not applicable.</li> <li>Carbon dioxide blanket, dry powder, foam, Water spray.</li> </ul>
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing



# MATERIAL SAFETY DATA SHEET PX-21445-B WHITE PLASTISOL

Version Number 1.0 Revision Date 06/09/2003 Page 3 of 6 Print Date 11/11/2011

Storage	:	fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials. Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.
8. EXP	OSUI	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	Under normal handling conditions a respirator may not be required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Calcium carbonate	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	ACGIH
Quartz	0.05 mg/m3	Time Weighted Average (TWA):	Respirable dust.	ACGIH
Quartz	0.05 mg/m3	Time Weighted Average (TWA):		ACGIH
Quartz	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odor Melting point/range : Liquid
: Viscous, Liquid
: WHITE
: Very faint
: Not applicable

Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density Not establishedNot determinedNot applicable.

Not determinedNot determined

3/6



# MATERIAL SAFETY DATA SHEET PX-21445-B WHITE PLASTISOL

Version Number 1.0 Revision Date 06/09/2003 Page 4 of 6 Print Date 11/11/2011

Boiling Point::Water solubility:		ot applicable miscible	рН	: Not applicable.	
	10	). STABILITY AND RE	ACTIVITY		
Stability	:	Stable.			
Hazardous Polymerization	:	Will not occur.			
Conditions to avoid	:	Keep away from oxidizide decomposition, do not o		ame. To avoid thermal	
Incompatible Materials	:	Incompatible with stron with acetal homopolyme	0 0	6	
Hazardous decomposition products	:	Carbon dioxide (CO2), (NOx), hydrogen chlorid smoke are all possible. degradation. As a gener after one hour at 177 °C and within 5 minutes at	de (HCl), other hazarde Prolonged heating may ral rule of thumb, degra (350 °F), after 10 min	dous materials, and ay result in product radation begins to occur	

## **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
14808-60-7	Quartz	Systemic effects	Eyes, Respiratory system.
471-34-1	Calcium carbonate	Irritant	Eyes, Skin.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
471-34-1	Calcium carbonate	Oral LD50	6,450 mg/kg	rat

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No. Chemical Name OSHA IARC NTP				
	Chemical Name	OSHA	IARC	

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

PolvOne.

# MATERIAL SAFETY DATA SHEET PX-21445-B WHITE PLASTISOL

Version Number 1.0 Revision Date 06/09/2003 Page 5 of 6 Print Date 11/11/2011

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

## Additional Health Hazard Information:

**Quartz** 14808-60-7 This material in its free releasable form may cause respiratory tract irritation, and possibly silicosis which is a scarring of the lungs.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
<b>Bioaccumulation Potential</b>	: No data available.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA	: Refer to specific regulation.
IMO / IMDG	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA

PolyOne.

# MATERIAL SAFETY DATA SHEET **PX-21445-B WHITE PLASTISOL**

Version Number 1.0 Revision Date 06/09/2003 Page 6 of 6 Print Date 11/11/2011

US. EPA CERCLA Hazardous	Sub	stances (40 CFR 302)
Not applicable		
California Proposition 65	:	WARNING! This product contains a chemical known to the State of California to cause cancer.
SARA Title III Section 302 Extra	rem	ely Hazardous Substance
Not applicable		
SARA Title III Section 313 Tox	cic C	Chemicals:
Not applicable Canadian Regulations:		
National Pollutant Release	se Iı	nventory (NPRI)
Not applicable		
WHMIS Classification	:	D2A
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:		
Australia AICS	:	Not determined.
China IECS	:	Not determined.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Not determined.
Philippines PICCS	:	Not determined.
Japan ENCS Korea KECI	:	Not determined. Not determined.

## **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.