

### MATERIAL SAFETY DATA SHEET

### PX-10598-E SINAGE

Version Number 1.0 Revision Date 06/30/2003

Page 1 of 6 Print Date 11/11/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

### POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Energency telephone	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PX-10598-E SINAGE
Product code	:	FO20005525
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Antimony trioxide	1309-64-4	1 - 5

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



## MATERIAL SAFETY DATA SHEET

## PX-10598-E SINAGE

Version Number 1.0 Revision Date 06/30/2003 Page 2 of 6 Print Date 11/11/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available.
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>No data available.</li> <li>No data available.</li> <li>Not applicable.</li> <li>Carbon dioxide blanket, dry powder, foam, water spray.</li> </ul>
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing



# MATERIAL SAFETY DATA SHEET **PX-10598-E SINAGE**

sion Number 1.0 ision Date 06/30/2003				Print D	Page 3 Date 11/11/2
	Р	ume condensates m eriodically clean ho ccumulation of thes	ods, ducts, and o		
Storage		Leep containers dry nd contamination.			e absorption
8. F	XPOSURE	CONTROLS / PE	RSONAL PRO	TECTION	
Respiratory protection	: T	Inder normal handli	ng conditions a re	espirator may not	be required.
Eye/Face Protection	: S	afety glasses with s	ide-shields.		
Hand protection	: P	rotective gloves.			
Skin and body protection	: L	ong sleeved clothin	ıg.		
Additional Protective Measures	: S	: Safety shoes.			
General Hygiene Considerations		landle in accordance Vash hands before b			safety practice
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)					
Components	Value	Exposure ti	ime H	Exposure type	List:
Antimony trioxide	0.5 mg/m3	PEL:		as Sb	OSHA Z1
	9. PHYSI	CAL AND CHEM	ICAL PROPER	LIES	
<b>F</b> errar	T.	. 1			
Form Appearance	: Liqu	ous, Liquid	Evaporation Specific Gra		t established t determined
Color	: WH	-	Bulk density		t applicable.
Odor	: Very		Vapor pressu		t determined
Melting point/range	•	applicable	Vapor densit		t determined
Boiling Point:		applicable	pH	•	t applicable.
Water solubility	: Imm		pm	. 100	applicable.
	10. 9	STABILITY AND	REACTIVITY		
Stability	: S	table.			
Hazardous Polymerization	n : V	Vill not occur.			
Thazardous i orymetrization				onen floma To	
Conditions to avoid		keep away from oxi ecomposition, do n		open name. To a	avoid thermai



# MATERIAL SAFETY DATA SHEET **PX-10598-E SINAGE**

Version Number 1.0 Revision Date 06/30/2003

Page 4 of 6 Print Date 11/11/2011

Incompatible Materials	:	Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1309-64-4	Antimony trioxide	Systemic effects	Eyes, Respiratory system.
		sensitizer	Skin.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1309-64-4	Antimony trioxide	Oral LD50	> 34,600 mg/kg	rat

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1309-64-4	Antimony trioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

### Additional Health Hazard Information:

Antimony trioxide 1309-64-4 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).



## MATERIAL SAFETY DATA SHEET **PX-10598-E SINAGE**

Version Number 1.0 Revision Date 06/30/2003 Page 5 of 6 Print Date 11/11/2011

Persistence and degradability	y : Not rea	: Not readily biodegradable.				
Environmental Toxicity		: Environmental toxicity has not been established for this mixture as a whole.				
Bioaccumulation Potential	: No dat	: No data available.				
Additional advice	: No dat	: No data available.				
	13. DISP	OSAL CONSIDE	CRATIONS			
Product	genera classifi	tor of waste mater cation, transporta	g is preferred to dispo- ial has the responsibil- tion and disposal in ac provincial and local re	ity for proper waste cordance with		
Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.						
	14. TRA	NSPORT INFOR	RMATION			
U.S. DOT Classification	: Refer t	o specific regulati	on.			
ICAO/IATA	: Refer t	o specific regulati	on.			
IMO / IMDG	: Refer t	o specific regulati	on.			
	15. REGU	LATORY INFO	RMATION			
US Regulations:						
OSHA Status	: Classif	ied as hazardous t	based on components.			
TSCA Status	: All co Invento		roduct are listed on or	exempt from the TSC.		
US. EPA CERCLA Hazardo	us Substances (	(40 CFR 302)				
Chemical Name	CAS-No.	% in Product	RQ for component	RQ for Mixture/Product		
Antimony trioxide	1309-64-4	1.3566	1,000 lbs	73,714 LB		



## MATERIAL SAFETY DATA SHEET

## PX-10598-E SINAGE

Version Number 1.0 Revision Date 06/30/2003 Page 6 of 6 Print Date 11/11/2011

California Proposition : WARNING! This product contains a chemical known to the State of California to cause cancer.

SARA Title III Section 302 Extremely Hazardous Substance

Not applicable

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
ANTIMONY COMPOUNDS	1309-64-4	1.35

Canadian Regulations:

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

C.	AS-No.	
13	09-64-4	

DSL

: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	: Listed.
China IECS	: Not determined.
Europe EINECS	: Not determined.
Japan ENCS	: Not determined.
Korea KECI	: Not determined.
Philippines PICCS	: Listed.

### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.