

#### MATERIAL SAFETY DATA SHEET

# V1764A BLACK SELF BOND (IS)

Version Number 1.0 Page 1 of 7
Revision Date 08/05/2003 Print Date 11/11/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION

2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY : Product Stewardship, (314) 771-1800

TELEPHONE

Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure

number or accident).

Product name : V1764A BLACK SELF BOND (IS)

Product code : FO20005874 Chemical Name : Mixture CAS-No. : Mixture

Product Use : Industrial Applications

#### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

| Components                            | CAS-No.    | Weight % |
|---------------------------------------|------------|----------|
| Bisphenol A - Epichlorohydrin polymer | 25068-38-6 | 1 - 5    |
| 1-Cyanoguanidine                      | 461-58-5   | 1 - 5    |
| Carbon black                          | 1333-86-4  | 0.1 - 1  |

### 3. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Inhalation, Skin contact, Ingestion

Acute exposure

Inhalation : Resin particles, like other inert materials, can be mechanically irritating.

Ingestion : May be harmful if swallowed.

Eyes : Particulates, like other inert materials can be mechanically irritating.

Skin : Experience shows no unusual dermatitis hazard from routine handling.

**Chronic exposure** : Refer to Section 11 for Toxicological Information.



#### MATERIAL SAFETY DATA SHEET

# V1764A BLACK SELF BOND (IS)

 Version Number 1.0
 Page 2 of 7

 Revision Date 08/05/2003
 Print Date 11/11/2011

Medical Conditions Aggravated by Exposure: : None known.

4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of fumes from

overheating or combustion. When symptoms persist or in all cases of

doubt seek medical advice.

Ingestion : Do not induce vomiting without medical advice. When symptoms

persist or in all cases of doubt seek medical advice.

Eyes : Rinse immediately with plenty of water, also under the eyelids, for at

least 15 minutes. If eye irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists seek

medical attention.

**5. FIRE-FIGHTING MEASURES** 

Flash point : Not applicable

Flammable Limits

Upper explosion limit : Not applicable Lower explosion limit : Not applicable Autoignition temperature : Not relevant

Suitable extinguishing media : Carbon dioxide blanket, water spray, dry powder, foam.

Special Fire Fighting

Procedures

: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne

contaminants.

Unusual Fire/Explosion

Hazards

May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under

fire conditions.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear appropriate personal protection during cleanup, such as

impervious gloves, boots and coveralls.

Environmental precautions : Should not be released into the environment. The product should not

be allowed to enter drains, water courses or the soil.

Methods for cleaning up : Clean up promptly by sweeping or vacuum. Package all material in

plastic, cardboard or metal containers for disposal. Refer to Section 13

of this MSDS for proper disposal methods.

7. HANDLING AND STORAGE

Handling : Take measures to prevent the build up of electrostatic charge. Heat

only in areas with appropriate exhaust ventilation. Processing fume



#### MATERIAL SAFETY DATA SHEET

# V1764A BLACK SELF BOND (IS)

Version Number 1.0 Page 3 of 7
Revision Date 08/05/2003 Print Date 11/11/2011

condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of

these materials.

Storage : Keep containers dry and tightly closed to avoid moisture absorption

and contamination. Keep in a dry, cool place.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection : No personal respiratory protective equipment normally required. If

dusty conditions occur wear appropriate respiratory protection.

Eye/Face Protection : Safety glasses with side-shields.

Hand protection : Protective gloves.

Skin and body protection : Long sleeved clothing.

Additional Protective

Measures

Safety shoes.

General Hygiene

Considerations

Handle in accordance with good industrial hygiene and safety practice.

Wash hands before breaks and at the end of workday.

Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide

appropriate exhaust ventilation at machinery.

Exposure limit(s)

| Components             | Value     | Exposure time         | Exposure type         | List:   |
|------------------------|-----------|-----------------------|-----------------------|---------|
| Carbon black 3.5 mg/m3 |           | Time Weighted Average | Total dust. as carbon | ACGIH   |
|                        |           | (TWA):                | black                 |         |
| Carbon black           | 3.5 mg/m3 | PEL:                  | Total dust. as carbon | OSHA Z1 |
|                        |           |                       | black                 |         |

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form : Solid Evaporation rate : Not applicable. powder, granular Appearance Specific Gravity Not determined Color : BLACK Bulk density Not determined Odor : Very faint Vapor pressure : Not applicable : Not determined : Not applicable Melting point/range Vapor density **Boiling Point:** : Not applicable pН : Not applicable

Water solubility : Insoluble

## 10. STABILITY AND REACTIVITY

Stability : Stable.



#### MATERIAL SAFETY DATA SHEET

# V1764A BLACK SELF BOND (IS)

Version Number 1.0 Page 4 of 7
Revision Date 08/05/2003 Print Date 11/11/2011

Hazardous Polymerization : Will not occur.

Conditions to avoid : To avoid thermal decomposition, do not overheat. Keep away from

oxidizing agents and open flame.

Incompatible Materials : Incompatible with strong acids and oxidizing agents. Avoid contact

with acetal homopolymers and acetal copolymers during processing.

Hazardous decomposition

products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes

or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon

monoxide and hydrogen chloride.

## 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

| CAS-No.    | Chemical Name           | Effect           | Target Organ              |
|------------|-------------------------|------------------|---------------------------|
| 25068-38-6 | Bisphenol A -           | Irritant         | Skin.                     |
|            | Epichlorohydrin polymer |                  |                           |
|            |                         | sensitizer       | Skin.                     |
| 461-58-5   | 1-Cyanoguanidine        | Systemic effects | blood and blood forming   |
|            |                         |                  | system.                   |
| 1333-86-4  | Carbon black            | Systemic effects | Eyes, Respiratory system. |

## LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

| CAS-No.    | Chemical Name           | Route       | Value          | Species |
|------------|-------------------------|-------------|----------------|---------|
| 25068-38-6 | Bisphenol A -           | Oral LD50   | 11,400 mg/kg   | rat     |
|            | Epichlorohydrin polymer | Dermal LD50 | > 6,000 mg/kg  | rabbit  |
| 461-58-5   | 1-Cyanoguanidine        | Oral LD50   | > 10 gm/kg     | mouse   |
| 1333-86-4  | Carbon black            | Oral LD50   | > 15,400 mg/kg | rat     |
|            |                         | Dermal LD50 | > 3 gm/kg      | rabbit  |

#### Carcinogenicity:

This product contains the following components which, in their pure form, have the following carcinogenicity data:

| CAS-No.   | Chemical Name | OSHA | IARC | NTP |
|-----------|---------------|------|------|-----|
| 1333-86-4 | Carbon black  | no   | 2B   | no  |

#### IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.



#### MATERIAL SAFETY DATA SHEET

# V1764A BLACK SELF BOND (IS)

 Version Number 1.0
 Page 5 of 7

 Revision Date 08/05/2003
 Print Date 11/11/2011

- 2A The component is probably carcinogenic to humans.
- 2B The component is possibly carcinogenic to humans.

#### NTP Carcinogen Classifications:

- 1 The component is known to be a human carcinogen.
- 2 The component is reasonably anticipated to be a human carcinogen.

#### **Additional Health Hazard Information:**

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

#### 12. ECOLOGICAL INFORMATION

Persistence and degradability : Not readily biodegradable.

Environmental Toxicity : Adverse ecological impact is not known or expected under normal use.

Bioaccumulation Potential : No data available.

Additional advice : No data available.

#### 13. DISPOSAL CONSIDERATIONS

Product : Where possible, recycling is preferred to disposal or incineration. The

generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste material

has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial

and local regulations.

#### 14. TRANSPORT INFORMATION

U.S. DOT Classification : Not regulated for transportation.

ICAO/IATA : Not regulated for transportation.

IMO / IMDG : Not regulated for transportation.



#### MATERIAL SAFETY DATA SHEET

# V1764A BLACK SELF BOND (IS)

Version Number 1.0 Page 6 of 7
Revision Date 08/05/2003 Print Date 11/11/2011

#### 15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on or exempt from the TSCA

Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

| Chemical Name  | CAS-No. | % in Product | RQ for component | RQ for          |
|----------------|---------|--------------|------------------|-----------------|
|                |         |              |                  | Mixture/Product |
| Vinyl chloride | 75-01-4 | 0.0007       | 001 lbs          | 142,857 LB      |
| monomer        |         |              |                  |                 |

California Proposition : WARNING! This product contains a chemical known to the State of

65 California to cause cancer.

SARA Title III Section 302 Extremely Hazardous Substance

Not applicable

SARA Title III Section 313 Toxic Chemicals:

Not applicable Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Not applicable

WHMIS Classification : D2A

DSL : All of the components of this product are listed on the Canadian

Inventories or are exempt. However, at least one component of this product is on the Canadian Non-Domestic Substances List (NDSL).

Quantity use in Canada is restricted by regulations.

National Inventories:

Australia AICS : Listed.

China IECS : Not determined.

Europe EINECS : Not determined.



MATERIAL SAFETY DATA SHEET

# V1764A BLACK SELF BOND (IS)

Version Number 1.0 Page 7 of 7
Revision Date 08/05/2003 Print Date 11/11/2011

Japan ENCS : Not determined.

Korea KECI : Not determined.

Philippines PICCS : Not determined.

# 16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.