## MATERIAL SAFETY DATA SHEET CX-6245-A SILVER/BLUE ICE PLASTISOL

Version Number 1.2 Revision Date 08/31/2007 Page 1 of 9 Print Date 11/30/2011

#### **1. PRODUCT AND COMPANY IDENTIFICATION**

#### POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone:Emergency telephone:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	CX-6245-A SILVER/BLUE ICE PLASTISOL
Product code :	FO20005894
Chemical Name :	Mixture
CAS-No. :	Mixture
Product Use :	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Cobalt aluminate blue spinel (C.I. Pigment	1345-16-0	0.1 - 1
Blue 28)		
Di(2-ethylhexyl)phthalate	117-81-7	0.1 - 1
Quartz	14808-60-7	0.1 - 1
Naphthalene	91-20-3	0.1 - 1
Silica, amorphous	7631-86-9	1 - 5
Silica, amorphous, diatomaceous earth	68855-54-9	1 - 5
Silica, cristobalite	14464-46-1	1 - 5
Titanium dioxide	13463-67-7	10 - 30

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.



# MATERIAL SAFETY DATA SHEET CX-6245-A SILVER/BLUE ICE PLASTISOL

ion Number 1.2 sion Date 08/31/2007	Page 2 Print Date 11/30/2
-	
Eyes Skin	<ul><li>May cause eye/skin irritation.</li><li>Experience shows no unusual dermatitis hazard from routine handling</li></ul>
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits	
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Autoignition temperature Suitable extinguishing media	<ul><li>Not applicable</li><li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li></ul>
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	<ul> <li>May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or th soil. Should not be released into the environment.



# MATERIAL SAFETY DATA SHEET CX-6245-A SILVER/BLUE ICE PLASTISOL

rsion Number 1.2 vision Date 08/31/2007	Pag Print Date 11/	ge 3 of /30/201
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid bi universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for pro disposal methods.	
	7. HANDLING AND STORAGE	
Handling	: Heat only in areas with appropriate exhaust ventilation. Processi fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.	ing
Storage	: Keep containers dry and tightly closed to avoid moisture absorpt and contamination. Store in a cool dry place.	ion
8. EXF	SURE CONTROLS / PERSONAL PROTECTION	
Respiratory protection	: No personal respiratory protective equipment normally required.	
Eye/Face Protection	: Safety glasses with side-shields	
Hand protection	: Protective gloves	
Skin and body protection	: Long sleeved clothing	
Additional Protective Measures	: Safety shoes	
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety pra Wash hands before breaks and at the end of workday.	ctice.
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.	
Exposure limit(s)		

PolyOne.

## MATERIAL SAFETY DATA SHEET CX-6245-A SILVER/BLUE ICE PLASTISOL

Version Number 1.2 Revision Date 08/31/2007 Page 4 of 9 Print Date 11/30/2011

Components	Value	Exposure time	Exposure type	List:
Cobalt aluminate blue	0.02	Time Weighted Average	as Co	ACGIH
spinel (C.I. Pigment	mg/m3	(TWA):		
Blue 28)				
Di(2-ethylhexyl)phthal	5 mg/m3	Time Weighted Average		ACGIH
ate		(TWA):		
	5 mg/m3	PEL:		OSHA Z1
	5 mg/m3	Time Weighted Average		MX OEL
		(TWA):		
	10 mg/m3	Short Term Exposure Limit		MX OEL
2		(STEL):		
Quartz	0.025	Time Weighted Average	Respirable fraction.	ACGIH
	mg/m3	(TWA):		
	0.1 mg/m3	Time Weighted Average	Respirable.	Z3
		(TWA):	<b>T</b> 11	72
	0.3 mg/m3	Time Weighted Average	Total dust.	Z3
	0.1 / 2	(TWA):		NUCCEI
	0.1 mg/m3	Time Weighted Average		MX OEL
0'1'	0.0	(TWA):		72
Silica, amorphous	0.8 mg/m3	Time Weighted Average		Z3
	$10 m a/m^2$	(TWA): Time Weighted Average	Inhalable particulate.	MX OEL
	10 mg/m3	(TWA):	minarable particulate.	MA OEL
	3 mg/m3	Time Weighted Average	Respirable dust.	MX OEL
	5 mg/m5	(TWA):	Respirable dust.	MA OEL
Silica, amorphous,	0.8 mg/m3	Time Weighted Average		Z3
diatomaceous earth	0.8 mg/m3	(TWA):		23
diatomaceous cartin	10 mg/m3	Time Weighted Average	Inhalable particulate.	MX OEL
	10 119 113	(TWA):	minutable particulate.	MIX OLL
	3 mg/m3	Time Weighted Average	Respirable dust.	MX OEL
	e ing ine	(TWA):		
Silica, cristobalite	0.025	Time Weighted Average	Respirable fraction.	ACGIH
	mg/m3	(TWA):		
	0.05	Time Weighted Average	Respirable.	Z3
	mg/m3	(TWA):	I	
	0.15	Time Weighted Average	Total dust.	Z3
	mg/m3	(TWA):		
	0.05	Time Weighted Average		MX OEL
	mg/m3	(TWA):		
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
	U U	(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average	as Ti	MX OEL
	C C	(TWA):		
	20 mg/m3	Short Term Exposure Limit	as Ti	MX OEL
	U	(STEL):		
Naphthalene	10 ppm 52	Time Weighted Average	Vapor.	ACGIH
	mg/m3	(TWA):	-	



## MATERIAL SAFETY DATA SHEET CX-6245-A SILVER/BLUE ICE PLASTISOL

#### Version Number 1.2 Revision Date 08/31/2007

Page 5 of 9 Print Date 11/30/2011

	15 ppm 79 mg/m3	Short Term Exposure L (STEL):	imit Vapor.	ACGIH
	10 ppm 50 mg/m3	PEL:	Vapor.	OSHA Z1
	9. PHYSIC	CAL AND CHEMICAL	PROPERTIES	
Form Appearance Color Odour Melting point/range Boiling Point: Water solubility	: BLU : Very : Not a	ous, liquid S E E 7 faint V applicable V applicable p	Evaporation rate:Decific Gravity:Bulk density:Vapour pressure:Vapour density:H:	Not established Not determined Not applicable Not determined Not determined Not applicable
	10. 8	STABILITY AND REA	CTIVITY	
Stability	: S	table.		
Hazardous Polymerization	n : W	Vill not occur.		
Conditions to avoid		: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.		
Incompatible Materials			acids and oxidizing agent and acetal copolymers d	
Hazardous decomposition products	(1 sı dı at	NOx), hydrogen chloride moke are all possible. Pr egradation. As a general	rbon monoxide (CO), oxi (HCl), other hazardous n olonged heating may resu rule of thumb, degradatio (350 °F), after 10 minutes a (2 °C (450 °F).	naterials, and alt in product on begins to occur

**11. TOXICOLOGICAL INFORMATION** 

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1345-16-0	Cobalt aluminate blue spinel (C.I. Pigment Blue 28)	Irritant	Eyes, Skin, Respiratory system.
		sensitizer	Skin.
117-81-7	Di(2-ethylhexyl)phthalate	Systemic effects	Eyes, Respiratory system, Liver, central nervous system (CNS), Skin, digestive system.



## MATERIAL SAFETY DATA SHEET CX-6245-A SILVER/BLUE ICE PLASTISOL

Version Number 1.2 Revision Date 08/31/2007 Page 6 of 9 Print Date 11/30/2011

14808-60-7	Quartz	Systemic effects	Eyes, Respiratory system.
91-20-3	Naphthalene	Irritant	Eyes.
		Systemic effects	Eyes, Respiratory system, central nervous system (CNS).
		Toxic	Refer to LC50 / LD50 Data on MSDS
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
68855-54-9	Silica, amorphous, diatomaceous earth	Irritant	Eyes, Skin, Respiratory system.
14464-46-1	Silica, cristobalite	Systemic effects	Respiratory system.
		Irritant	Eyes, Skin, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
117-81-7	Di(2-ethylhexyl)phthalate	Oral LD50	30 gm/kg	rat
		Dermal LD50	25 gm/kg	rabbit
91-20-3	Naphthalene	LC50	> 340 mg/m3	rat
		Oral LD50	490 mg/kg	rat
		Dermal LD50	> 20 gm/kg	rabbit
7631-86-9	Silica, amorphous	Oral	15,000	mouserat
		LD50Oral	mg/kg22,500	
		LD50	mg/kg	

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1345-16-0	Cobalt aluminate blue spinel (C.I. Pigment Blue 28)	no	2B	no
14808-60-7	Quartz	no	1	no
91-20-3	Naphthalene	no	2B	no
14464-46-1	Silica, cristobalite	no	1	no
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

#### Additional Health Hazard Information:

#### MATERIAL SAFETY DATA SHEET CX-6245-A SILVER/BLUE ICE PLASTISOL

Version Number 1.2 Revision Date 08/31/2007 Page 7 of 9 Print Date 11/30/2011

Di(2-ethylhexyl)phthalate 117-81-7 There is sufficient evidence for the carcinogenicity of di (2-ethylhexyl) phthalate in experimental animals. Administered in the feed this chemical caused an increase incidence of liver cancer in male and female rats and mice. The relevance of this finding to humans is uncertain.

#### Additional Health Hazard Information:

Quartz 14808-60-7 This material in its free releasable form may cause respiratory tract irritation. Long-term exposure may cause coughing, chest pain, diminished chest expansion and possibly silicosis, which is a scarring of the lungs.

#### Additional Health Hazard Information:

Silica, cristobalite 14464-46-1 This material in its free releasable form may cause respiratory tract irritation. Long-term exposure may cause coughing, chest pain, diminished chest expansion and possibly silicosis, which is a scarring of the lungs.

Persistence and degradability	: Not readily biodegradable.	
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.	
Bioaccumulation Potential	: No data available	
Additional advice	: No data available	
	13. DISPOSAL CONSIDERATIONS	
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.	
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.	
	14. TRANSPORT INFORMATION	
U.S. DOT Classification	: Refer to specific regulation.	
ICAO/IATA (air)	: Refer to specific regulation.	
IMO / IMDG (maritime)	: Refer to specific regulation.	
	15. REGULATORY INFORMATION	
US Regulations:		

7/9

PolyOne.

#### MATERIAL SAFETY DATA SHEET CX-6245-A SILVER/BLUE ICE PLASTISOL

sion Number 1.2			_	Page 8 of 9		
vision Date 08/31/2007			P	rint Date 11/30/2011		
OSHA Status : Classified as ha	azardous ba	ased on com	ponents.			
	s of this pr	oduct are lis	ted on or exe	mpt from the TSCA		
Inventory.						
US. EPA CERCLA Hazardous Substances (40 CFR	302)					
Not applicable						
California Proposition : WARNING! T	his produc	ct contains a	chemical kn	own to the State of		
65 California to ca						
SARA Title III Section 302 Extremely Hazardous Su	ubstance					
Sindi The missenen 302 Externely malaraous se	abbtanee					
Unless specific chamicals are identified under this as	action this	mucdulat in N	Jot Applicab	le under this regulation		
Unless specific chemicals are identified under this se	ection, this	product is r	Not Applicab	le under uns regulation		
SARA Title III Section 313 Toxic Chemicals:						
Unless specific chemicals are identified under this se	ection, this	product is N	Not Applicab	le under this regulation		
Chemical Name		CAS-No. Weight %				
COBALT COMPOUNDS		1345-16-0		0.10 - 1.00		
NAPHTHALENE				0 - 1.00		
INAFIIIIALENE		91-20-3	0.10	- 1.00		
Canadian Regulations:						
National Pollutant Release Inventory (NPRI)						
Chemical Name	CAS-No.		Weight %	NPRI ID#		
Cobalt aluminate blue spinel (C.I. Pigment Blue	1345-16-0		0.10 - 1.00	70		
28)						
Zinc	7440-66-6		0.10 - 1.00	231		
1,2,4-Trimethylbenzene	95-63-6		0.10 - 1.00	223		
Naphthalene	91-20-3		0.10 - 1.00	167		
WHMIS Classification : D2A						
WHMIS Ingredient Disclosure List						
WINNIS Ingreatent Disclosure List						
CAS-No.						
<u>CAS-NO.</u> 117-81-7						

7631-86-9 68855-54-9

<u>PolyOne</u>

## MATERIAL SAFETY DATA SHEET CX-6245-A SILVER/BLUE ICE PLASTISOL

Version Number 1.2 Revision Date 08/31/2007		Page 9 of 9 Print Date <i>11/30/2011</i>			
14464-46-1 95-63-6 DSL	:	All of the components of this product are listed on the Canadian Inventories or are exempt. However, at least one component of this product is on the Canadian Non-Domestic Substances List (NDSL). Quantity use in Canada is restricted by regulations.			
National Inventories:					
Australia AICS	:	Not determined			
China IECS	:	Not determined			
Europe EINECS	:	Not determined			
Japan ENCS	:	Not determined			
Korea KECI	:	Not determined			
Philippines PICCS	:	Not determined			
16. OTHER INFORMATION					

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.