# MATERIAL SAFETY DATA SHEET VBX3521E 30%6252 WHITE

Version Number 1.0 Revision Date 08/20/2003 Page 1 of 6 Print Date 11/12/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	VBX3521E 30%6252 WHITE
Product code	:	FO20006013
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
1,2-Benzenedicarboxylic acid, butyl	85-68-7	10 - 30
phenylmethylester		
Titanium dioxide	13463-67-7	1 - 5

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation Ingestion Eyes Skin	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Particulates, like other inert materials can be mechanically irritating.</li> <li>Experience shows no unusual dermatitis hazard from routine handling.</li> </ul>
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

## MATERIAL SAFETY DATA SHEET VBX3521E 30%6252 WHITE

Version Number 1.0 Revision Date 08/20/2003 Page 2 of 6 Print Date 11/12/2011

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not relevant</li> <li>Carbon dioxide blanket, water spray, dry powder, foam.</li> </ul>
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. Processing fume



## MATERIAL SAFETY DATA SHEET VBX3521E 30%6252 WHITE

Version Number 1.0 Revision Date 08/20/2003

Page 3 of 6 Print Date 11/12/2011

condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.

Storage

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection	: No personal respiratory protective equipment normally require dusty conditions occur wear appropriate respiratory protection	
Eye/Face Protection	: Safety glasses with side-shields.	
Hand protection	: Protective gloves.	
Skin and body protection	: Long sleeved clothing.	
Additional Protective Measures	: Safety shoes.	
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety p Wash hands before breaks and at the end of workday.	practice.
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provid appropriate exhaust ventilation at machinery.	de

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form
Appearance
Color
Odor
Melting point/range
<b>Boiling Point:</b>
Water solubility

: Solid powder, granular : WHITE : : Very faint : Not determined : Not applicable : Insoluble

Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pН

Not applicable. : Not determined : Not determined : Not applicable : : Not applicable

: Not applicable

#### **10. STABILITY AND REACTIVITY**

Stability

: Stable.

Hazardous Polymerization

Will not occur. :



## MATERIAL SAFETY DATA SHEET VBX3521E 30%6252 WHITE

Version Number 1.0 Revision Date 08/20/2003 Page 4 of 6 Print Date *11/12/2011* 

Conditions to avoid	:	To avoid thermal decomposition, do not overheat. Keep away from oxidizing agents and open flame.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
85-68-7	1,2-Benzenedicarboxylic	Irritant	Eyes, Skin.
	acid, butyl		
	phenylmethylester		
		Systemic effects	Liver, reproductive system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

### LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

Γ	CAS-No.	Chemical Name	Route	Value	Species
	85-68-7	1,2-Benzenedicarboxylic acid, butyl phenylmethylester	Oral LD50 Dermal LD50	2,330 mg/kg > 10 gm/kg	rat rabbit

		12	. ECOLOGICAL INFORMATION	]
Per	rsistence and degradability	:	Not readily biodegradable.	
En	vironmental Toxicity	:	Adverse ecological impact is not known or expected under normal use.	
Bio	oaccumulation Potential	:	No data available.	
Ad	lditional advice	:	No data available.	
		13	3. DISPOSAL CONSIDERATIONS	
Pro	oduct	:	Where possible, recycling is preferred to disposal or incineration. The	

PolyOne.

## MATERIAL SAFETY DATA SHEET VBX3521E 30%6252 WHITE

sion Number 1.0 ision Date 08/20/2003				Page 5 Print Date 11/12/2
	classifi	cation, transporta	ial has the responsibil tion and disposal in ac provincial and local re	cordance with
Contaminated packaging	has the and dis	responsibility for	hen possible. The gen proper waste classific ce with applicable fed	
	14. TRAN	NSPORT INFOR	RMATION	
U.S. DOT Classification	: Not reg	gulated for transpo	ortation.	
ICAO/IATA	: Not reg	gulated for transpo	ortation.	
IMO / IMDG	-	gulated for transpo		
		LATORY INFO		
	13. KEOU			
US Regulations:				
OSHA Status	: Classifi	ied as hazardous l	based on components.	
TSCA Status			product are listed on or	exempt from the TSCA
	Invento	-		
US. EPA CERCLA Hazard	ous Substances (4	40 CFR 302)		
Chemical Name	CAS-No.	% in Product	RQ for component	RQ for Mixture/Product
1,2-Benzenedicarb oxylic acid, butyl phenylmethylester	85-68-7	21.6206	100 lbs	463 LB
California Propositio 65		IING! This produ		l known to the State of
SARA Title III Section 302	Extremely Haza	rdous Substance		
Not applicable				
SARA Title III Section 313	Toxic Chemical	s:		
Not applicable				
Canadian Regulations:				

PolyOne

## MATERIAL SAFETY DATA SHEET VBX3521E 30%6252 WHITE

Version Number 1.0 Revision Date 08/20/2003 Page 6 of 6 Print Date 11/12/2011

National Pollutant Release Inventory (NPRI) Chemical Name		CAS-No.	Weight %	NPRI ID#	
1,2-Benzenedicarboxylic acid, butyl		85-68-7	21.62	37	
phenylmethylester					
WHMIS Classification	: D2B				
WHMIS Ingredient Disc	losure List				
CAS-No. 85-68-7					
DSL		All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.			
ional Inventories:					
Australia AICS	: Listed.	Listed.			
China IECS	: Listed.				
Europe EINECS	: Not determi	Not determined.			
Japan ENCS	: Not determi	Not determined.			
Korea KECI	: Not determi	Not determined.			
Philippines PICCS	: Listed.				

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.