PolvOne

MATERIAL SAFETY DATA SHEET FK101SL MSM-SL DARK BEIGE-FR

Version Number 1.3 Revision Date 10/01/2007 Page 1 of 7 Print Date 12/1/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	FK101SL MSM-SL DARK BEIGE-FR
Product code	:	FO20006352
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Azodicarbonamide	123-77-3	1 - 5
Antimony trioxide	1309-64-4	1 - 5
Calcium carbonate	1317-65-3	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET FK101SL MSM-SL DARK BEIGE-FR

Version Number 1.3 Revision Date 10/01/2007 Page 2 of 7 Print Date 12/1/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 No data available No data available Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE

PolyOne.

MATERIAL SAFETY DATA SHEET FK101SL MSM-SL DARK BEIGE-FR

Version Number 1.3 Revision Date 10/01/2007		Page 3 of 7 Print Date 12/1/2011
Handling	:	Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.
8. EXI	POSUE	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

Components	Value	Exposure time	ime Exposure type	
Antimony trioxide	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odour
- : liquid: Viscous, liquid: BROWN: Very faint
- Evaporation rate Specific Gravity Bulk density Vapour pressure
- Not establishedNot determinedNot applicableNot determined

MATERIAL SAFETY DATA SHEET FK101SL MSM-SL DARK BEIGE-FR

Version Number 1.3 Revision Date 10/01/2007

Melting point/range Boiling Point: Water solubility	:	Not applicable Not applicable Immiscible	Vapour density pH	Not determinedNot applicable
		10. STABILITY AND	REACTIVITY	
Stability		: Stable.		
Hazardous Polymerization		: Will not occur.		
Conditions to avoid		: Keep away from ox decomposition, do r	idizing agents and open flanot overheat.	ame. To avoid thermal
Incompatible Materials		-	trong acids and oxidizing a lymers and acetal copolyn	•
Hazardous decomposition products		(NOx), hydrogen ch smoke are all possil degradation. As a g after one hour at 17	D2), carbon monoxide (CO aloride (HCl), other hazard ble. Prolonged heating ma general rule of thumb, degr 7 °C (350 °F), after 10 mir ss at 232 °C (450 °F).	ous materials, and y result in product adation begins to occur
		TOTION		

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
123-77-3	Azodicarbonamide	sensitizer	Respiratory system.
1309-64-4	Antimony trioxide	Systemic effects	Eyes, Respiratory system.
		sensitizer	Skin.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
123-77-3	Azodicarbonamide	LC50	200 mg/l	rat
		Oral LD50	> 6,400 mg/kg	rat
		Dermal LD50	> 2,000 mg/kg	rabbit
1309-64-4	Antimony trioxide	Oral LD50	> 34,600 mg/kg	rat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

Page 4 of 7 Print Date 12/1/2011

MATERIAL SAFETY DATA SHEET FK101SL MSM-SL DARK BEIGE-FR

Version Number 1.3 Revision Date 10/01/2007 Page 5 of 7 Print Date 12/1/2011

CAS-No.	Chemical Name	OSHA	IARC	NTP
1309-64-4	Antimony trioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Azodicarbonamide 123-77-3 Sensitizer to the respiratory system with repeated minimal inhalation. While no chronic health problems have been identified, individuals with respiratory problems should avoid inhalation exposure to this material.

Additional Health Hazard Information:

Antimony trioxide 1309-64-4 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: No data available
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. Th generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.

PolyOne.

MATERIAL SAFETY DATA SHEET FK101SL MSM-SL DARK BEIGE-FR

ersion Number 1.3 Page 6 of evision Date 10/01/2007 Print Date 12/1/201						Page 6 of 7 ate 12/1/2011						
					-							
ICAO/IATA (air) :	Refer to specific	regulation.										
IMO / IMDG (maritime) :	IMO / IMDG (maritime) : Refer to specific regulation.											
15.	15. REGULATORY INFORMATION											
LIC Degulations:												
US Regulations:												
OSHA Status :	Classified as haz	ardous base	d on con	nponents.								
TSCA Status :	All components Inventory.	of this prod	uct are li	sted on or	exempt fro	m the TSCA						
US. EPA CERCLA Hazardous Subst	tances (40 CFR 3	02)										
Not applicable												
-	WARNING! Th California to cau	-	ontains a	a chemica	l known to	the State of						
SARA Title III Section 302 Extreme	ly Hazardous Sut	ostance										
Unless specific chemicals are identified	ied under this sec	tion, this pr	oduct is	Not Appl	icable unde	r this regulation						
SARA Title III Section 313 Toxic Ch	nemicals:											
Unless specific chemicals are identified	ied under this sec	tion, this pr	oduct is	Not Appli	icable unde	r this regulation						
Chemical Name					Veight %							
ANTIMONY COMPOUNDS		13	09-64-4	1	.00 - 5.00							
Canadian Regulations:												
National Dallatant Dalaasa Ju												
National Pollutant Release Inv Chemical Name	ventory (NPRI)	CAS-No.		Weight %	6 NP	RI ID#						
Antimony trioxide												
Minimulty aroundsNot Available0.10 - 1.00241												
WHMIS Classification :	D2A											
WHIMIC Loss Prove D'	- T :											
w HMIS Ingredient Disclosure	e List					WHMIS Ingredient Disclosure List						

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET FK101SL MSM-SL DARK BEIGE-FR

Version Number 1.3 Revision Date 10/01/2007	Page 7 of 7 Print Date 12/1/2011
CAS-No. 1309-64-4 DSL	All of the components of this product are listed on the Canadian Inventories or are exempt. However, at least one component of this product is on the Canadian Non-Domestic Substances List (NDSL). Quantity use in Canada is restricted by regulations.
National Inventories:	
Australia AICS	Not determined
China IECS	Not determined
Europe EINECS	Listed
Japan ENCS	Not determined
Korea KECI	Not determined
Philippines PICCS	Not determined
	16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.